OCT 8 '86

483-E-1

EP 42:M56/7

United States Environmental Protection Agency

Office of Air Quality Planning and Standards Research Triangle Park NC 27711

EPA-450/3-85-015
June 1985

Air

EPA

# Survey of Methylene Chloride Emission Sources

206
COMPLETED

ORIGINAL

BEST COPY AVAILABLE

NESHAP

EPA-450/3-85-015

# Survey of Methylene Chloride Emission Sources

Emission Standards and Engineering Division

U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Air and Radiation
Office of Air Quality Planning and Standards
Research Triangle Park, NC 27711

June 1985

BEST COPY AVAILABLE

I

This report has been reviewed by the Emisson Standards and Engineering Division of the Office of Air Quality Planning and Standards, EPA, and approved for publication. Mention of trade names or commercial products is not intended to constitute endorsement or recommendation for use. Copies of this report are available through the Library Services Office (MD-35), U.S. Environmental Protection Agency, Research Triangle Park, N.C. 27711, or from National Technical Information Services, 5285 Port Royal Road, Springfield, Virginia 22161.



BEST COPY AVAILABLE

TABLE OF CONTENTS


| | | |
|---|---|---|
| TABLE OF CONTENTS | | iii |
| LIST OF TABLES | | viii |
| LIST OF FIGURES | | x |
| Chapter | | Page |
| 1.0 | INTRODUCTION AND SUMMARY | 1-1 |
| | 1.1 INTRODUCTION | 1-1 |
| | 1.2 SUMMARY | 1-2 |
| | 1.2.1 MC Emission Source Categories | 1-2 |
| | 1.2.2 Emission Estimates | 1-3 |
| | 1.2.3 Additional Control of MC Emissions | 1-6 |
| | 1.2.4 Regulatory Requirements | 1-7 |
| | 1.3 REFERENCES | 1-10 |
| 2.0 | METHYLENE CHLORIDE PRODUCTION | 2-1 |
| | 2.1 QUANTITIES PRODUCED AND MANUFACTURERS | 2-1 |
| | 2.2 PRODUCTION PROCESSES | 2-3 |
| | 2.2.1 Direct Chlorination of Methane | 2-3 |
| | 2.2.2 Hydrochlorination of Methanol | 2-4 |
| | 2.3 CURRENT EMISSIONS AND CONTROLS | 2-4 |
| | 2.4 COST OF ADDITIONAL CONTROLS | 2-19 |
| | 2.4.1 Control of Process Vent Emissions | 2-19 |
| | 2.4.2 Control of Equipment Leak Emissions | 2-23 |
| | 2.4.3 Control of Storage Emissions | 2-23 |
| | 2.4.4 Control of Loading Emissions | 2-24 |
| | 2.5 REFERENCES | 2-25 |
| 3.0 | OTHER CHEMICAL PLANTS | 3-1 |
| | 3.1 PROCESS DESCRIPTIONS, EMISSIONS, AND CURRENT CONTROLS | 3-1 |
| | 3.1.1 TRIACETATE FIBER PRODUCTION | 3-1 |
| | 3.1.1.1 Process Description | 3-1 |
| | 3.1.1.2 Current Emissions and Controls | 3-3 |
| | 3.1.2 POLYCARBONATE RESIN | 3-13 |
| | 3.1.2.1 Process Description | 3-13 |
| | 3.1.2.2 Current Controls and Emissions | 3-13 |
| | 3.1.3 RUBBER CEMENT MANUFACTURING | 3-19 |
| | 3.1.3.1 Current Emissions and Controls | 3-19 |
| | 3.1.4 RUBBER ACCELERATOR MANUFACTURING | 3-20 |
| | 3.1.4.1 Current Emissions and Controls | 3-20 |




BEST COPY AVAILABLE

TABLE OF CONTENTS (Continued)


| Chapter | | Page |
|---|---|---|
| | 3.1.5 INSULATING MATERIALS MANUFACTURE | 3-22 |
| | 3.1.5.1 Current Emissions and Controls | 3-22 |
| | 3.1.6 BAYGON[R] 1.5 MANUFACTURING | 3-22 |
| | 3.1.6.1 Current Emissions and Controls | 3-23 |
| | 3.1.7 SPECIALTY CHEMICALS | 3-23 |
| | 3.1.7.1 Process Description | 3-23 |
| | 3.1.7.2 Current Emissions and Controls | 3-24 |
| | 3.1.8 UNIDENTIFIED PRODUCTION PROCESSES | 3-24 |
| | 3.1.8.1 Current Emissions and Controls | 3-25 |
| | 3.1.9 VINYL CHLORIDE MONOMER | 3-28 |
| | 3.1.9.1 Process Description | 3-28 |
| | 3.1.9.2 Current Emissions and Controls | 3-28 |
| | 3.1.10 PLASTICS PRODUCTION | 3-28 |
| | 3.1.10.1 Current Emissions and Controls | 3-28 |
| | 3.2 COST OF ADDITIONAL CONTROL | 3-30 |
| | 3.2.1 Control of Process Vent Emissions | 3-31 |
| | 3.2.2 Control of Equipment Leaks | 3-31 |
| | 3.2.3 Control of Storage Emissions | 3-36 |
| | 3.3 REFERENCES | 3-37 |
| 4.0 | SOLVENT DEGREASING OPERATIONS | 4-1 |
| | 4.1 INDUSTRY DESCRIPTION | 4-1 |
| | 4.2 DEGREASING EQUIPMENT | 4-2 |
| | 4.3 EMISSIONS FROM DEGREASING OPERATIONS | 4-3 |
| | 4.4 EMISSIONS CONTROL | 4-5 |
| | 4.5 COST OF EMISSIONS CONTROL | 4-8 |
| | 4.6 REGULATORY REQUIREMENTS | 4-14 |
| | 4.7 REFERENCES | 4-15 |
| 5.0 | PHOTORESIST STRIPPING OPERATIONS | 5-1 |




BEST COPY AVAILABLE

TABLE OF CONTENTS (Continued)


| Chapter | | Page |
|---|---|---|
| | 5.1 INDUSTRY DESCRIPTION | 5-1 |
| | 5.2 EMISSIONS AND CONTROL TECHNIQUES | 5-2 |
| | 5.3 REGULATORY REQUIREMENTS | 5-3 |
| | 5.4 REFERENCES | 5-5 |
| 6.0 | FOAM MANUFACTURING | 6-1 |
| | 6.1 INDUSTRY DESCRIPTION | 6-1 |
| | 6.2 CURRENT EMISSIONS AND CONTROLS | 6-2 |
| | 6.3 REFERENCES | 6-4 |
| 7.0 | PHARMACEUTICAL MANUFACTURING | 7-1 |
| | 7.1 INDUSTRY DESCRIPTION | 7-1 |
| | 7.2 CURRENT EMISSIONS AND CONTROLS | 7-2 |
| | 7.3 REFERENCES | 7-4 |
| 8.0 | PESTICIDE MANUFACTURING | 8-1 |
| | 8.1 INDUSTRY DESCRIPTION | 8-1 |
| | 8.2 EMISSIONS AND CONTROLS | 8-3 |
| | 8.3 REFERENCES | 8-4 |
| 9.0 | DISTRIBUTION FACILITIES | 9-1 |
| | 9.1 EMISSIONS FROM DISTRIBUTION FACILITIES | 9-1 |
| | 9.2 REGULATORY REQUIREMENTS | 9-2 |
| | 9.3 REFERENCES | 9-4 |
| 10.0 | ADDITIONAL EMISSION SOURCES OF MC | 10-1 |
| | 10.1 AEROSOLS | 10-1 |
| | 10.2 PAINT REMOVERS | 10-3 |




BEST COPY AVAILABLE

TABLE OF CONTENTS (Continued)


| Chapter | | Page |
|---|---|---|
| | 10.3 PHOTOGRAPHIC FILM PROCESSING. . . . . | 10-3 |
| | 10.4 FOOD PROCESSING INDUSTRY. . . . . | 10-3 |
| | 10.5 GENERAL MISCELLANEOUS . . . . . | 10-4 |
| | 10.6 REFERENCES. . . . . | 10-5 |
| APPENDIX A: | METHODS USED FOR ESTIMATING STORAGE TANK AND EQUIPMENT LEAK EMISSIONS . . . . . | A-1 |
| | A.1 EMISSION FACTORS FOR FIXED-ROOF TANKS . . . . . | A-1 |
| | A.1.1 Emission Equations . . . . . | A-1 |
| | A.1.2 Parameter Values and Assumptions . . . . | A-1 |
| | A.1.3 Sample Calculation . . . . . | A-2 |
| | A.2 EMISSION FACTORS FOR INTERNAL FLOATING ROOF STORAGE TANKS. . . . . | A-4 |
| | A.2.1 Emission Equations . . . . . | A-4 |
| | A.2.2 Parameter Values and Assumptions . . . . | A-4 |
| | A.2.3 Sample Calculation . . . . . | A-7 |
| | A.3 EQUIPMENT LEAK EMISSIONS-SAMPLE CALCULATIONS. . | A-10 |
| | A.4 REFERENCES. . . . . | A-12 |
| APPENDIX B: | METHODS FOR ESTIMATING EMISSION CONTROL COSTS. . . . | B-1 |
| | B.1 PROCESS VENT EMISSIONS CONTROL COST ESTIMATION. | B-1 |
| | B.2 COST CALCULATIONS FOR INSTALLING INTERNAL FLOATING ROOFS IN FIXED ROOF TANKS. . . . . | B-14 |
| | B.2.1 Capital Cost . . . . . | B-14 |
| | B.2.2 Annual Cost. . . . . | B-15 |
| | B.2.3 MC/VOC Reduction . . . . . | B-15 |
| | B.2.4 Recovery Credits . . . . . | B-16 |
| | B.2.5 Net Annual Cost. . . . . | B-16 |
| | B.2.6 Cost Effectiveness . . . . . | B-16 |
| | B.3 COST CALCULATIONS FOR INSTALLATION OF REFRIGERATED CONDENSERS TO CONTROL STORAGE AND LOADING EMISSIONS . . . . . | B-16 |
| | B.3.1 Capital Cost . . . . . | B-17 |
| | B.3.2 Annual Cost. . . . . | B-17 |
| | B.3.3 MC/VOC Emission Reduction. . . . . | B-17 |
| | B.3.4. Recovery Credit. . . . . | B-18 |




BEST COPY AVAILABLE

TABLE OF CONTENTS (Continued)


| Chapter | | Page |
|---|---|---|
| | B.3.5 Net Annual Cost. . . . . | B-18 |
| | B.3.6 Cost Effectiveness . . . . . | B-18 |
| | B.4 SAMPLE CALCULATIONS FOR EQUIPMENT LEAK CONTROL COSTS . . . . . | B-18 |
| | B.5 REFERENCES. . . . . | B-22 |
| APPENDIX C: | SUMMARY OF EXISTING STATE AND FEDERAL REGULATIONS AFFECTING METHYLENE CHLORIDE EMISSION SOURCES . . . . | C-1 |
| | C.1 EXISTING STATE REGULATIONS . . . . . | C-1 |
| | C.1.1 Introduction. . . . . | C-1 |
| | C.1.2 General State VOC Regulations for Solvent Use . . . . . | C-1 |
| | C.1.3 Prevention of Significant Deterioration Regulations . . . . . | C-3 |
| | C.1.4 State Regulations Affecting Chemical Production. . . . . | C-3 |
| | C.2 EXISTING FEDERAL REGULATIONS . . . . . | C-3 |
| APPENDIX D: | MATERIAL BALANCE FOR MC EMISSIONS OPERATIONS. . . . . | D-1 |
| | D.1 MATERIAL BALANCE . . . . . | D-1 |
| | D.2 NATIONAL EMISSION REDUCTION CALCULATIONS . . . . | D-3 |
| | D.3 PHOTORESIST STRIPPING EMISSION FACTOR. . . . . | D-6 |
| | D.4 REFERENCES . . . . . | D-7 |
| APPENDIX E: | EMISSIONS FROM DISTRIBUTIONS FACILITIES . . . . . | E-1 |




BEST COPY AVAILABLE

LIST OF TABLES


| Table | | Page |
|---|---|---|
| 1-1 | EMISSIONS FROM THE PRODUCTION AND USE OF METHYLENE CHLORIDE. . . . . | 1-4 |
| 1-2 | ACHIEVABLE MC EMISSION REDUCTION FOR ALL CHEMICAL PLANTS AND DEGREASERS AS A FUNCTION OF COST EFFECTIVENESS . . . . . | 1-8 |
| 2-1 | METHYLENE CHLORIDE PRODUCERS AND PRODUCTION CAPACITIES. . | 2-2 |
| 2-2 | TOTAL EMISSIONS FROM METHYLENE CHLORIDE PRODUCTION FACILITIES. . . . . | 2-7 |
| 2-3 | CURRENT CONTROLS AND ESTIMATED EMISSIONS AT FACILITIES PRODUCING METHYLENE CHLORIDE . . . . . | 2-9 |
| 2-4 | COST OF ADDITIONAL CONTROLS AT MC PRODUCTION FACILITIES . | 2-20 |
| 2-5 | ESTIMATED MC EMISSION REDUCTIONS FOR MC PRODUCTION FACILITIES AS A FUNCTION OF COST EFFECTIVENESS. . . . . | 2-22 |
| 3-1 | TOTAL EMISSIONS FROM CHEMICAL PLANTS USING METHYLENE CHLORIDE PRODUCTION FACILITIES . . . . . | 3-2 |
| 3-2 | ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHORIDE IN PRODUCTION . . . . . | 3-5 |
| 3-3 | COST OF ADDITIONAL CONTROLS AT CHEMICAL PLANTS USING MC IN PRODUCTION . . . . . | 3-32 |
| 3-4 | ESTIMATED MC EMISSION REDUCTIONS FOR OTHER CHEMICAL PLANTS AS A FUNCTION OF COST EFFECTIVENESS . . . . . | 3-35 |
| 4-1 | 1983 MC EMISSIONS FROM DEGREASING OPERATIONS, BY INDUSTRY | 4-4 |
| 4-2 | 1983 METHYLENE CHLORIDE EMISSIONS FROM DEGREASING OPERATIONS, BY STATE. . . . . | 4-6 |
| 4-3 | EXAMPLE CONTROL TECHNIQUES FOR DEGREASERS . . . . . | 4-7 |
| 4-4 | RETROFIT CONTROL COSTS FOR COLD CLEANERS. . . . . | 4-9 |
| 4-5 | RETROFIT CONTROL COSTS FOR OPEN TOP VAPOR DEGREASERS. . . . . | 4-10 |
| 4-6 | RETROFIT CONTROL COSTS FOR CONVEYORIZED DEGREASERS . . . . | 4-12 |




BEST COPY AVAILABLE

LIST OF TABLES (Continued)


| Table | | Page |
|---|---|---|
| 5-1 | 1983 METHYLENE CHLORIDE EMISSIONS FROM PHOTORESIST STRIPPING OPERATIONS, BY STATE. . . . . | 5-4 |
| 6-1 | 1983 MC EMISSIONS FROM FOAM MANUFACTURING, BY STATE . . . | 6-3 |
| 8-1 | 1983 CONSUMPTION OF METHYLENE CHLORIDE IN PESTICIDE MANUFACTURING . . . . . | 8-2 |
| 9-1 | SUMMARY OF MAJOR METHYLENE CHLORIDE DISTRIBUTORS. . . . . | 9-3 |
| 10-1 | ADDITIONAL USES OF METHYLENE CHLORIDE IN 1983 . . . . . | 10-2 |
| A-1 | PAINT FACTORS FOR FIXED-ROOF TANKS. . . . . | A-3 |
| A-2 | TYPICAL NUMBER OF COLUMNS AS A FUNCTION OF TANK DIAMETERS | A-5 |
| A-3 | SUMMARY OF DECK FITTING LOSS FACTORS ($K_f$) AND TYPICAL NUMBER OF FITTINGS ($N_f$) . . . . . | A-8 |
| B-1 | TOTAL INSTALLED CAPITAL COST AS A FUNCTION OF VENT STREAM FLOW RATE. . . . . | B-2 |
| B-2 | ADDITIONAL DUCT COST. . . . . | B-3 |
| B-3 | PIPE RACK COST. . . . . | B-4 |
| B-4 | OPERATING FACTORS FOR EACH DESIGN CATEGORY. . . . . | B-5 |
| B-5 | ANNUALIZED COST FACTORS . . . . . | B-6 |
| B-6 | SAMPLE CALCULATION FOR INCINERATOR COSTING. . . . . | B-7 |
| B-7 | COST CONVERSION FACTORS . . . . . | B-13 |
| B-8 | CONTROL TECHNIQUES AND COST FOR CONTROLLING EQUIPMENT LEAK EMISSION SOURCES. . . . . | B-19 |
| C-1 | GENERAL STATE VOC REGULATIONS FOR PHOTOCHEMICAL SOLVENTS. | C-2 |
| C-2 | STATE REGULATIONS AFFECTING CHEMICAL PRODUCTION FACILITIES EMITTING METHYLENE CHLORIDE . . . . . | C-4 |
| C-3 | SUMMARY OF FEDERAL REGULATIONS AFFECTING VOLATILE ORGANIC COMPOUND EMITTING SOURCES . . . . . | C-5 |




BEST COPY AVAILABLE

## LIST OF FIGURES


| Figure | | Page |
|---|---|---|
| 2-1 | Process flow diagram for the production of methylene chloride and co-products by the direct chlorination of methane. . . . . | 2-5 |
| 2-2 | Process flow diagram for the production of methylene chloride and co-products by the hydrochlorination of methanol . . . . . | 2-6 |
| 3-1 | Process flow diagram for the production of triacetate fiber . . . . . | 3-4 |
| 3-2 | Process flow diagram for the production of polycarbonate resin . . . . . | 3-14 |




BEST COPY AVAILABLE

# 1.0 INTRODUCTION AND SUMMARY

## 1.1 INTRODUCTION

This document identifies the sources and locations of methylene chloride (MC) emissions, estimates total 1983 production and consumption volumes, estimates emission levels, identifies applicable control techniques for each source, and estimates the cost effectiveness of controlling emissions for selected sources. The information collected in this source assessment study will also be used by the U.S. Environmental Protection Agency (EPA) to estimate human exposure to MC.

Information for this document was acquired from various sources. Background information, such as previous EPA documents and other published literature, was reviewed in an attempt to identify the producers of MC and the major applications. Four companies producing MC at six facilities were identified. Also, two companies producing polycarbonate resins and one company producing triacetate fibers were identified. Letters were sent to these seven companies under the authority of Section 114 of the Clean Air Act requesting information concerning MC emissions, emission levels, and control techniques for all possible emission sources associated with the production, storage, and use of MC in the calendar year 1983. General information such as production volumes and total sales/purchase data were also requested in order to verify the completeness of the submitted information. The production and sales/purchase information was requested to be treated as confidential and is not discussed in this report. For each process unit making or consuming MC, detailed information was requested on the following emission types: process vent emissions, equipment leaks, equipment opening losses, raw material/product storage emissions, loading/handling emissions, and secondary emissions (i.e. emissions as a result of treating or disposing of plant waste streams). The companies were asked only to estimate these emissions. No testing was required specifically for this information request.



BEST COPY AVAILABLE

Plant trips were taken to Vulcan Chemicals in Geismar, Louisiana; Dow Chemical U.S.A. in Plaquemine, Louisiana; and General Electric in Mt. Vernon, Indiana to gain familiarity with the processes, emission sources, and emission controls at these facilites. Meetings were held with plant representatives to discuss operating procedures, the process equipment used, potential emission sources, and methods of emissions control.

The predominant uses of MC are as a constituent in aerosols and paint removers. Since aerosols and paint removers are largely consumer products, it was assumed that associated emissions are proportional to general population distribution in the U.S. Other significant uses of MC that were identified include solvent degreasing, chemical production, foam manufacturing, pharmaceutical manufacturing, pesticide manufacturing and photoresist stripping. Information for chemical plants was obtained directly through Section 114 requests. For the other significant MC use categories, no attempt was made to identify the locations of all facilities using MC. However, information was obtained from the Halogenated Solvents Industry Alliance (HSIA), a trade group representing the producers of MC and other halogentated solvents, regarding the total amount of MC used in 1983 for all known applications. Using HSIA and other available information, emission levels in 1983 were estimated for each application.

## 1.2 SUMMARY

### 1.2.1 MC Emission Source Categories

Methylene chloride is produced by four companies at six plants in the United States. The estimated total 1983 production volume of MC was 240,000 Mg[1]. Two processes are used to produce MC: (1) hydrochlorination of methanol, and (2) chlorination of methane. In 1983, the disposition of MC was as follows: aerosols (22 percent), paint removers (28 percent), degreasing operations (9 percent), foam manufacturing (7 percent), pharmaceutical manufacturing (6 percent), photoresist stripping operations (5 percent), film processing (3 percent), food processing (1 percent), and pesticide manufacturing (1 percent).



BEST COPY AVAILABLE

Additional applications include general miscellaneous uses such as a solvent in the printing industry, as a thinning agent for adhesives, as a solvent in cleaning solutions, and as a solvent or reactant in the chemical processing industry. Individual consumption levels are not known for these general uses. Their combined consumption was 5 percent of total use.

Emission estimates have been made in this study for the following categories: MC production facilities, chemical plants, degreasing operations, photoresist stripping operations, foam manufacturing, pharmaceutical manufacturing, pesticide manufacturing, distribution facilities, aerosols, paint removers, photographic film processing, food processing, and the general miscellaneous applications.

### 1.2.2 Emission Estimates

The total emissions from MC production and use in 1983 are estimated to be 197,500 Mg/yr. The largest sources of MC emissions were paint removers (62,000 Mg/yr), aerosols (52,900 Mg/yr), degreasing operations (17,700 Mg/yr), foam manufacturing (14,200 Mg/yr), and photoresist stripping operations (6,800 Mg/yr). The source categories and emissions are presented in Table 1-1.

Methylene chloride emissions from MC production processes are estimated to be 770 Mg/yr. MC emissions from miscellaneous chemical production processes using MC are estimated to be 10,700 Mg/yr. The chemical products of these processes include triacetate fibers, polycarbonate resins, plastics, rubber cement, rubber accelerators, insulating materials, specialty chemicals, vinyl chloride, and BAYGON$^{R}$ 1.5 (pesticide). The estimate of total emissions from MC producing plants and other chemical plants was obtained from information provided by these facilities in response to Section 114 requests. These plants provided emission estimates from process vents (estimated at full capacity), loading/handling operations, equipment opening losses, pressure relief valve discharges, and secondary streams. The chemical plants also provided counts of all equipment (such as pumps, valves, and flanges) in MC service and data on the number and types of product/raw



BEST COPY AVAILABLE

TABLE 1-1. EMISSIONS IN 1983 FROM THE PRODUCTION AND USE OF METHYLENE CHLORIDE

| Emission Source | Production/Consumption (Mg/yr) | Emissions (Mg/yr) |
|---|---|---|
| MC Production | 240,000 | 770 |
| Other Chemical Production | N/A | 10,700[b] |
| Degreasing Operations | 21,300 | 17,700 |
| Photoresist Stripping Operations | 11,900 | 6,800 |
| Foam Manufacturing | 14,200 | 14,200 |
| Pharmaceutical Manufacturing | 13,200 | 5,700 |
| Pesticide Manufacturing | 2,700 | 2,700 |
| Distribution Facilities | 218,000[a] | 500 |
| Aerosols | 52,900 | 52,900 |
| Paint Removers | 62,000 | 62,000 |
| Photographic (film processing) | 8,100 | 8,100 |
| Food Processing | 3,330 | 3,300 |
| Miscellaneous | 12,100 | 12,100 |
| TOTAL | - | 197,500 |

[a]Estimated amount of MC sold through distribution.
[b]Based on update of preliminary information provided by chemical plants.

N/A = Not Available



BEST COPY AVAILABLE

material storage tanks containing MC. Total volatile organic compound (VOC) emissions from equipment leaks were calculated by applying the Synthetic Organic Chemical Manufacturing Industry (SOCMI) VOC equipment leak emission factors to the equipment counts.[2] MC emissions were estimated in a similar manner except that the fraction of MC in the stream for each piece of equipment was applied to the calculated VOC emissions. Emissions from storage tanks were estimated by using AP-42 equations and storage tank data supplied by each company.[3] Methods for estimating these emissions are described in Appendix A.

Methylene chloride emissions from degreasing operations were estimated to be 17,700 Mg in 1983. Degreasing emission estimates were made using HSIA information on 1983 MC consumption in various degreasing applications and available emission factors. The HSIA indicated that MC was used as a degreasing solvent in five major industry groups in 1983. These are: furniture and fixtures (Standard Industrial Classification (SIC)25), fabricated metal products (SIC 34), electric and electronic equipment (SIC 36), transportation equipment (SIC 37), and miscellaneous industries (SIC 39). Emission factors for degreasing operations were obtained from previous EPA studies.

MC emissions from photoresist stripping operations were estimated to be 6,800 Mg in 1983. Emissions were estimated using 1983 consumption data provided by HSIA and emissions factors derived for the printed circuit board manufacturing industry, in which photoresist stripping operations occur.

Almost all of the MC produced is sold through various chemical distributors. The handling and storage operations at distribution facilities located throughout the country were estimated to account for 500 Mg of TCE emissions in 1983.

Emissions of MC from foam manufacturing were estimated to be 14,200 Mg in 1983. Emission estimates were made using 1983 consumption data for foam manufacturing provided by the HSIA. It was assumed that all the MC used in foam manufacturing is emitted.



BEST COPY AVAILABLE

Emissions of MC from pharmaceutical manufacturing were estimated to be 5,700 Mg in 1983. Emissions were estimated using 1983 consumption data for pharmaceutical manufacturing provided by HSIA and an emission factor for pharmaceutical manufacturing obtained in a previous EPA study.

Emissions of MC from pesticide manufacturing were estimated to be 2,700 Mg in 1983. Emissions were estimated from 1983 consumption data for pesticide manufacturing provided by HSIA. It was assumed that all the MC consumed in pesticide manufacturing during 1983 was emitted.

Emissions of MC from photographic film processing were estimated to be 8,100 Mg in 1983. Emissions were estimated from 1983 consumption data for film processing provided by HSIA. It was assumed that all the MC consumed in photographic film processing during 1983 was emitted.

Emissions of MC from food processing were estimated to be 3,300 Mg in 1983. This estimate was based as 1983 consumption data for food processing provided by HSIA, assuming all MC consuming in food processing during 1983 was emitted.

Emissions of MC from the aggregated general miscellaneous source category were estimated to be 12,100 Mg in 1983. HSIA indicated 12,100 Mg was the consumption level of MC for the combined miscellaneous sources. It was assumed that all MC consumed in those applications is emitted.

### 1.2.3 Additional Control of MC Emissions

The cost associated with additional control of MC emissions was estimated for MC production plants, other chemical plants and degreasers. Due to the large number of degreasers, no attempt was made to develop cost estimates for each degreaser actually in use. Instead, cost estimates were developed for model degreasers. National costs and national emission reductions associated with controlling degreasers were based on model degreaser data. Specific information was provided for MC production and other chemical production facilities. This information was used to develop national costs and emission reduction estimates were made for these production facilities. The methodology for estimating control costs is presented in Appendix B.



BEST COPY AVAILABLE

Emissions of MC from chemical plants producing or using MC can be reduced by various technically feasible controls. Process vent emissions can be controlled by incineration. Equipment leak emissions can be reduced through a combination of leak detection and repair programs and application of equipment control devices. Storage tank emissions can be reduced by installation of floating roofs in fixed roof tanks. Where floating roofs are not technically feasible (i.e. horizontal tanks or extremely small diameter tanks), a refrigerated condenser can be used for control of storage emissions. Loading emissions can be controlled by venting displaced vapors to a refrigerated condenser.

Emissions of MC from degreasers can be reduced by using covers for degreasers openings, increasing degreaser freeboard area, adding freeboard chillers, providing drainage racks for parts, and installing carbon adsorbers. The methodology for estimating cost effectiveness of degreaser emission control is presented in Chapter 4.

Costs were estimated for the above control techniques for all emission sources from chemical plants and degreasers which are not presently well controlled. These costs estimates are based on the information provided in the company Section 114 responses on the emission stream and process equipment parameters and also on the data for model degreasers. It is estimated that about 11,300 Mg/yr MC emissions can be controlled by the application of control techniques on process vent, fugitive, storage tanks, and handling emissions and by application of control techniques on uncontroiled degreasers. This represents an overall emission reduction of about 39 percent over current estimated emissions from chemical production and degreasing. Table 1-2 shows the emission reduction for each emission type for various ranges of cost effectiveness.

1.2.4 Regulatory Requirements

The plants that produce MC or use it in production processes are located in 13 States: West Virginia, Texas, Louisiana, Kansas, Massachusetts, Indiana, New York, South Carolina, Pennsylvania, California Ohio, Missouri, and Michigan. Emissions from these existing chemical production facilities are not controlled by Federal regulations



BEST COPY AVAILABLE

BEST COPY AVAILABLE

TABLE 1-2. ACHIEVABLE MC EMISSION REDUCTION FOR ALL CHEMICAL PLANTS AND DEGREASERS AS A FUNCTION OF COST EFFECTIVENESS

| Cost Effectiveness Range, $/Mg of VOC | Nationwide MC Emission Reduction, Mg/Yr | | | | | |
|---|---|---|---|---|---|---|
| | Process Vents | Equipment Leak | Storage Tanks | Loading | Degreasing | Total |
| Credit | 864 | - | 182 | - | - | 1,050 |
| 0-500 | 1,940 | 339 | 47.8 | - | 4,130 | 6,460 |
| 501-1000 | - | 69.7 | 10.9 | - | - | 81 |
| 1001-2000 | 82.4 | 25.4 | 33.6 | 51.9 | 2,460 | 2,650 |
| 2001-5000 | 132 | 1.2 | 18.3 | 73.2 | - | 225 |
| > 5000 | 851 | - | 13.8 | 16.9 | - | 882 |
| TOTAL | 3,870 | 435 | 307 | 142 | 6,590 | 11,300 |

such as the new source performance standards (NSPS) for volatile organic compounds (VOC) in the synthetic organic chemical manufacturing industry (SOCMI) because these regulations are designed to cover new, modified, or reconstructed sources.

The emissions of MC from chemical plants are controlled in only two (Pennsylvania, and Michigan) of the 11 States where MC is produced or used in production processes. MC is exempt from VOC regulations in the other States because of its negligible photochemical reactivity with the exception of Massachusetts where MC emissions from specific sources such as metal coating are regulated. However, Massachusetts regulations do not impact chemical plants.

Michigan has adopted regulations controlling storage of organic compounds having a true vapor pressure between 1.5 psia and 11 psia in existing stationary vessels of more than 40,000 gallon capacity. The vapor pressure of MC at 20°C (68°F) is approximately 6.75 psia. The regulations require that the storage tank is a pressure tank, be equipped with a floating cover with closure seal or seals, or be equipped with a vapor recovery system capable of 90 percent recovery. Pennsylvania regulations require storage tanks with a volume below 40,000 gallons to be equipped with pressure relief devices; for tanks above 40,000 gallons the regulations require a floating roof and vapor recovery system.

VOC emissions from loading/handling emissions are regulated by Michigan. The state regulation requires loading facilities handling 5,000 gal/year or more of VOC (with a true vapor pressure equal to 1.5 psia) to have submerged fill pipes.

There are no Federal regulations for MC emissions from degreasing operations. A CTG for organic solvent cleaners has been issued by EPA establishing RACT guidelines that have been used by State agencies to develop SIPs. Thirty-two States and the District of Columbia have adopted RACT for use of MC in degreasing operations. Eighteen States have not adopted any regulations. Further details on State regulations are presented in Appendix C.



BEST COPY AVAILABLE

## 1.3 REFERENCES


1. Mannsville Chemical Products. Chemical Products Synopsis - Methylene chloride. Cortland, New York. November 1984.

2. U. S. Environmental Protection Agency. Benzene Fugitive Emissions-Background Information Document. Research Triangle Park, North Carolina. Publication No. EPA-450/3-80-0326. June 1982. Appendix A. 1982.

3. Compilation of Air Pollutant Emission Factors, 3rd Edition. U. S. Environmental Protection Agency, Office of Air Quality Planning and Standards, Monitoring and Data Analysis Division. Research Triangle Park, N.C. January 1984.


BEST COPY AVAILABLE

# 2.0 METHYLENE CHLORIDE PRODUCTION

This chapter presents the emissions and controls associated with the production of methylene chloride (MC) at the six production facilities in the United States. Methylene chloride is produced by the hydrochlorination of methanol at all six of these plants and by the direct chlorination of methane at one of these plants. Emission sources in MC production facilities are process vents, equipment leaks, equipment openings, relief devices, storage tanks, secondary sources, and truck, rail-car, drum, or barge loading.

## 2.1 QUANTITIES PRODUCED AND MANUFACTURERS

Methylene Chloride is currently produced by four companies at six plants. The estimated total production capacity of these plants is 358,000 Mg/yr.[1] In 1983 about 240,000 Mg of methylene chloride was produced.[1] The total imports of methylene chloride in 1983 were 20,000 Mg, and the total exports were 32,700 Mg indicating a domestic United States demand of about 228,000 Mg in 1983.[1] The producers, their capacities, and production processes are listed in Table 2-1.

Methylene Chloride consumption declined approximately 14 percent from 1979 to 1983.[1] This is because several MC end uses such as paint stripping, aerosols, and metal and plastic processing consumption levels decreased during the economic downturn. However, in 1984 MC demand level was 252,000 Mg, showing a 10.5 percent growth over 1983.[2] Also in 1984, imports increased to 30,000 Mg, 50 percent higher than in 1983.[2] The import surge upset the traditional trade surplus of U.S. MC but tightening chlorine availability in Europe is expected to drop imports in 1985.[2] Current predictions for future growth are in the 2 to 3 percent range.[1,2]



//

BEST COPY AVAILABLE

BEST COPY AVAILABLE

TABLE 2-1. METHYLENE CHLORIDE PRODUCERS AND PRODUCTION CAPACITIES

| Company | Location | Process | Capacity[a] (Mg/yr) (1984) |
|---|---|---|---|
| Diamond Shamrock Corporation | Belle, WV | Hydrochlorination of methanol | 50,000 |
| Dow Chemical U.S.A. | Freeport, TX | Hydrochlorination of methanol | 91,000 |
| | Plaquemine, LA | Hydrochlorination of methanol | 86,000 |
| LCP Chemicals | Moundsville, WV | Hydrochlorination of methanol | 36,000 |
| Vulcan Materials Co. | Geismar, LA | Hydrochlorination of methanol | 36,000 |
| | Wichita, KS | Hydrochlorination of methanol<br>Chlorination of methane | 59,000[b] |
| TOTAL | | | 358,000 |

[a]Estimated capacities from Mannsville Chemical Products Corporation.
[b]Combined capacity for both processes.

## 2.2 PRODUCTION PROCESSES

The two basic methods of methylene chloride production, direct chlorination of methane and hydrochlorination of methanol, differ primarily in the initial feedstock. Both processes produce methyl chloride as an intermediate. Methylene chloride is then produced by the direct chlorination of methyl chloride.

All six plants produce MC by the hydrochlorination of methanol. In addition, Vulcan/Wichita uses the direct chlorination of methane to produce about 33 percent of their MC output.[3]

### 2.2.1 Direct Chlorination of Methane.[4]

Methyl chloride, methylene chloride, chloroform, and carbon tetrachloride are co-produced via the direct chlorination of methane. Methane is mixed with chlorine and fed to a chlorination reactor where all four co-products are produced. The co-products are then separated by distillation. After separation the methyl chloride can be recycled to the chlorinator. The reaction conditions and the amount of methyl chloride recycled to the chlorination reactor can be controlled to yield predominantly methylene chloride. The chlorination process occurs according to the reactions:

$$\underset{\text{(methane)}}{CH_4} + \underset{\text{(chlorine)}}{Cl_2} \longrightarrow \underset{\text{(methyl chloride)}}{CH_3Cl} + \underset{\text{(hydrogen chloride)}}{HCl}$$

$$\underset{\text{(methyl chloride)}}{CH_3Cl} + \underset{\text{(chlorine)}}{Cl_2} \longrightarrow \underset{\text{(methylene chloride)}}{CH_2Cl_2} + \underset{\text{(hydrogen chloride)}}{HCl}$$

$$\underset{\text{(methylene chloride)}}{CH_2Cl_2} + \underset{\text{(chlorine)}}{Cl_2} \longrightarrow \underset{\text{(chloroform)}}{CHCl_3} + \underset{\text{(hydrogen chloride)}}{HCl}$$

$$\underset{\text{(chloroform)}}{CHCl_3} + \underset{\text{(chlorine)}}{Cl_2} \longrightarrow \underset{\text{(carbon tetrachloride)}}{CCl_4} + \underset{\text{(hydrogen chloride)}}{HCl}$$



BEST COPY AVAILABLE

The reactions are usually carried out at about 350°C to 370°C (660°F to 700°F) and at a pressure slightly above one atmosphere. The process flow diagram is shown in Figure 2-1.

2.2.2 Hydrochlorination of Methanol[4]

Methyl chloride is produced via the hydrochlorination of methanol, the reaction of hydrochloric acid with methanol in the liquid phase and in the presence of a catalyst at about 340°C (644°F). The direct chlorination of methyl chloride then produces methylene chloride and chloroform as co-products, and carbon tetrachloride as a by-product. The chlorination processes occur according to the reactions:

$$\underset{\text{(methanol)}}{CH_3OH} + \underset{\text{(hydrochloric acid)}}{HCl} \xrightarrow{\text{catalyst}} \underset{\text{liquid pnase (methyl chloride)}}{CH_3Cl} + \underset{\text{(water)}}{H_2O}$$

$$\underset{\text{(methyl chloride)}}{CH_3Cl} + \underset{\text{(chlorine)}}{Cl_2} \longrightarrow \underset{\text{(methylene chloride)}}{CH_2Cl_2} + \underset{\text{(hydrochloric acid)}}{HCl}$$

$$\underset{\text{(methylene chloride)}}{CH_2Cl_2} + \underset{\text{(chlorine)}}{Cl_2} \longrightarrow \underset{\text{(chloroform)}}{CHCl3} + \underset{\text{(hydrogen chloride)}}{HCl}$$

$$\underset{\text{(chloroform)}}{CHCl_3} + \underset{\text{(chlorine)}}{Cl_2} \longrightarrow \underset{\text{(carbon tetrachloride)}}{CCl_4} + \underset{\text{(hydrogen chloride)}}{HCl}$$

Cuprous chloride, activated charcoal, or zinc chloride on pumice is used as catalyst in the hydrochlorination reaction. A process flow diagram is shown in Figure 2-2.

2.3 CURRENT EMISSIONS AND CONTROLS

Emission sources and emission levels for each facility producing methylene chloride are summarized in Table 2-2. A more detailed discussion of emission sources including controls, and control



BEST COPY AVAILABLE

BLANK PAGE

BLANK PAGE

BLANK PAGE




Figure 2-1. Process flow diagram for the production of methylene chloride and co-products by the direct chlorination of methane.



BEST COPY AVAILABLE

COPY AVAILABLE






Figure 2-2. Process flow diagram for the production of methylene chloride and co-products by the hydrochlorination of methanol

16.

TABLE 2-2 TOTAL EMISSIONS FROM METHYLENE CHLORIDE PRODUCTION FACILITIES

| Plant/Location | 1983 Methylene Chloride Emissions (Mg/yr) | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | Process | Equipment Leaks | Relief Devices | Storage[b] | Handling | Equipment Openings | Secondary | TOTAL |
| Diamond Shamrock Belle, WV | 5.7 | 75.2 | 3.4 | 26.1 | 4.2 | 1.1 | 0.7 | 116 |
| Dow Chemical Freeport, TX | - | 87.3 | - | 18.3 | 4.2 | .05 | 0.8 | 111 |
| Dow Chemical Plaquemine, LA | - | 27.5 | .05 | 73.5 | 115 | 0.6 | .02 | 217 |
| LCP Chemicals Moundsville, WV | 84.4 | 28.5 | 0.5 | 21.1 | 23.7 | 0.9 | 6.4 | 165 |
| Vulcan Materials Geismar, LA | 0.7 | 35.5 | .01 | 19.3 | 8.2 | 0.6 | 3.9 | 68.2 |
| Vulcan Materials Wichita, KS | 12.3 | 38.1 | - | 32.2 | 6.2 | 0.8 | - | 89.6 |
| TOTAL | 103 | 292 | 4.0 | 190 | 162 | 4.1 | 11.8 | 770 |

[a]Based on equipment count provided by plants and SOCMI fugitive emission factors.

[b]Based on storage tank information provided by plants and AP-42 equations.



BEST COPY AVAILABLE

17.

efficiencies is presented below and shown in Table 2-3. Equipment leak, storage tank, and handling emissions account for the majority of the methylene chloride emissions from these facilities. Process vent, equipment opening, relief device, and secondary emissions were also reported by the six plants.

Dow Chemicals U.S.A. - Freeport, TX[5]

The production of methylene chloride by hydrochlorination of methanol at this facility resulted in total emissions of methylene chloride of 111 Mg in 1983. Equipment leaks accounted for a majority of these emissions, totalling 87.3 Mg/yr. The largest sources of equipment leaks were valves, flanges, and pressure relief devices. Emissions from valves were approximately 42 Mg/yr (48 percent of total equipment leaks). Seventeen percent of the equipment leaks were from flanges. Pressure relief devices constituted 19 percent of these emissions. Dow reported that inspection programs were in place for monitoring equipment leaks. These programs include routine inspection of equipment during each shift, a pressure vessel inspection program, an annual leak survey, and continuous corrosion rate monitoring. Since no repair frequency was reported, no control efficiency could be estimated for Dow's inspection program. Therefore, equipment leak emission estimates assume no control. This may overstate somewhat Dow's equipment leak emissions.

The Texas Air Control Board has recently promulgated regulations that will require a formal monitoring and repair program for volatile organic compound equipment leaks. The first round of monitoring must be completed by the end of 1987. The regulation will require the periodic testing of all valves in VOC service with a portable hydrocarbon meter, capping of open-ended lines and valves, monitoring of pump seals, and detailed record keeping of these practices. Methylene Chloride is excluded from these regulations and from other regulations governing volatile organic compounds in Texas because of its low photochemical reactivity. However, Dow would be covered by Texas regulations where MC streams are mixed with regulated volatile organic compounds (such as methyl chloride, chloroform, and carbon tetrachloride).



BEST COPY AVAILABLE

TABLE 2-3. CURRENT CONTROLS AND ESTIMATED EMISSIONS AT FACILITIES PRODUCING METHYLENE CHLORIDE

| Company/Location | Type of Emission/ Source | Present Controls | Reported Control Efficiency | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|
| Diamond Shamrock Belle, WV | Process | | | | |
| | o Regeneration Vent | None | 0 | 3.8 | |
| | o Vent Recovery System 1 | Condenser | 68.5 | 1.1 | |
| | o Vent Recovery System 2 | Condenser | 26.7 | 0.8 | |
| | Equipment Leaks | None | 0 | 75.2 | Visual inspection |
| | Storage | | | | |
| | o Fixed-Roof Tank | Conservation Vent Water Cooled Condenser | 62.4 | 1.8 | 15,000 gallons |
| | o Fixed-Roof Tank | Conservation Vent Water Cooled Condenser | 86.7 | 0.8 | 20,000 gallons |
| | o Fixed-Roof Tank | Conservation Vent Water Cooled Condenser | 86.7 | 0.8 | 20,000 gallons |
| | o Fixed-Roof Tank | Conservation Vent Water Cooled Condenser | 86.7 | 0.4 | 17,000 gallons |
| | o Fixed-Roof Tank | None | 0 | 0.4 | 15,000 gallons |
| | o Fixed-Roof Tank | None | 0 | 2.9 | 15,000 gallons |
| | o Fixed-Roof Tank | Conservation Vent Water Cooled Condenser | 41.9 | 5.3 | 20,000 gallons |
| | o Fixed-Roof Tank | Conservation Vent Water Cooled Condenser | 41.9 | 5.3 | 20,000 gallons |
| | o Fixed-Roof Tank | None | 0 | 0.1 | 900 gallons |
| | o Fixed-Roof Tank | None | 0 | 0.04 | 2,350 gallons |
| | o Fixed-Roof Tank | None | 0 | 0.04 | 250 gallons |
| | o Fixed-Roof Tank | None | 0 | 0.08 | 550 gallons |
| | o Fixed-Roof Tank | None | 0 | 0.9 | 20,000 gallons |
| | o Fixed-Roof Tank | None | 0 | 1.0 | 20,000 gallons |
| | o Fixed-Roof Tank | Conservation Vent Water Cooled Condenser Refrigerator Condenser | 90.7 | 4.4 | 500,000 gallons |
| | o Fixed-Roof Tank | Conservation Vent Water Cooled Condenser | 62.4 | 1.8 | 15,000 gallons |
| | Equipment Opening | None | 0 | 1.1 | 12 major 150 minor |
| | Handling | | | | |
| | o Tank cars, tank trucks | None | 0 | 0.3 | Dome loading |
| | o Barges | None | 0 | 3.9 | Bottom loading |

(Continued)



BEST COPY AVAILABLE

BEST COPY AVAILABLE

## TABLE 2-3 CONTINUED. CURRENT CONTROLS AND ESTIMATED EMISSIONS AT FACILITIES PRODUCING METHYLENE CHLORIDE

| Company/Location | Type of Emission/ Source | Present Controls | Reported Control Efficiency | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|
| | Secondary<br>o Wastewater Treatment Influent | Steam Strip/Carbon Adsorp. | N/R | 0.05 | |
| | o Solid Waste Drumming | Landfill | N/R | 0.43 | |
| | o Sludge Disposal | Off-site Treatment | N/R | 0.24 | |
| | Relief Devices | N/A | | 3.4 | Relief Valve |
| Dow Chemical Freeport, TX | Equipment Leaks | None | 0 | 87.3 | Routine Freeport, inspection programs |
| | Storage | | | | |
| | o * | * | * | 18.3 | |
| | Equipment Opening | None | 0 | 0.05 | 216 openings, large vessels cleared to 200 ppm organics |
| | Handling<br>o Tank trucks, tank cars, ships, barges | None | 0 | 4.2 | Open dome loading |
| | o Drums | Flume vacuum system | N/R | N/R | |
| | Secondary<br>o Wastewater rain and washdown | Nonbiological Treatment | 0 | 0.8 | |
| | o Spent Filter Elements | Material and Energy Recovery Unit | N/R | | |
| Dow Chemical Plaquemine, LA | Equipment Leaks | None | 0 | 27.5 | Continuous Air Monitoring |
| | Storage<br>o Fixed-Roof Tank | None | 0 | 6.3 | 126,500 gallons |
| | o Fixed-Roof Tank | None | 0 | 2.7 | 56,000 gallons |

(Continued)

30.

TABLE 2-3 CONTINUED. CURRENT CONTROLS AND ESTIMATED EMISSIONS AT FACILITIES PRODUCING METHYLENE CHLORIDE

| Company/Location | Type of Emission/ Source | Present Controls | Reported Control Efficiency | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|
| | o Fixed-Roof Tank | None | 0 | 12.0 | 187,900 gallons |
| | o Fixed-Roof Tank | None | 0 | 23.4 | 48,000 gallons |
| | o Fixed-Roof Tank | None | 0 | 23.4 | 48,000 gallons |
| | o Contact Internal Floating-Roof | N/A | N/A | 5.7 | 507,600 gallons |
| | Equipment Opening | None | 0 | 0.6 | 54 Openings |
| | Handling | | | | |
| | o tank truck, tank car, barges | None | 0 | 115 | Dip pipe loading |
| | Secondary | | | | |
| | o Not identified | None | 0 | 0.02 | |
| | Relief Devices | N/A | 0 | 0.05 | Reactor Discharge |
| LCP Chemicals Moundsville, WV | Process | | | | |
| | o Purge Condenser | Compression and Condensation | b | 84.3 | |
| | o Recovery Tank | None | 0 | 0.05 | |
| | Equipment Leaks | None | N/R | 28.5 | Sampling Program |
| | Storage | | | | |
| | o Fixed-Roof Tank | None | 0 | 1.3 | 13,600 gallons |
| | o Fixed-Roof Tank | None | 0 | 1.3 | 13,600 gallons |
| | o Fixed-Roof Tank | None | 0 | 1.3 | 13,600 gallons |
| | o Fixed-Roof Tank | None | 0 | 4.3 | 51,456 gallons |
| | o Fixed-Roof Tank | None | 0 | 10.7 | 100,455 gallons |
| | o Fixed-Roof Tank | None | 0 | 1.7 | 18,260 gallons |
| | o Fixed-Roof Tank | None | 0 | 0.5 | 4,750 gallons |
| | Handling | | | | |
| | o Rail cars, truck | None | 0 | 23.7 | Splash Fill |
| | Secondary | | | | |
| | o Not identified | Distillation and Recovery | N/R | 1.3 | |
| | o Not identified | Neutralization and Carbon Adsorp. | N/R | 0.6 | |
| | o Not identified | Off-site | N/R | 4.5 | |
| | Relief Devices | N/A | | 0.5 | Reactor Overpressurization (7 times) |

(Continued)



BEST COPY AVAILABLE

BLANK PAGE

BLANK PAGE

BLANK PAGE

BEST COPY AVAILABLE

TABLE 2-3 CONCLUDED. CURRENT CONTROLS AND ESTIMATED EMISSIONS AT FACILITIES PRODUCING METHYLENE CHLORIDE

| Company/Location | Type of Emission/ Source | Present Controls | Reported Control Efficiency | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|
| Vulcan Chemicals Geismar, LA | Process Vent o * | * | * | 0.7 | |
| | Equipment Leaks | * | * | 35.5 | |
| | Storage | * | * | 19.3 | |
| | Equipment Opening | * | * | 0.6 | |
| | Handling | * | * | 8.2 | |
| | Secondary | * | * | 3.9 | |
| | Relief Devices | * | * | 0.01 | |
| Vulcan Chemicals[a] Wichita, KS | Process Vent o * | * | * | 12.3 | |
| | Equipment Leaks | * | * | 38.1 | |
| | Storage o * | * | * | 32.2 | |
| | Equipment Opening | * | * | 0.8 | |
| | Handling | * | * | 6.2 | |

*This information is considered by the company to be confidential.

[a]Company reported greater than 98 percent control, but 98 percent was used in the absence of supporting test data.

N/A = Not applicable.
N/R = Not reported.

Losses from product storage were approximately 18.3 Mg/yr. All information concerning storage facilities and controls is considered confidential by Dow. Since methylene chloride is excluded from regulation in Texas, no state storage tank regulations are applicable to the Dow plant.

Losses due to handling were approximately 4.2 Mg/yr. Methylene chloride product is currently loaded and transported in tank trucks, tank cars, barges and ships using open dome loading. It is also shipped in 55 gallon drums which are loaded using a flume vacuum system. Emission levels were calculated by Dow from air samples taken during tank truck and rail car loading.

Dow reported two process waste emission sources. These are a wastewater stream and spent filter elements. The two sources emit approximately 0.8 Mg/yr of methylene chloride. The wastewater stream is treated in a nonbiological treatment system, and the spent filter elements are treated in a material and energy recovery unit. The wastewater stream accounts for 99% of the secondary emissions. Dow indicated a formal wastewater monitoring procedure is followed where a sample is taken every fifteen minutes and analyzed in a gas chromatograph. Dow reported the wastewater monitoring system as a means of monitoring MC secondary emissions.

The methylene chloride emissions from 216 process equipment openings in 1983 were 0.05 Mg/yr. Ninety-five percent of the equipment openings were for pump seal replacement. The remaining five percent of equipment openings were on larger pieces of equipment during routine cleaning and inspection. Dow reported that the vessels are cleared to a concentration of 200 ppm organics before being opened. Dow did not describe the procedure followed to clear vessels of organics.

There were no emissions from process vents at the Freeport facility. Dow reported that there are no process vents and all vapor streams are recycled within the process.



BEST COPY AVAILABLE

Vulcan Materials - Geismar, LA[6]

Total emissions generated by the hydrochlorination process at this plant were 68.2 Mg in 1983. The largest quantity of emissions was from equipment leaks. Methylene chloride equipment leak emissions in 1983 were approximately 35.5 Mg. Product storage tanks released 19.3 Mg of methylene chloride to the atmosphere in 1983. Secondary emissions from waste treatment or disposal were 3.9 Mg. Emissions from process vents, handling, and equipment openings were 0.7 Mg/yr, 8.2 Mg/yr and 0.6 Mg/yr, respectively. Relief device discharges emitted .01 Mg of methylene chloride in 1983. All information concerning equipment (such as process vents, process components including valves and flanges, and storage facilities) and controls is considered confidential by Vulcan.

The State of Louisiana has adopted regulations for control of emissions of volatile organic compounds from storage facilities, loading facilities, process components and specific MC end uses such as surface coating and solvent metal cleaning. Methylene chloride is excluded from these regulations. However, mixed streams containing methylene chloride may be controlled under these regulations.

Vulcan Materials - Wichita, KS[7]

Emissions from MC production by the direct chlorination of methane and the hydrochlorination of methanol were 89.6 Mg at this facility in 1983. Vulcan did not distinguish equipment leaks, storage emissions, handling losses, and equipment opening losses by production process. Process vent emissions were reported only for the hydrochlorination process.

The largest quantity of emissions was from equipment leaks. Methylene chloride equipment leak emissions in 1983 were approximately 38.1 Mg. Product storage tanks released 32.2 Mg of MC to the atmosphere in 1983. Process vents emitted 12.3 Mg of MC. Emissions from handling and equipment openings were 6.2 Mg and 0.8 Mg, respectively. All information concerning equipment and controls is considered confidential by Vulcan.

There are no regulations in Kansas for control of organic compound emissions from chemical production facilities.



BEST COPY AVAILABLE

Diamond Shamrock - Belle, WV[8]

This plant emitted 116 Mg of MC in 1983. The largest quantity of emissions was from equipment leaks, totalling 75.2 Mg. Fifty-five percent (41.5 Mg) of the equipment leaks were from valves. Nineteen percent (14.6 Mg/yr) were from flanges and fifteen percent (11.3 Mg/yr) from pump seals. Diamond Shamrock has equipped 52 percent (13 of 25) of their pressure relief devices with rupture disks. The plant indicated that operators make hourly checks of the operating equipment to check for leaks. Also, all employees are required to wear sample pumps on their person several times per year. Exposure levels are used to identify potential problems. Since no leak repair frequency was reported by Diamond Shamrock, no control efficiency could be estimated for their inspection program and equipment leak emission estimates are for uncontrolled sources. Therefore, actual equipment leak emissions may be somewhat lower.

Emissions from sixteen fixed roof storage tanks are estimated to have been 26.1 Mg in 1983. Tanks range in volume from 250 gallons to 500,000 gallons. The 500,000 gallon fixed roof tank had 1983 emissions of 4.4 Mg and is equipped with a conservation vent, a water cooled condenser, and a freon cooled condenser for a combined estimated control efficiency of 90.7 percent. Seven other storage tanks (with volumes between 15,000 and 20,000 gallons) are equipped with conservation vents and water cooled condensers. Control efficiencies range from 41.9 percent to 86.7 percent. The remaining eight storage tanks are not equipped with emission control devices.

MC emissions from process vents were 5.7 Mg. Sixty-seven percent (3.8 Mg/yr) of these emissions were from a regeneration vent. There was no methylene chloride control device for this vent. Two vent recovery systems emitted 19 percent and 14 percent of total process vent emissions. Both vents are equipped with condensers with control efficiencies of 68.5 percent and 26.7 percent, respectively.

Total emissions from loading/handling were 4.2 Mg/yr. Methylene chloride is loaded into tank cars, tank trucks, and barges. Tank cars and tank trucks are loaded through the domes. Barges are loaded from the bottom and are vented through a four inch header on either end of the barge.



BEST COPY AVAILABLE

A pressure relief valve malfunction resulted in a discharge of 3.4 Mg of MC in 1983. The relief valve was on a methyl separation column reboiler. This was the only emission from relief devices in 1983.

Equipment opening losses totalled 1.1 Mg in 1983. There were 12 major equipment openings and 150 minor equipment openings.

Secondary emissions of MC from three waste streams totalled about 0.7 Mg/yr. Emissions from the waste treatment plant influent contributed only 7 percent (.05 Mg/yr) of the total. The waste is treated by steam stripping and carbon adsorption. Disposal and related activities accounted for the major portion of secondary emissions. Sixty percent (0.43 Mg/yr) of MC emissions were from drumming solid waste for off-site landfilling. Loading sludge from the waste treatment plant into bulk tank trucks for off-site treatment contributed approximately 33 percent (.24 Mg/yr) of emissions.

West Virginia does not have regulations requiring control of MC emissions from this plant.

Dow Chemical - Plaquemine, LA[9]

Dow - Plaquemine produces MC by the hydrochlorination of methanol. Total emissions of MC at the facility were 217 Mg in 1983.

The largest source of air emissions reported at the Dow facility was from loading and handling practices. Dow calculated losses to be 115 Mg (53% of total emissions). Methylene chloride is shipped by tank truck, tank car, and barge. Submerged fill pipe loading is used to reduce emissions from what would occur with splash fill loading. Louisiana regulates loading facilities for VOC with throughputs of 20,000 gallons/day or more (40,000 gallons or more for existing facilities), but methylene chloride is excluded from this regulation.

Emissions from storage facilities contributed 34 percent (73.5 Mg) of total 1983 MC emissions. Dow has five fixed roof storage tanks and one contact internal floating roof storage tank with a mechanical shoe floating roof seal (primary only). None of the storage tanks are equipped with control devices. Louisiana regulations on VOC storage tanks are not applicable to MC.



BEST COPY AVAILABLE

Emissions from equipment leaks totalled 27.5 Mg in 1983. Twenty-five pressure relief devices were the largest source of emissions, releasing 8.7 Mg (32%) of the total equipment leaks emissions. One pressure relief device in gas service was equipped with a rupture disc. Emissions from valves were 8.5 Mg (31 percent) of equipment leak emissions. Nineteen percent (5.2 Mg) of the total equipment leaks emissions were released from mechanical pump seals. Liquid and gas sample connections were the sources of 15 percent of equipment leaks emissions, contributing 1.6 Mg and 2.4 Mg respectively. A compressor was the next largest source, emitting five percent (1.0 Mg) of total equipment leaks emissions. To monitor equipment for leaks, Dow has installed two process vapor phase chromatographs each capable of analyzing 10 streams. Twenty points in the process area are monitored and an alarm is set at 100 ppm. In addition, Dow requires operators to make a minimum of 12 rounds through the process, storage area per 24 hour day. Other formal division-wide programs include preventative maintenance, a pressure valve program, pressure safety valve, critical instrument, equipment thickness check, and visual internal inspections. In January, 1985 an equipment leaks emissions test conducted at Dow indicated 1.6 percent of the valves and 0.91 percent of the flanges were leaking. Calculated emission estimates incorporate this test data. Louisiana regulations requiring a VOC leak patrol/repair program do not apply to MC.

Losses from equipment openings were 0.6 Mg in 1983. The emissions were from 24 pump openings, 10 vessel openings, and 20 piping openings. Dow reported one discharge from pressure relief devices in 1983. A reactor instrument malfunction resulted in the discharge of .05 Mg of MC. A waste stream from the plant emitted approximately 0.02 Mg of MC. Dow reported no process vents emitting MC.

LCP Chemicals - Moundsville, WV[10]

The production of MC at this facility resulted in total emissions of 165 Mg MC in 1983. Emissions from two process vents were about 84.9 Mg, or 51 percent of total emissions. An unidentified process vent emitted more than 99 percent (84.3 Mg) of those emissions. LCP reported



BEST COPY AVAILABLE

that the process vent is controlled by a chloromethanes purge condenser that is operating at 100 percent pollutant removal efficiency. However, the purge condenser is only in operation for 50 percent of the plant operating hours. Therefore, the process vent emissions reported are for when the purge condenser is inoperative and the process vent is uncontrolled. The remaining process vent emissions (.05 Mg) were from a chloromethanes recovery tank.

Emissions from equipment leaks accounted for 17 percent of total emissions, or 28.5 Mg. The largest sources of equipment leaks were valves, flanges, and pressure relief devices. Emissions from the valves were approximately 12.4 Mg (44 percent of total equipment leaks emissions). Twenty-two percent (6.2 Mg) of the emissions were from flanges. Pressure relief devices constituted 12 percent of these emissions. LCP indicated that five areas are manually sampled once per shift for contaminants. The samples are transported to the plant laboratory and analyzed by gas chromatograph. Since no leak repair frequency was reported no control efficiency could be estimated for LCPs inspection program. Therefore, all emission estimates are for uncontrolled sources. This may overstate LCP's equipment leak emissions.

Losses from product loading and handling were approximately 23.7 Mg MC in 1983. Methylene chloride is loaded into rail cars and trucks by the top splash fill method at a rate of approximately 75 gpm. Approximately 30 percent of the MC is transported by rail cars with the remaining 70 percent transported by truck.

Seven fixed roof storage tanks emitted 21.1 Mg of MC in 1983. None of the storage tanks are equipped with control devices.

Secondary emissions from three waste streams totalled 6.4 Mg in 1983. A waste stream sent to off-site treatment and disposal contributes 70 percent of the secondary emissions. Twenty-one percent of the secondary emissions were from distillation and recovery. Emissions from treatment by neutralization and carbon adsorption accounted for 9 percent of secondary emissions. LCP reported a fourth waste stream treated by neutralization. However, no information was given regarding MC concentration in this stream.



BEST COPY AVAILABLE

LCP reported 8 discharges from pressure relief devices in 1983. All of the discharges were due to overpressurization of a thermal reactor. Estimated emissions were 0.5 Mg.

There were 104 changeouts of liquid driers in 1983. A changeout is accomplished by opening the drier and removing the spent drier residue. LCP indicated that emissions from drier changeouts were 0.9 Mg.

West Virginia has no regulations governing volatile organic compounds.

## 2.4 COST OF ADDITIONAL CONTROLS

Cost estimates were developed for control of process vent, fugitive, storage, and loading emission sources not presently well controlled. The cost effectiveness to control each of these emission sources at facilities producing methylene chloride are presented in Table 2-4 and discussed in the following sections. Methods used for estimating costs are presented in Appendix B.

The achievable emission reduction for different VOC cost effectiveness ranges is presented in Table 2-5. The achievable MC emission reduction is 552 Mg. This emission reduction can be compared to total estimated MC emissions of 770 Mg in 1983 (presented in Table 2-2).

### 2.4.1 Control of Process Vent Emissions

Incinerator cost estimates were developed for process vents not presently controlled by 98 percent or better. These estimates along with the estimated cost effectiveness are presented in Table 2-4. Three facilities, Diamond Shamrock in Belle, WV, LCP Chemicals in Moundsville, WV, and Vulcan Chemical, in Wichita, KS reported process vents not presently controlled 98 percent or better. The cost effectiveness of controlling process vent emissions at LCP, Diamond Shamrock and Vulcan is $1,220/Mg of VOC, $16,200/Mg of VOC and $17,100/Mg of VOC respectively. The combined MC emission reduction is 88.7 Mg, an 86 percent reduction in process vent emissions from all MC production facilities.



BEST COPY AVAILABLE

BEST COPY AVAILABLE



## TABLE 2-4. COST OF ADDITIONAL CONTROLS AT MC PRODUCTION FACILITIES

| Company/Location | Emission Type | Control[a] | Control Efficiency (%) | MC/VOC Emission Reduction (Mg/yr) | Capital Cost ($10^3$ $) | Recovery Credit ($10^3$ $) | Net Annual Cost ($10^3$ $) | Cost Effectiveness MC ($/Mg) | Cost Effectiveness VOC ($/Mg) |
|---|---|---|---|---|---|---|---|---|---|
| Diamond Shamrock | Process | Incineration | 98 | 5.6/25.8 | 1,220 | 0.0 | 418.5 | 74,900 | 16,200 |
| Belle, WV | Equipment Leak | LDAR | 53 | 40.0/81.6 | 58.0 | 33.1 | 29.5 | 737 | 361 |
| | Storage | COND | 85 | 1.1/ 1.4 | 111 | 1.0 | 28.1 | 26,100 | 20,700 |
| | Storage | FR-PO | 94 | 0.4/ 0.4 | 14.7 | 0.2 | 3.7 | 10,500 | 10,500 |
| | Storage | FR-SS | 97 | 2.8/ 2.8 | 16.9 | 2.3 | 2.1 | 753 | 753 |
| | Storage | FR-SS | 97 | 10.3/12.5 | 35.3 | 9.1 | 0.2 | 16 | 13 |
| | Storage | COND | 85 | 0.1/ 0.1 | 111 | 0.1 | 29.0 | 286,000 | 284,000 |
| | Storage | COND | 85 | 0.1/ 0.1 | 111 | 0.1 | 29.1 | 402,000 | 318,000 |
| | Storage | FR-PO | 94 | 1.8/ 1.8 | 32.7 | 0.9 | 7.7 | 4,220 | 4,220 |
| | Storage | FR-SS | 97 | 1.7/ 2.2 | 16.9 | 1.6 | 2.9 | 1,650 | 1,310 |
| | Loading | COND | 90 | 3.5/ 3.5 | 247 | 1.5 | 108 | 30,800 | 30,800 |
| Dow Chemical | Equipment Leak | LDAR | 60 | 52.4/72.0 | 56.0 | 31.9 | 16.8 | 321 | 234 |
| Freeport, TX | Storage | FR-SS | 97 | 1.9/ 1.9 | 19.0 | 1.5 | 3.4 | 1,820 | 1,820 |
| | Storage | FR-SS | 97 | 3.8/ 3.9 | 18.8 | 3.1 | 1.8 | 477 | 463 |
| | Storage | FR-SS | 97 | 3.8/ 3.9 | 18.8 | 3.1 | 1.8 | 477 | 463 |
| | Loading | COND condenser | 90 | 3.8/ 3.8 | 247 | 1.7 | 108 | 28,500 | 28,500 |
| Dow Chemical | Equipment Leak | LDAR | 68 | 18.6/31.3 | 60.6 | 13.2 | 27.1 | 1,460 | 866 |
| Plaquemine, LA | Storage | FR-SS | 97 | 6.2/ 6.2 | 39.1 | 5.0 | 5.2 | 852 | 852 |
| | Storage | FR-SS | 97 | 2.6/ 2.6 | 26.9 | 2.1 | 4.9 | 1,890 | 1,890 |
| | Storage | FR-SS | 97 | 11.7/11.7 | 50.6 | 9.5 | 3.8 | 324 | 324 |
| | Storage | FR-SS | 97 | 45.4/45.4 | 53.5 | 37.0 | -22.9 | -505 | -505 |
| | Loading | COND | 90 | 51.9/51.9 | 247 | 22.8 | 68.1 | 1,700 | 1,700 |
| | Loading | COND | 90 | 51.9/51.9 | 380 | 22.8 | 145 | 2,800 | 2,800 |

(Continued)

TABLE 2-4 CONCLUDED. COST OF ADDITIONAL CONTROLS AT MC PRODUCTION FACILITIES

| Company/Location | Emission Type | Control[a] | Control Efficiency (%) | MC/VOC Emission Reduction (Mg/yr) | Capital Cost ($10^3$ $) | Recovery Credit ($10^3$ $) | Net Annual Cost ($10^3$ $) | Cost Effectiveness MC ($/Mg) | Cost Effectiveness VOC ($/Mg) |
|---|---|---|---|---|---|---|---|---|---|
| LCP Chemicals Moundsville, WV | Process | Incineration | 98 | 82.4/329 | 1,190 | 0.0 | 403 | 4,900 | 1,220 |
| | Equipment Leak | LDAR | 59 | 16.7/56.6 | 133 | 21.3 | 27.0 | 1,620 | 478 |
| | Storage | COND | 85 | 3.2/ 3.2 | 333 | 2.6 | 84.8 | 26,500 | 26,500 |
| | Storage | FR-SS | 97 | 4.2/ 4.2 | 18.4 | 3.4 | 1.4 | 344 | 344 |
| | Storage | FR-SS | 97 | 10.4/10.4 | 35.1 | 8.5 | 0.7 | 69 | 69 |
| | Storage | COND | 85 | 1.5/ 1.5 | 111 | 1.2 | 27.9 | 18,900 | 18,900 |
| | Storage | FR-PO | 94 | 0.5/ 0.5 | 12.5 | 0.2 | 3.1 | 6,690 | 6,690 |
| | Loading | COND | 90 | 21.3/21.3 | 219 | 9.4 | 88.5 | 4,200 | 4,200 |
| Vulcan Chemical Geismar, LA | Equipment Leak | LDAR | 49 | 17.4/33.2 | 27.6 | 13.6 | 20.1 | 1,150 | 605 |
| | Storage | FR-SS | 97 | 14.5/14.5 | 105 | 11.8 | 15.7 | 1,080 | 1,080 |
| | Storage | FR-PO | 94 | 4.2/ 4.2 | 77.1 | 2.0 | 18.2 | 4,370 | 4,370 |
| | Loading | COND | 90 | 4.0/ 4.0 | 83.6 | 1.7 | 166 | 41,400 | 41,400 |
| Vulcan Chemical Wichita, KS | Process | Incineration | 98 | 0.7/24.1 | 1,210 | 0.0 | 410 | 585,000 | 17,100 |
| | Equipment Leak | LDAR | 58 | 22.0/50.5 | 47.5 | 20.1 | 21.0 | 954 | 416 |
| | Storage | COND | 85 | 0.4/ 0.4 | 111 | 0.3 | 28.8 | 80,200 | 80,200 |
| | Storage | COND | 85 | 0.6/ 0.6 | 111 | 0.5 | 28.6 | 49,100 | 49,100 |
| | Storage | COND | 85 | 0.4/ 0.4 | 111 | 0.3 | 28.8 | 80,900 | 80,900 |
| | Storage | COND | 85 | 0.8/ 0.8 | 333 | 0.6 | 86.7 | 112,000 | 112,000 |
| | Storage | COND | 85 | 11.9/11.9 | 222 | 9.7 | 485 | 4,060 | 4,060 |
| | Storage | COND | 85 | 8.1/16.2 | 111 | 9.2 | 19.9 | 2,460 | 1,230 |
| | Storage | COND | 85 | 0.5/ 9.5 | 111 | 3.4 | 25.8 | 54,300 | 2,710 |
| | Loading | COND | 90 | 5.6/ 5.6 | 247 | 2.5 | 107 | 19,100 | 19,100 |

[a]Abbreviations
FR-SS: Floating roof with primary and secondary seals.
FR-PO: Floating roof with primary seals only.
COND: Refrigerated condenser.
LDAR: Leak Detection and Repair.

[a] Product storage tank: emissions previously described as process vent emissions.



BEST COPY AVAILABLE

31.

TABLE 2-5. ESTIMATED MC EMISSION REDUCTIONS FOR MC PRODUCTION FACILITIES AS A FUNCTION OF COST EFFECTIVENESS

| Cost Effectiveness Range ($/Mg VOC) | Nationwide MC Emission Reduction (Mg/yr) | | | | |
|---|---|---|---|---|---|
| | Process | Equipment Leaks | Storage | Loading | Total |
| Credit | - | - | 45.4 | - | 45.4 |
| 0 - 500 | - | 131 | 44.2 | - | 175 |
| 501 - 1000 | - | 36.0 | 9.0 | - | 45.0 |
| 1001 - 2000 | 82.4 | - | 28.8 | 51.9 | 163 |
| 2001 - 5000 | - | - | 18.1 | 73.2 | 91.3 |
| > 5000 | 6.3 | - | 9.1 | 16.9 | 32.3 |
| TOTAL | 88.7 | 167 | 155 | 142 | 552 |

BEST COPY AVAILABLE

### 2.4.2 Control of Equipment Leak Emissions

The costs for additional control of equipment leak emissions from process components were estimated based on the requirements of the benzene equipment leaks NESHAP and the equipment count data supplied by the production facilities. The potential reduction in emissions from equipment leaks is estimated to be 167 Mg MC, 57 percent of total emissions from equipment leaks. Control efficiencies associated with controlling equipment leak sources range from 49 percent at the Vulcan-Geismar facility to 68 percent at the Dow-Plaquemine plant. MC emission reductions range from 16.7 Mg at the LCP plant (control efficiency 58 percent) to 52.4 Mg at Dow-Freeport (control efficiency 60 percent). The cost effectiveness of controlling equipment leaks ranges from $234/Mg VOC at Dow-Freeport to $866/Mg VOC at the Dow-Plaquemine plant.

### 2.4.3 Control of Storage Emissions

Cost estimates were developed for control of storage emissions from tanks not presently controlled by floating roofs, vapor recovery (85 percent control or better), or incineration. Three control options were evaluated: contact internal floating roof with primary seal only, contact internal floating roof with primary and secondary seals, and a refrigerated condenser for vapor recovery. Internal floating roofs were not costed for tanks smaller than 2 meters in diameter or horizontal tanks. Costs/cost-effectiveness estimates are presented in Table 2-4 for the most cost effective option. Using the most cost-effective option, storage emissions may be reduced by 155 Mg of MC (82 percent). The estimated cost effectiveness ranges from a net credit of $505/Mg of VOC to $573,000/Mg of VOC for the most cost-effective option on individual tanks. The estimated MC cost effectiveness is almost identical because these tanks store product MC typically greater than 99 percent pure. Since emissions are a function of throughput as well as size, there is no direct correlation between tank size and cost effectiveness. Achievable storage tank emission reduction as a function of cost effectiveness is presented in Table 2-5.



BEST COPY AVAILABLE

2.4.4 Control of Loading Emissions

Costs and cost-effectiveness estimates were developed for each uncontrolled land and marine loading operation. A refrigerated vapor recovery system operating at 90 percent MC removal efficiency was used as the control technique. The estimated costs of controlling each type of loading operation at individual facilities are presented in Table 2-4. The range of estimated cost effectiveness is $1,700/Mg VOC to $41,400/Mg of VOC. Using refrigerated vapor recovery as the control technique, total loading emissions may be reduced by 142 Mg (88 percent).

BEST COPY AVAILABLE

## 2.5 REFERENCES


1. Mannsville Chemical Products. Chemical Products Synopsis-Methylene chloride. Cortland, New York. 1984.

2. Chloromethanes Makers Project Further Gains After Strong '84: DuPont Shift to Alter the Market. Chemical Marketing Reporter. 227(6):5,15,17, 1984.

3. SRI International. 1984 Directory of Chemical Producers. Stanford Research Institute International. Menlo Park, California.

4. Organic Chemical Manufacturing, Volume 8: Selected Processes, U. S. Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, North Carolina, Publication No. EPA-450/3-80-028C. December, 1980.

5. Letter and attachments from Arnold, S.L., Dow Chemical U.S.A., to Farmer, J.R., EPA:ESED. March 7, 1985. Response to MC 114 Questionnaire.

6. Letter and attachments from Berg, R.E., Vulcan Chemicals, to Farmer, J.R., EPA:ESED. January 31, 1985. Response to MC 114 Questionnaire.

7. Letter and attachments from Boyd, J.M., Vulcan Chemicals, to Farmer, J.R., EPA:ESED. February 1, 1985. Response to MC 114 Questionnaire.

8. Letter and attachments from Christensen, B.H., Diamond Shamrock Company, to Farmer, J.R., EPA:ESED. January 31, 1985. Response to MC 114 Questionnaire.

9. Letter and attachments from Arnold, S.L., Dow Chemical U.S.A., to Farmer, J.R., EPA:ESED. March 12, 1985. Response to MC 114 Questionnaire.

10. Letter and attachments from Morris, A.R., LCP Chemicals, to Farmer, J.R., EPA:ESED. February 28, 1985. Response to MC 114 Questionnaire.




BEST COPY AVAILABLE

# 3.0 OTHER CHEMICAL PLANTS

## 3.1 PROCESS DESCRIPTIONS, EMISSIONS, AND CURRENT CONTROLS

This chapter presents the emissions and controls associated with the use of methylene chloride (MC) as a raw material used in the synthesis of other chemical products. Eleven plants use MC in production processes. These processes include: triacetate fibers, polycarbonate resin, plastics, rubber cement, rubber accelerator, insulating materials, specialty chemicals, vinyl chloride monomer, and production of BAYGON$^{R}$ 1.5, a pesticide. Emissions from BAYGON$^{R}$ 1.5 production are duscussed in this chapter since detailed emission estimates were received from the company for this facility. The chapter on Pesticide Manufacturing (Ch. 8) presents only generalized consumption and emissions information for the pesticide industry. MC is also used in other chemical production processes which are not identified because the company either considers production process descriptions as proprietary information, or the company did not provide sufficient information on the type of operation.

Methylene chloride emissions from these chemical plants are from equipment leaks, raw material storage, process vents, equipment openings, loading and handling, and secondary sources. The plants using MC in production and the types and amounts of emissions from these plants are presented in Table 3-1.

### 3.1.1 Triacetate Fiber Production

Triacetate fiber is manufactured by Celanese Fibers Operation in Rock Hill, South Carolina. Methylene chloride is used by Celanese to dissolve triacetate polymer flake and form a liquid polymer (referred to as "dope") that is suitable for extruding.

3.1.1.1 Process Description[1]. A solution of methylene chloride and methanol is fed into a batch mixer containing triacetate polymer flakes and other dry ingredients.



BEST COPY AVAILABLE

BEST COPY AVAILABLE

## TABLE 3-1. TOTAL EMISSIONS FROM CHEMICAL PLANTS USING METHYLENE CHLORIDE IN PRODUCTION

| Plant/Location | 1983 Methylene Chloride Emissions (Mg/Yr) | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | Process | Equipment Leaks[a] | Relief Devices | Storage[b] | Handling | Equipment Openings | Secondary | Total |
| B.F. Goodrich, Plant I Cleveland, OH | 65.6[c] | 4.6 | --- | 0.2 | --- | --- | 169 | 239 |
| B.F. Goodrich, Plant II Cleveland, OH | 7.5 | 10.1 | --- | 0.5 | --- | --- | --- | 18.1 |
| Borden Chemical Fremont, CA | 2.2 | 0.003 | --- | --- | --- | --- | 0.3 | 2.5 |
| Borden Chemical Norristown, PA | --- | 2.1 | --- | 0.8 | 0.3 | --- | --- | 3.2 |
| Celanese Rock Hill, SC | 5150 | 22.0 | 2.7 | --- | 0.5 | --- | --- | 5180 |
| Dow Chemical Midland, MI | 1120 | 207 | 0.1 | 29.0 | 2.7 | 4.3 | 88.5 | 1450 |
| General Electric Mount Vernon, IN | 2680 | 247 | --- | --- | --- | 63.7 | 584 | 3570 |
| General Electric Pittsfield, MA | 64.9 | 6.1 | --- | 0.3 | 0.2 | 2.3 | 0.2 | 74.0 |
| General Electric Schenectady, NY | 0.01 | 0.001 | --- | --- | --- | --- | 0.2 | 0.2 |
| Mobay Chemicals Baytown, TX | 0.4 | 51.2 | --- | 0.2 | 0.6 | 16.5 | 74.4 | 143 |
| Mobay Chemicals Kansas City, MO | --- | 0.02 | --- | 0.4 | --- | --- | --- | 0.4 |
| Shell Deer Park, TX | --- | --- | --- | --- | --- | --- | 0.06 | 0.06 |
| | 9090 | 550 | 2.8 | 31.0 | 4.3 | 86.8 | 917 | 10,700 |

[a]Based on equipment count provided by plants and SOCMI fugitive emission factors.

[b]Based on storage tank information provided by plants and AP-42 equations.

[c]Combined emissions from process vents, equipment openings, and loading and handling.

The solvents are slowly mixed with the solids until the solids are completely dissolved, forming the liquid polymer dope. The dope is then filtered and pumped to the extrusion area, where it is preheated, and then extruded and dried. The dried fibers are spun onto bobbins until further processing including twisting, coning, and beaming. A process flow diagram is shown in Figure 3-1.

3.1.1.2 Current Emissions and Controls[2]. Methylene chloride emissions totalled 5180 Mg at the Celanese facility in 1983. Emission sources, current controls, control efficiencies, and emission amounts are given in Table 3-2. The major emission source from triacetate fiber production is from solvent recovery. Carbon adsorption units operating at a reported control efficiency of greater than 98 percent are used to recover spent solvent. Emissions from the units were 5150 Mg in 1983. Celanese did not report any other process vent emission points.

Equipment leaks were the source of 22.0 Mg of MC emissions. Valves contributed 51 percent (11.2 Mg) of those emissions. Flanges and pumps seals emitted 22 percent (4.9 Mg) and 21 percent (4.6 Mg), respectively. To monitor for equipment leaks, Celanese operates four infra-red gas analyzers in different process areas. The analyzers measure room concentrations and are equipped with recorders and alarms. These instruments are useful in detecting process upsets and spills, but not for determining individual equipment leaks. Celanese did not report a leak repair program, therefore no control efficiency could be estimated for their inspection program and emission estimates are for uncontrolled sources. This may overstate somewhat Celanese's equipment leak emissions.

Handling emissions accounted for about 0.5 Mg of MC emissions at the Celanese facility. Methylene chloride is received by tank truck and tank car. The tank truck or tank car compartments are pressurized with inert gas and the MC is pumped to storage tanks. The storage tanks are tied into the solvent recovery ducting. Therefore, losses occur only when the tank truck or car is empty and the compartment is depressurized into the atmosphere. Celanese indicated that there are no emissions from MC storage since storage tanks are vented into the solvent recovery ducting.

BEST COPY AVAILABLE

BEST COPY AVAILABLE




Figure 3-1. Process flow diagram for the production of triacetate fiber.

## TABLE 3-2 ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHLORIDE IN PRODUCTION

| Company/Location | Product | Type of Emissions | Present Controls | Reported Control Efficiency (%) | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|---|
| B.F. Goodrich Cleveland, OH Plant I | Rubber Accelerator | Miscellaneous[a] | | | 65.6 | From mass balance-See discussion |
| | | Equipment Leaks | None | 0 | 4.6 | Visual inspection |
| | | Storage<br>o Fixed-Roof Tank | None | 0 | 0.2 | |
| | | Secondary<br>o Product water wash | To POTW | NR | 169 | |
| B.F. Goodrich Cleveland, OH Plant II | Rubber Accelerator | Process<br>o Vacuum jet pump | Water cooled condenser, refrigerated condenser | 94 | 7.5 | |
| | | Equipment Leaks | None | 0 | 10.1 | No monitoring |
| | | Storage<br>o Pressure vessel<br>o Pressure vessel<br>o Pressure vessel | Back pressure relief valve<br>Back pressure relief valve<br>Back pressure relief valve | NR<br>NR<br>NR | 0.06<br>0.1<br>0.4 | 750 gallons<br>750 gallons<br>750 gallons |
| Borden Chemical Fremont, CA | Rubber Cement | Process<br>o Adhesives fume collection | None | | 2.2 | |
| | | Equipment Leaks | None | 0 | 0.003 | 4 process components |
| | | Secondary<br>o Waste product drums | To solvent reclaimer | NR | 0.3 | |
| Borden Chemical Norristown, PA | Liquid Chemical Specialty Products | Equipment Leaks | None | 0 | 2.1 | Visual inspection |
| | | Storage<br>o Fixed-Roof Tank<br>o Fixed-Roof Tank<br>o Fixed-Roof Tank<br>o Fixed-Roof Tank | None<br>None<br>None<br>None | 0<br>0<br>0<br>0 | 0.4<br>0.2<br>0.1<br>0.06 | 5,000 gallons<br>10,000 gallons<br>5,000 gallons<br>3,000 gallons |

(Continued)



BEST COPY AVAILABLE

BEST COPY AVAILABLE

## TABLE 3-2 CONTINUED. ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHLORIDE IN PRODUCTION

| Company/Location | Product | Type of Emissions | Present Controls | Reported Control Efficiency (%) | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|---|
| Borden Chemical Norristown, PA (Cont'd) | | Handling<br>o Tank trucks<br>o Product handling | None | 0 | 0.3 | |
| Celanese Rock Hill, SC | Triacetate Fibers | Process<br>o Solvent Recovery | Carbon Adsorption | 98[b] | 5150 | |
| | | Equipment Leaks | Infra-red gas analyzers | 0 | 22.0 | |
| | | Handling<br>o Tank truck, tank car<br>Relief Devices | Vent to solvent recovery<br>NA | NR | 0.5<br>2.7 | Mixer Rupture Discharge |
| Dow Chemical (#5) Midland, MI | Unidentified | Process<br>o * | * | * | 1.7 | 3 vents |
| | | Equipment Leaks | Pressure relief device controls | 0 | 8.2 | Visual inspection preventive maintenance |
| | | Storage<br>o Fixed-Roof Tank | Vapor Return Conservation vent | 98[b] | 0.003 | |
| | | Equipment opening | None | 0 | 0.02 | 17 openings |
| | | Handling<br>o Tank truck | Vapor balance line | 95 | 0.03 | |
| Dow Chemical (#6) Midland, MI | Unidentified | Process<br>o * | * | * | 67.1 | 1 vent |
| | | Equipment Leaks | Pressure relief device controls | 0 | 16.6 | Visual inspection preventive maintenance |
| | | Storage<br>o Pressure vessel<br>o Pressure vessel | None<br>None | 0<br>0 | .01<br>.02 | 30 gallons<br>100 gallons |
| | | Equipment opening | None | 0 | 0.04 | 200 openings (Experimental process-small lines) |

(Continued)

BLANK PAGE

BLANK PAGE

BLANK PAGE

TABLE 3-2 CONTINUED. ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHLORIDE IN PRODUCTION

| Company/Location | Product | Type of Emissions | Present Controls | Reported Control Efficiency (%) | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|---|
| Dow Chemical (#7) Midland, MI | Unidentified | Process | | | | |
| | | o * | * | * | 54.5 | 1 vent |
| | | Equipment Leaks | None | 0 | 5.5 | Visual inspection preventive maintenance |
| | | Equipment opening | None | 0 | 0.2 | 2 openings |
| | | Secondary | | | | |
| | | o Liquid waste stream | Biological Treatment | NR | 40.2 | |
| Dow Chemical (#8) Midland, MI | Unidentified | Process | | | | |
| | | o * | * | * | 52.5 | 4 vents |
| | | Equipment Leaks | Chromatographic Air Monitoring Pressure Relief device controls | NR | 60.1 | |
| | | Equipment opening | None | 0 | 0.3 | 54 openings |
| | | Secondary | | | | |
| | | o Liquid waste stream | Biotreatment | NR | 0.006 | |
| | | o Liquid waste stream | Biotreatment | NR | 1.0 | |
| | | o Liquid waste stream | Process Recovery | NR | 12.8 | |
| | | o Liquid waste stream | Process Recovery | NR | 0.01 | |
| | | o Liquid waste stream | Incinerator | NR | 0 | |
| Dow Chemical (#9) Midland, MI | Unidentified | Process | | | | |
| | | o * | * | * | 135 | 2 vents |
| | | Equipment Leaks | Pressure relief device controls | | 13.3 | Visual inspection Preventive maintenance |
| | | Storage | | | | |
| | | o Pressure vessel | Pressure Relief Device | NR | 0.5 | 10,000 gallons |
| | | o Pressure vessel | Pressure Relief Device | NR | 0.1 | 500 gallons |
| | | o Pressure vessel | Pressure Relief Device | NR | 1.0 | 8,000 gallons |
| | | Handling | | | | |
| | | o Tank cars | None | 0 | 1.4 | |

(Continued)



BEST COPY AVAILABLE

BEST COPY AVAILABLE

## TABLE 3-2 CONTINUED. ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHLORIDE IN PRODUCTION

| Company/Location | Product | Type of Emissions | Present Controls | Reported Control Efficiency (%) | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|---|
| Dow Chemical (#10) Midland, MI | Unidentified | Process | | | | |
| | | o * | * | * | 0.7 | 2 vents |
| | | Equipment Leaks | Quarterly air monitoring pressure relief device controls | NR | 27.6 | Visual inspection |
| | | Storage | | | | |
| | | o Pressure vessel | None | 0 | 1.0 | 32,000 gallons |
| | | Equipment openings | None | 0 | 0.7 | 100 openings |
| | | Handling | | | | |
| | | o Rail car | None | 0 | 1.3 | |
| | | Secondary | | | | |
| | | o Liquid Waste Stream | Biotreatment | NR | 1.2 | |
| Dow Chemical (#11) Midland, MI | Unidentified | Equipment Leaks | Continuous Air Monitor | NR | 6.7 | 20 sampling probes |
| | | Storage | | | | |
| | | o Fixed-Roof Tank | Relief Valve | NR | 0.4 | 2,850 gallons |
| | | o Fixed-Roof Tank | Relief Valve | NR | 0.4 | 2,850 gallons |
| | | o Fixed-Roof Tank | Relief Valve | NR | 0.08 | 1,900 gallons |
| | | o Fixed-Roof Tank | Relief Valve | NR | 0.08 | 2,000 gallons |
| | | o Fixed-Roof Tank | Relief Valve | NR | 0.02 | 2,850 gallons |
| | | Equipment opening | None | 0 | 0.5 | 115 openings |
| Dow Chemical (#12) Midland, MI | Unidentified | Process | | | | |
| | | o * | * | * | 810.8 | 3 vents |
| | | Equipment Leaks | Continuous Air Monitor | NR | 68.7 | 20 sampling probes |
| | | Storage | | | | |
| | | o Fixed-Roof Tank | Relief Valve | NR | 12.0 | 47,000 gallons |
| | | o Fixed-Roof Tank | Vented to Scrubber | NR | 3.7 | 5,900 gallons |
| | | o Pressure vessel | Water seal and relief valve | NR | 4.7 | 12,900 gallons |
| | | o Fixed-Roof Tank | Vented to Scrubber | NR | 1.8 | 5,900 gallons |
| | | o Fixed-Roof Tank | Vented to Scrubber | NR | 1.9 | 4,300 gallons |
| | | o Fixed-Roof Tank | None | 0 | 1.0 | 12,900 gallons |
| | | Equipment opening | None | 0 | 2.5 | 234 openings |
| | | Secondary | | | | |
| | | o Liquid waste stream | Biological Treatment | 5 | 33.3 | |
| | | Relief devices | NA | | 0.1 | Storage tank corrosion failure |





(Continued)

## TABLE 3-2 CONTINUED. ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHLORIDE IN PRODUCTION

| Company/Location | Product | Type of Emissions | Present Controls | Reported Control Efficiency (%) | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|---|
| General Electric Mount Vernon, IN | Polycarbonate Resin | Process | | | | |
| | | o Hopper Dryers | None | 0 | 17.0 | 41 dryers |
| | | o Hopper Dryers | None | 0 | 18.6 | 45 dryers |
| | | o Extruder Die Hoods | None | 0 | 224.6 | 7 hoods |
| | | o Extruder Die Hood | None | 0 | 4.5 | 1 hood |
| | | o Extruder Die Hood | None | 0 | 2.5 | 1 hood |
| | | o Extruder Die Hood | None | 0 | 8.8 | 1 hood |
| | | o Extruder Die Hood | None | 0 | 13.4 | 1 hood |
| | | o Extruder Die Hood | None | 0 | 0.2 | 1 hood |
| | | o Molding Machine Vents | None | 0 | 4.8 | 2 vents |
| | | o Q.A. Hood Vent | None | 0 | 6.4 | 4 vents |
| | | o Extruder Die Vents | None | 0 | 391 | 17 vents |
| | | o Extruder Vacuum Pump | None | 0 | 86.4 | 6 pumps |
| | | o Extruder/Die Vent | None | 0 | 11.2 | 3 vents |
| | | o Extruder/Die Vent | None | 0 | 93.8 | 8 vents |
| | | o Molding Machine | None | 0 | 3.2 | 2 units |
| | | o Vacuum Stripping Blowers | None | 0 | 0.6 | 4 units |
| | | o Vent Gas Absorber | Water Scrubber | 87 | 477.3 | 1 vent |
| | | o Vent Gas Absorber | Water Scrubber | 87 | 477.3 | 1 vent |
| | | o Carbon Adsorption System | Carbon Bed | 87 | 46.2 | |
| | | o Filter Receiver | None | 0 | 85.6 | 2 units |
| | | o Filter Receiver | None | 0 | 85.6 | 2 units |
| | | o Weight Hopper Vent | None | 0 | 0.6 | 2 units |
| | | o Feed Hopper | None | 0 | 0.3 | 1 unit |
| | | o Surge Hopper | None | 0 | 7.6 | 2 units |
| | | o MC Storage Tank | Conservation Vent | 10 | 17.6 | |
| | | o Storage Silo | None | 0 | 170 | |
| | | o Solvent Recovery | Carbon Bed | 87 | 347 | |
| | | o MC Dryer System | Knock Out Pot/Demister | 50 | 79.6 | |
| | | o Tar/Isomer Storage | None | 0 | 0.4 | |
| | | Equipment Leaks | | | | |
| | | o Building 14/16 | Photo ionization detection system | 0 | 175 | Monitors 40 points |
| | | o Building 15/31 | Photo ionization detection system | 0 | 71.8 | Monitors 10 points |

(Continued)



BEST COPY AVAILABLE

BEST COPY AVAILABLE

## TABLE 3-2 CONTINUED. ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHLORIDE IN PRODUCTION

| Company/Location | Product | Type of Emissions | Present Controls | Reported Control Efficiency (%) | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|---|
| General Electric Mount Vernon, IN (Cont'd) | | Storage | | | | |
| | | o 44 process and storage vessels | Vent gas absorbers | 87 | 0.1 | Bldg 14/16 |
| | | o Pressure Vessel | Conservation Vent | 10 | 1.5 | Bldg 15/31 |
| | | Equipment Opening | None | 0 | 63.7 | |
| | | Secondary | | | | |
| | | o Biological Treatment | None | 0 | 584 | |
| General Electric Pittsfield, MA | Plastics Manufacture | Process | | | | |
| | | o Reactor Vent | None | 0 | 4.6 | |
| | | o Phosgenation Reactor | None | 0 | 2.4 | |
| | | o Precip.Room Vent | None | 0 | 1.8 | |
| | | o Work-up Room Vent | None | 0 | 1.3 | |
| | | o Stripper Room Vent | None | 0 | 1.8 | |
| | | o Stripper Room Vent | None | 0 | 1.8 | |
| | | o Percip. Condenser Vent | Condenser | 50 | 27.2 | |
| | | o MC Still Watertank | None | 0 | 0.9 | |
| | | o Area Vent | None | 0 | 2.7 | |
| | | o MC Still Vent | Condenser | 97 | 8.2 | |
| | | o MC/Water Separator | None | 0 | 1.8 | |
| | | o Still Decant Tank | None | 0 | 0.5 | |
| | | o Dryer Vacuum Pump | Condenser | 50 | 9.8 | |
| | | Equipment leaks | None | 0 | 6.1 | Leaks detected by observation and weekly mass balance |
| | | Storage | | | | |
| | | o Fixed-Roof Tank | To Condenser | 50 | 0.09 | 4100 gallons |
| | | o Fixed-Roof Tank | None | 0 | 0.06 | 500 gallons |
| | | o Fixed-Roof Tank | None | 0 | 0.06 | 500 gallons |
| | | o Fixed-Roof Tank | To Condenser | 50 | 0.007 | 1500 gallons |
| | | o Fixed-Roof Tank | To Condenser | 50 | 0.1 | 1250 gallons |
| | | o Fixed-Roof Tank | None | 0 | 0.005 | 250 gallons |

(Continued)

## TABLE 3-2 CONTINUED. ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHLORIDE IN PRODUCTION

| Company/Location | Product | Type of Emissions | Present Controls | Reported Control Efficiency (%) | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|---|
| General Electric Pittsfield, MA (Cont'd) | | Equipment Opening | None | 0 | 2.3 | 2000 openings |
| | | Handling | | | | |
| | | o Drums | None | 0 | 0.2 | Present delivery via tank trucks. |
| | | Secondary | | | | |
| | | o Aqueous waste stream | To Sewage Treatment | 80 | 0.1 | |
| | | o Drums | To Haz.Waste Disposal | 98[b] | 0.01 | |
| General Electric Schenectady, NY | Insulating Materials | Process | | | | |
| | | o * | * | * | 0.01 | |
| | | Secondary | | | | |
| | | o * | * | * | 0.2 | |
| Mobay Chemicals Baytown, TX | Polycarbonate Resin | Process | | | | |
| | | o Vent | Scrubber | 98 | 0.3 | |
| | | o Reactor Vent | None | 0 | 0.07 | |
| | | o Reactor Vent | None | 0 | 0.05 | |
| | | Equipment Leaks | Monthly Portable Gas Chromatograph Check, Pressure Relief Device Controls | NR | 51.2 | |
| | | Equipment opening | None | 0 | 16.5 | Primarily sampling openings |
| | | Storage | | | | |
| | | o Fixed-Roof Tank | Vent to Scrubber | 98 | 0.006 | 27,100 gallons |
| | | o Fixed-Roof Tank | Vent to Scrubber | 98 | 0.006 | 150,000 gallons |
| | | o Fixed-Roof Tank | Vent to Scrubber | 98 | 0.1 | 85,200 gallons |
| | | o Fixed-Roof Tank | Vent to Scrubber | 98 | 0.1 | 85,200 gallons |
| | | o Fixed-Roof Tank | Vent to Scrubber | 98 | 0.003 | 27,100 gallons |
| | | Secondary | | | | |
| | | o Wastewater stream | Biological & Carbon Treatment | NR | 22.0 | |
| | | o Contained solvent | Incineration | NR | 0 | |
| | | o Process Water Trench | Biological & Carbon Treatment | 80 | 11.0 | |
| | | o Leaks and spills | None | 0 | 41.4 | |

(Continued)



BEST COPY AVAILABLE

BEST COPY AVAILABLE

## TABLE 3-2 CONCLUDED. ESTIMATED EMISSIONS AND CURRENT CONTROLS AT FACILITIES USING METHYLENE CHLORIDE IN PRODUCTION

| Company/Location | Product | Type of Emissions | Present Controls | Reported Control Efficiency (%) | Present MC Emissions (Mg/yr) | Comments |
|---|---|---|---|---|---|---|
| | | Handling<br>o Rail car, tank truck | None | 0 | 0.6 | |
| Mobay Chemicals<br>Kansas City, MO | BAYGON 1.5 | Equipment Leaks | None | 0 | 0.02 | No monitoring |
| | | Storage<br>o Fixed-Roof Tank | None | 0 | 0.4 | No longer uses on-site storage |
| Shell<br>Deer Park, TX | Vinyl Chloride Monomer | Secondary<br>o Waste stream one | Biotreatment | NR | 0.06 | |

*The company considers this confidential information.

[a]Combined emissions from process vents, equipment openings, and loading and handling.

[b]Company reported greater than 98 percent control, but only 98 percent is accepted without supporting test data.

NR = Not reported.
NA = Not applicable.

Celanese reported one discharge from a pressure relief device on a mixer. The discharge resulted in 2.7 Mg of MC emissions.

South Carolina has developed regulations pertaining to emissions of volatile organic compounds (VOC) from specific sources, such as solvent metal cleaning and storage tanks. However, methylene chloride is excluded from these regulations in South Carolina due to its negligible photochemical reactivity.

### 3.1.2 Polycarbonate Resin

Polycarbonate resins were manufactured by two producers in 1983. These are General Electric in Mount Vernon, Indiana, and Mobay Chemical in Baytown, Texas. Methylene chloride is used by both plants as a solvent in the polymerization reaction.

3.1.2.1 Process Description[1]. Bisphenol-A is reacted with phosgene in the presence of pyridine to form a polycarbonate. MC is used as a solvent in the polymerization reaction. The reaction is carried out at a temperature below 40°C (104°F) with a residence time of 1 to 3 hours. The polycarbonate production process occurs according to the reaction:

$$\underset{\text{(Bisphenol-A)}}{HO_6H_4C(CH_3)_2C_6H_4H} + \underset{\text{(phosgene)}}{COCl_2} \xrightarrow[\text{MC}]{\text{pyridine}} \text{polycarbonate resin}$$

Following reaction, reactor contents are washed to remove excess pyridine from the polymer/methylene chloride stream. This stream is treated with an organic compound, such as aliphatic hydrocarbon, to effect precipitation of the polymer. After the polycarbonate precipitates, it is filtered and dried. Methylene chloride is present in all process steps. A process flow diagram is shown in Figure 3-2.

3.1.2.2 Current Controls and Emissions. The types of emissions from this process at the two production facilities are from process vents, equipment leaks, storage, handling, equipment openings, and secondary sources. The emission types and their controls are discussed below.



BEST COPY AVAILABLE




Figure 3-2. Process flow diagram for the Production of polycarbonate resin.

BEST COPY AVAILABLE

General Electric - Mount Vernon, Indiana

The production of polycarbonate resins and proprietary associated processes at this facility resulted in 3,570 Mg of MC emissions in 1983. General Electric indicated that emissions reported for individual sources were either rough estimates or maximum allowable permitted levels and that they could not give exact values for each emission source. Actual emissions in 1983 were much lower than the reported levels. General Electric reported 4 process areas emitting MC. Two of the process areas use methylene chloride in polycarbonate synthesis. Therefore emissions result from process vents as well as equipment leaks and equipment openings. The other two areas are used in polycarbonate processing and MC emissions result from residual in materials processed. Emission sources, current controls, control efficiencies, and emission quantities are presented in Table 3-2. Process vents were the source of 2,680 Mg of those emissions. Seventeen extruder die vents emitted about 391 Mg MC (27 percent of total process vent emissions). Seven extruder die hoods emitted approximately 225 Mg MC (15 percent of process vent emissions). Neither the extruder die vents nor the extruder die hoods are equipped with MC control devices. Other major uncontrolled contributors include six extruder vacuum pumps 86.4 Mg/year emissions), eight more extruder die vents (93.8 Mg/year emissions), two filter receivers emitting 85.6 Mg of MC each, and two storage silos emitting 85.0 Mg of MC each.

General Electric reported control devices on 6 process vents. Two vent gas absorbers are controlled by water scrubbers at an estimated 87 percent MC control efficiency. Emissions from the vent gas absorbers were 477 Mg each. Two carbon adsorbers control various process vents. The adsorbers achieve 87 percent pollutant removal giving final emission levels of 46.3 Mg and 348 Mg. A MC dryer system is equipped with a knock-out Pot/Demister that reduced emissions by 50 percent, to 79.5 Mg. General Electric also reported a conservation vent on a MC storage tank with 10 percent control efficiency. The storage tank emissions were 17.6 Mg of MC. This tank was reported as a process vent by General Electric.



BEST COPY AVAILABLE

Current estimates for emissions from secondary sources are 584 Mg/year. General Electric estimates that approximately 1,818 kg/day MC is discharged to the site sewer system. Approximately 218 kg/day reaches the wastewater treatment plant for on-site biological treatment. The remaining 1,600 kg/day is lost to the atmosphere in three areas: (1) the Brine Recovery Operation,( 2) the sewer system, and (3) the wastewater treatment plant prior to biological treatment.

Equipment leaks were the next largest source of emissions generated at the General Electric facility, totalling 247 Mg of MC. General Electric reported equipment counts for two of four process areas. The other two process areas do not have equipment in MC service and emissions result from residual in materials processed. Equipment leaks in one process building resulted in emissions of 176 Mg MC with flanges being the major contributor (42 percent). General Electric reported that multipoint programmable sequence area monitoring is performed to detect MC leaks using a photo ionization detection HNu system. Forty points are monitored throughout the process area. According to General Electric, the monitoring has proven effective in identifying major leak occurrences and the instrumentation can detect MC in the low ppm range. However, sample system limitations with 40 sample points can inhibit detection of minor leaks and spillage. No information was reported about the frequency of repair of leaks. Therefore, uncontrolled emission factors were used to estimate equipment leak emissions, possibly resulting in an overestimate of these emissions. Equipment opening losses in this process area were reported as 5.1 Mg in 1983. The number of equipment openings was not provided, but this emissions estimate was based on scheduled maintenance activities assuming 100 percent loss of estimated quantities in the system at the time of opening.

Equipment leak losses in a second process building totalled 71 Mg MC. General Electric also utilizes a HNu system in and around the primary potential leak areas in this building. Continuous area monitoring is performed at 10 points in the operation. General Electric did not report the frequency of leak repair for this area. Therefore, uncontrolled emission factors were used to estimate equipment leak emissions and these emission levels may be overstated.



BEST COPY AVAILABLE

Equipment opening losses in this area were 58.6 Mg, as a result of weekly recorded activities for several hundred pieces of equipment. General Electric based this emission figure on field estimates of quantities in the system at the time of opening, and extrapolated emissions out using 100 percent loss and number of occurrences.

There are 45 process and storage vessels for MC at this facility. All but one of these vessels vent to gas absorbers, with an estimated 87 percent control efficiency. The remaining vessel is equipped with a conservation vent with an estimated 10 percent control efficiency. Emissions from storage facilities were 1.6 Mg in 1983.

Indiana has adopted regulations limiting the allowable emissions of volatile organic compounds to 100 tons per year or an 85 percent reduction of emissions. However, the regulations exclude non-photochemically reactive hydrocarbons and organic compounds that are not liquid at standard conditions. Methylene chloride is excluded from these regulations due to its negligible photochemical reactivity.

Mobay Chemical - Baytown, Texas[4]

The polycarbonate resin process generated 143 Mg MC emissions at this facility in 1983. Table 3-2 documents emission sources, current controls, control efficiencies, and emission amounts for this facility.

Emissions from secondary sources were the largest source of MC emitters at 74.4 Mg. Mobay listed three sources for these emissions: 1) a wastewater stream going to biological and carbon treatment (22.1 Mg), 2) a process water trench also going to biological and carbon treatment (10.9 Mg), and 3) other leaks and losses prior to maintenance work (41.4 Mg).

Emissions from equipment leaks were 51.2 Mg in 1983. Valves emitted 55 percent (28.4 Mg). Flanges accounted for 19 percent (9.5 Mg) and pump seals emitted 15 percent (7.6 Mg). Mobay has 33 pressure relief devices protected by rupture disks. Twenty more relief valves are vented to a scrubber to control emissions. Five pressure relief valves are unprotected.



BEST COPY AVAILABLE

Mobay records process variables each shift to detect obvious leaks. Also, a daily walkthrough is performed to spot leaks. A solvent inventory is taken each week to account for any unusual loss. All pump seals and vent locations are checked monthly with a portable gas chromatograph. In addition, one technician devotes half-time to solvent loss prevention. Mobay believes this monitoring system is reasonably effective for obvious losses. Mobay did not report the frequency of leak repairs and emissions from equipment leaks were calculated using uncontrolled emission factors. Therefore, these emissions may be overstated.

Losses from equipment openings were 16.5 Mg in 1983. Forty-four percent (7.3 Mg) of equipment openings losses were due to daily sampling. Mobay reports that approximately 50 samples are taken a day. Filter replacement contributed about 6.1 Mg (37 percent) of MC emissions. Replacement of an 80,000 gallon product tank emitted 1.6 Mg. Other equipment opening losses were due to routine maintenance of purification equipment, pump seal replacement, heat exchanger replacement, and from opening open solvent lines to remove pluggage.

Solvent handling losses were 0.6 Mg. MC is delivered by rail car and/or tank truck. No control equipment is used to reduce emissions during unloading.

Emissions from three process vents totalled 0.4 Mg in 1983. A process vent scrubber operating at 98 percent MC removal efficiency emits 0.3 Mg MC. The emission level was determined from inlet and outlet sampling and gas chromatograph analysis of the samples for composition. Two reactor vents that emit MC only when the reactor is being filled have a combined annual loss rate of about 0.1 Mg/year. Emissions occur from these vents for only about 10 minutes per month.

Losses from five fixed roof storage tanks were about 0.2 Mg in 1983. All storage tank conservation vents are vented to a scrubber. Mobay reported that sampling indicated that this control technique reduces emissions by 98 percent.

Texas has adopted regulations to control emissions from volatile organic compounds. However, methylene chloride is excluded from these regulations due to its negligible photochemical reactivity.

BEST COPY AVAILABLE

### 3.1.3 Rubber Cement Manufacturing

Methylene chloride is used in the production of rubber cement at Borden Chemical, Fremont, California. Borden considers process description information confidential.

3.1.3.1 Current Emissions and Controls. Emissions from rubber cement manufacturing at this facility are primarily from process vents, and secondary sources. In addition, some emissions result from equipment leaks. Emission levels and controls at these facilities are discussed below and are presented in Table 3-2.

The estimated methylene chloride emissions from this plant are 2.5 Mg/year. Emissions are from a process vent, waste product disposal, and equipment leaks. There were no relief device discharges or equipment openings during 1983. Methylene chloride and product containing MC are handled and stored in 5-gallon pails and 55-gallon drums. Emissions were estimated by the plant to be negligible from these sources.

An adhesives fume collection system was the primary emission source at the Borden facility with about 2.2 Mg MC emissions (Borden estimated this figure from 1984 production). MC emissions occur intermittently during the 6-hour batch cycle as the mixer lid is opened to add batch ingredients and to take product samples. The ventilation system serving the rubber cement mixers also serves several other mixers not using MC. The combined flow from all mixers discharges through one stack.

Waste product is packed in drums and sent to a solvent reclaimer for solvent recovery and/or disposal. Emissions during packing are estimated to be 0.3 Mg/year.

Equipment leaks from process components in MC service were 3 kg (.003 Mg) in 1983. Borden has only four components in MC service, used less than 0.1 percent of the time. They have no monitoring or repair program for equipment leaks.

Fremont is in the Bay Area Air Quality Management District (BAAQMD). The BAAQMD has adopted a series of rules for the regulation of precursor organic compounds. However, in the BAAQMD, methylene chloride is defined as a non-precursor organic compound and is therefore excluded from regulation.



BEST COPY AVAILABLE

### 3.1.4 Rubber Accelerator Manufacturing

B.F. Goodrich uses MC in the production of rubber accelerator at two plants in Cleveland, Ohio. Rubber accelerator is a compound that greatly reduces the time required for vulcanization of natural and synthetic rubbers, while improving the aging and other physical properties at the same time.

3.1.4.1 Current Emissions and Controls. Emission sources from rubber accelerator manufacture at the two B.F. Goodrich plants are process vents, equipment leaks, storage, and secondary sources. Emission levels and controls at these facilities are discussed below and are presented in Table 3-2.

#### B.F. Goodrich - Cleveland, Ohio; Plant I[6]

B.F. Goodrich did not supply emission estimates for process vents, equipment openings, or loading and handling losses at this facility. However, a material balance was provided indicating that 70.4 Mg MC are emitted directly to the air. This figure does not include a product water wash stream containing MC that is discharged to an industrial sewer for pretreatment, and then to a publicly owned treatment works (POTW) facility. This secondary source emits 169 Mg MC. B.F. Goodrich did not indicate what fraction of MC is emitted in pretreatment prior to discharge to the POTW facility. Therefore, it was assumed all MC is emitted at the B.F. Goodrich facility.

Emission estimates were calculated for equipment leaks for process components in MC service and for storage facilities. Equipment leaks resulted in MC emissions of 4.6 Mg in 1983. Valves were the largest source of equipment leak emissions emitting 2.4 Mg MC. Sample connections were the next largest contributor with 1.1 Mg MC. Pressure relief devices emitted 0.5 Mg. B.F. Goodrich reported that process components are monitored for leaks through routine visual inspection and equipment maintenance. Since a leak repair program was not reported, emissions from equipment leaks were calculated using uncontrolled emission factors.

BEST COPY AVAILABLE

One fixed roof underground storage tank was the source of 0.2 Mg of MC emissions. The tank is not equipped with a control device. B.F. Goodrich reported no other storage tanks in MC service.

Equipment leaks and storage tanks result in total MC emissions of 4.8 Mg. From the material balance, if 70.4 Mg MC are emitted directly to the air, then the remaining 65.6 Mg may be assumed to be from process vents, equipment openings and loading and handling losses. B.F. Goodrich reported six process vent emission points. Four of those emission points were equipped with brine cooled shell and tube condensers operating at more than 98 percent MC removal efficiency. The remaining two process vents, a wash tank and a centrifuge blower were uncontrolled.

There were seven equipment openings at this facility in 1983. No estimate can be made on specific emission levels from these openings since B.F. Goodrich gave no indication of solvent purging procedures prior to opening. No estimate can be made on loading and handling emissions either, since no information was given on loading and handling techniques (i.e., splashfill versus dip pipe loading).

The State of Ohio has adopted regulations controlling photochemically reactive materials, hydrocarbons, and related materials. However, MC is excluded from these regulations due to its negligible photochemical reactivity.

B.F. Goodrich - Cleveland, Ohio: Plant II[6]

Emissions from process vents, equipment leaks, and storage facilities are approximately 18.1 Mg/year at this facility. The rubber accelerator manufacturing process was not in operation in 1983, so this emission level represents current conditions. However, the MC emissions were incorporated in the 1983 total MC emission estimates. Emission sources, current controls, control efficiencies, and emission quantities are reported in Table 3-2. B.F. Goodrich did not supply information concerning emissions from pressure relief devices and equipment openings.



BEST COPY AVAILABLE

Equipment leaks from process components are the largest source of MC emissions at 10.1 Mg/year. Valves emit 4.3 Mg (43 percent), pump seals emit 3.0 Mg (30 percent), and pressure relief devices emit 1.6 Mg. Sample connections are also minor contributors. B.F. Goodrich does not have a formal process component leak monitoring and repair program.

A vacuum jet/pump is the only process vent emitting MC. The emission rate for this vent is 7.5 Mg/year following control by a water cooled condenser and a refrigerated condenser operating at -9°C (16°F). The estimated MC removal efficiency is 94 percent.

B.F. Goodrich stores MC in three pressure vessels ranging in volume from 750 gallons to 2,000 gallons. Emissions from these storage vessels are approximately 0.5 Mg/year. These tanks are $N_2$ blanketed. During filling operations, the $N_2$/MC headspace is vented through back pressure relief valves (approximately 7 inches $H_2O$) in ratio to the volume of liquid being filled. No estimate was provided for loading emissions.

### 3.1.5 Insulating Materials Manufacture

General Electric in Schenectady, New York, uses MC in the manufacture of insulating materials. General Electric considers all information concerning their process description and equipment and controls confidential.

3.1.5.1 Current Emissions and Controls[7]. Methylene chloride emissions at this facility are from a process vent and a secondary source. Total MC emissions were about 0.2 Mg in 1983. The process vent emits 0.01 Mg, while the secondary source emits 0.2 Mg. Equipment leak emissions are negligible (less than 1 kg/year). General Electric reported no discharges from pressure relief devices, no equipment opening losses, and no MC storage tanks. Methylene chloride is purchased and stored in drums. Emission sources, current controls, control efficiencies, and emission amounts are presented in Table 3-2.

### 3.1.6 BAYGON$^R$ 1.5 Manufacturing

Mobay Chemicals in Kansas City, Missouri, uses MC in their Agricultural Chemicals Division as a diluent in the formulation of BAYGON$^R$ 1.5, a pesticide. Mobay considers the process description and product packaging information confidential.

BEST COPY AVAILABLE

3.1.6.1 Current Emissions and Controls[4]. Total MC emissions at this facility are about 0.4 Mg/year. Emission sources, current controls, control efficiencies, and emission quantities are reported in Table 3-2.

One fixed roof storage tank emitted 0.4 Mg in 1983. However, Mobay indicated that MC is currently pumped directly from tank trucks to the process with no on-site storage. In the past, the MC was shipped to the plant in tank trucks and pumped into fixed roof storage tanks with no control devices in use.

Equipment leaks from process component leaks were 0.02 Mg in 1983. Mobay reported that BAYGON$^{R}$ 1.5 is only formulated 4 or 5 days per year for 8 hours per day, and the formulation process is a closed system with a minimum of production steps. Therefore, no monitoring or repair program is conducted for MC leaks.

Mobay reported no process vent emissions, no pressure relief device discharges, no equipment opening losses, and no emissions from secondary sources. Although Mobay indicated no controls were used for unloading MC in 1983, no handling emission estimates were given.

Missouri air laws are distinguished by metropolitan area. There are regulations controlling VOC emissions from specific sources (such as solvent metal cleaning) in the Kansas City metropolitan area. However, MC is excluded from these regulations due to its negligible photochemical reactivity.

3.1.7 Specialty Chemicals[5]

Borden Chemical, in Norristown, PA uses MC in liquid chemical specialty product mixes. Borden indicated that the rate of MC consumption at their facility has been declining and is expected to continue to decline. No explanation was given for the consumption decrease.

3.1.7.1 Process Description. At Borden, MC is pumped from storage to three liquid chemical specialty mixing tanks. Following mixing, the liquid chemical specialty product, containing 30 percent MC, is sent to a "filler" where pint size cans are filled at the rate of 18 gpm. The cans are then sealed and sent to packing, warehousing and marketing.



BEST COPY AVAILABLE

3.1.7.2 Current Emissions and Controls[5]. Emissions from equipment leaks, storage, and handling were 3.2 Mg at this facility in 1983. The emission levels and controls are presented in Table 3-2. Equipment leaks were the largest source of emissions, contributing 2.1 Mg. Pump seals contributed 51 percent of those emissions while valves contributed 47 percent. Borden reported the entire system is readily subject to visual inspection for liquid leaks which are obvious and that these leaks are repaired "promptly". However, since Borden did not report a definitive leak repair program, equipment leak emissions were calculated assuming uncontrolled sources. Therefore, equipment leaks at this plant may be overstated. Storage facilities emitted 0.8 Mg MC. These emissions were from four fixed roof tanks including the three specialty chemical mixing tanks. Handling losses were 0.3 Mg in 1983. These losses result from the uncontrolled loading of raw MC from tank trucks to storage tanks and from evaporation of the 30 percent MC specialty chemical solution as it passes through the "filler" which puts the product into sealed cans. There are no controls for the filler process.

Pennsylvania has adopted regulations controlling emissions from storage tanks containing volatile organic compounds. MC is not specifically excluded from these regulations. Storage tanks with capacity less than or equal to 40,000 gallons which contain VOC with vapor pressure greater than 1.5 psia under actual storage conditions must be equipped with pressure relief valves. Storage tanks with capacity greater than 40,000 gallons which contain VOC with vapor pressure greater than 1.5 psia must be equipped with an external or internal floating roof or a vapor recovery system capable of recovering at least 80 percent of the vapors emitted by the tank.

Borden storage tanks range in capacity from 3,000 to 10,000 gallons. Borden did not report any conservation vents on these tanks.

3.1.8 Unidentified Production Processes

Dow Chemical, in Midland, MI operates 8 process units using MC in production. These processes are identified as processes #5 through #12. Dow indicated that all information concerning process flowcharts and end

BEST COPY AVAILABLE

products is confidential business information. Therefore, this discussion is limited to emissions and controls used at the Dow facility.

3.1.8.1 Current Emissions and Controls[8]. Process vents and equipment leaks were the major emission sources at the Dow facility. Emissions were also reported from secondary sources, storage facilities, equipment openings, and loading and handling. In addition, Dow reported one discharge from a pressure relief device. Emissions, current controls, and control efficiencies for this facility are presented in Table 3-2.

Combined emissions from the eight process units were 1450 Mg in 1983. Emissions from process vents were 1120 Mg (77 percent of total emissions). Three process vents in process #12 emitted 811 Mg of total process vent emissions. Dow considers information on process vents and controls confidential for all processes except for an uncontrolled overheads receiver emitting 0.2 Mg/yr in process #5 and an uncontrolled storage tank emitting 129 Mg/yr in process #9. Dow reported the storage tank as a process vent. It is filled almost continuously and pumped out in batches. There are sixteen process vent emission points in the eight processes. Michigan has no regulations controlling VOC emissions from process vents.

Equipment leaks from process component leaks were 207 Mg at the Midland facility. Process components for processes #8, #10, and #12 emitted 60.1 Mg (29 percent), 27.6 Mg (13 percent), and 68.7 Mg (33 percent) respectively. Overall, the greatest sources of equipment leaks were valves (90.6 Mg, 44 percent), flanges (75.6 Mg, 37 percent), and pressure relief devices (27.2 Mg, 13 percent).

Equipment leaks are not controlled by Michigan state regulations. Monitoring programs vary widely in the degree of sophistication for different process units at this facility. Processes #11 and #12 are equipped with a continuous air monitor with 20 area sampling probes located throughout the process areas. The monitors are regularly standardized and calibrated and provide continuous sampling with time weighted average composition data. In addition to continuous air monitoring, shift personnel are responsible for 24 hour per day coverage



BEST COPY AVAILABLE

and equipment inspection. There are also scheduled preventive maintenance inspections for all pressure relief devices and critical instruments. Shift inspection and preventive maintenance inspections are also practiced at processes #5, #7, and #9, and are the only fugitive monitoring practices at these process areas.

Process area #8 is equipped with a chromatographic air monitoring device in addition to shift inspection and annual preventive maintenance. The system is alarmed and operators have been instructed on how to respond to this alarm by finding and correcting problems.

A MC air monitoring program is conducted quarterly in the process #10 area. Dow reported a $40,000 cost plus $10,000 for maintenance. This process area is also subjected to shift inspections and an annual preventive maintenance program.

Dow indicated process #6 is experimental in nature. Therefore, equipment leak monitoring is limited to inspection by operating technicians.

Although Dow reported several monitoring and inspection programs for equipment leaks, they did not report a repair program. Therefore, equipment leak emissions were calculated using uncontrolled emission factors, and emission levels may be overstated somewhat.

Emissions from secondary sources were 88.5 Mg at the Dow facility. Dow uses biological treatment or incineration to treat or dispose of process waste streams. Emissions from incineration are negligible, therefore all secondary emissions are a result of biological treatment. Michigan does not regulate VOC emissions from secondary sources.

Storage facility emissions were 29.0 Mg in 1983. Storage tanks range in volume from 30 gallons to 47,000 gallons and include pressure vessels and fixed roof tanks. Control techniques employed include vapor return, scrubbers, carbon adsorption systems, pressure relief devices, and conservation vents. The only reported control efficiency was for vapor return, estimated by Dow as 100 percent. However, only 98 percent control efficiency is accepted without supporting test data. Michigan has adopted regulations controlling storage of organic compounds having a true vapor pressure of more than 1.5 psia, but less than 11 psia, in existing stationary vessels of more than 40,000 gallon capacity. The

BEST COPY AVAILABLE



C1

vapor pressure of MC at 20°C (68°F) is approximately 6.75 psia, and MC is not specifically excluded from regulation in Michigan. The regulations require that the storage tank be a pressure tank, or be equipped with a floating cover with closure seal or seals, or be equipped with a vapor recovery system capable of 90 percent recovery. Dow has one fixed roof storage tank with capacity exceeding 40,000 gallons (a 47,000 gallon tank). The tank is only equipped with a pressure relief device.

Losses from equipment openings were 4.3 Mg in 1983. Losses were reported for all processes except for process #9 where Dow indicated all equipment is drained or pumped out before maintenance work. According to Dow, the equipment is empty when opened and estimated losses are minimal. Process #12 was the largest source of equipment opening losses where 2.5 Mg MC were emitted. There are no regulations in Michigan requiring control of these emissions.

Loading and handling emissions were 2.7 Mg in 1983. Methylene chloride is received by tank truck, rail car, in drums, or through direct pipeline transfer from other processes within the Dow facility. Additionally, product containing MC from process #9 is loaded into tank cars and tank trucks. At process #5, a vapor balance line is used between tank trucks and storage tanks to prevent filling losses during transfer. At process #9, connection lines are blown empty with inert gas before disconnecting to prevent spills. Process #10 receives MC by rail car; the car is pressurized with nitrogen to help the transfer. Following transfer the rail car is vented to the atmosphere. MC is unloaded via pump at process #12. Dow reported that since pressure transfer is not used there are no loading losses. Other processes either receive MC in drums or from other processes or have "negligible" handling losses. Michigan requires submerged fill pipes in ozone attainment areas for VOC loading facilities handling 5,000,000 gal/year or more of VOC with a true vapor pressure greater than or equal to 1.5 psia.

A corrosion failure of a storage tank neck resulted in a discharge of 0.1 Mg MC to the air in 1983. Dow reported the spilled material was contained in a dike. Dow reported this corrosion failure as a pressure relief device discharge.



BEST COPY AVAILABLE

3.1.9 Vinyl Chloride Monomer

Methylene chloride is produced as a by-product of Vinyl Chloride Monomer (VCM) manufacturing by Shell Oil Company in Deer Park, TX. This MC is sold as light ends.

3.1.9.1 Process Description[9]. Vinyl chloride (VC) is produced by the thermal dehydrochlorination (cracking) of ethylene dichloride (EDC). The cracking of EDC occurs according to the non-catalytic reaction:

$$\underset{\text{(ethylene dichloride)}}{CH_2ClCH_2Cl} \longrightarrow \underset{\text{(vinyl chloride)}}{C_2CHCl} + \underset{\text{(hydrogen chloride)}}{HCl}$$

Operating the process at high pressures results in higher yield, fewer by-products, and allows easier separation of the VCM product from unreacted EDC and by-products.

3.1.9.2 Current Emissions and Controls[10]. Total MC emissions were 0.06 Mg at this facility. Emissions are low because Shell did not report a MC concentration greater than 0.6 percent in its process streams and 0.004 percent in its storage tanks. Therefore, process emissions, equipment leaks, and equipment opening losses were reported as minimal prior to control. In addition, Shell operates two organic chloride incinerators at the Deer Park facility. Therefore, process emissions following incineration are insignificant. Four fixed roof storage tanks are controlled by compression and incineration and have negligible emissions. The total MC emissions of 0.06 Mg resulted from an unidentified waste stream being sent to a biotreatment process. These secondary source emissions are reported in Table 3-2.

3.1.10 Plastics Production

General Electric in Pittsfield, MA, uses MC in a plastics production operation. General Electric considers information concerning process description and end products confidential.

3.1.10.1 Current Emissions and Controls[11]. Process vents and process component leaks were the major emission sources at the General Electric facility. Emissions were also reported for secondary sources,

BEST COPY AVAILABLE

storage facilities, equipment openings, and loading and handling. Emission sources, current controls, control efficiencies, and emission levels are presented in Table 3-2.

Total methylene chloride emissions at this facility were 74.0 Mg in 1983. Emissions from process vents were 64.9 Mg MC (88 percent of total MC emissions). General Electric reported thirteen process vents with three vents controlled by condensers. A precipitation condenser vent and a dryer vacuum pump are both controlled by condensers operating at 50 percent MC removal efficiency. Emissions from these vents after control were 27.2 Mg and 9.8 Mg respectively. The precipitation condenser vent is the largest single MC emission point at the facility. A methylene chloride still vent is controlled by a condenser operating at 97 percent MC removal efficiency. Emissions from this vent were 8.2 Mg. The ten remaining process vents are uncontrolled. Emissions range from 4.6 Mg for reactor area ventilation to 0.9 Mg for the methylene chloride still water tank.

Equipment leaks resulted in MC emissions of 6.1 Mg. Valves emitted approximately 3.1 Mg MC (51 percent). Pump seals and flanges emitted 1.0 Mg (16 percent) and 0.8 Mg (13 percent), respectively. General Electric reported that there is no automated leak detection system for MC. Any significant MC leaks are generally determined by operator observation. Also, a weekly mass balance inventory is maintained for MC usage. Substantial increases over the normal process usage requirements initiates a full system investigation to determine if any leakages are occurring. Since General Electric did not report a leak repair program, uncontrolled emission factors were used to calculate equipment leak emissions, possibly resulting in an overestimate of these emissions.

Equipment opening losses were approximately 2.3 Mg in 1983. General Electric estimated this loss for approximately 2000 openings, 1300 of which were an end cap reactor nozzle opened each batch to add reactants. In addition, another reactor nozzle is opened 650 times per year. Other equipment openings involved work-up tanks, Westfalia centrifuges, filter feed tanks, filters, methylene chloride stills and separator/decant tank. General Electric provided on overall equipment opening loss estimate and did not identify emissions by specific sources.



BEST COPY AVAILABLE

General Electric maintains five fixed roof storage tanks containing MC. The emissions from these tanks totalled 0.3 Mg. The tanks range in volume from 250 gallons to 4100 gallons. Three of the tanks are vented to a vent condenser with 50 percent control efficiency. Two other tanks emissions are piped to a controlled tank, while one tank is uncontrolled.

Through September, 1983, MC was delivered in 55 gallon drums. The MC was pumped from the drums into dry MC tanks for process use. General Electric estimated that emissions from this operation were 0.2 Mg. In September 1983, a bulk handling system became operational. Tank truck deliveries are now made to a fixed roof 4100 gallon storage tank. The tank car feed line is connected to a pump at the storage tank base and delivered into the storage tank. Vapors are piped to the plant vent system, which condenses most of the MC vapors. General Electric reported air intake is through a cannister and a vacuum relief valve.

Two waste streams emitted about 0.2 Mg MC in 1983. The major secondary emission source is a liquid stream to a sewage treatment plant which emits 0.15 Mg of MC. A second waste stream was unidentified. This stream is contained in drums which are sent to a licensed hazardous waste disposal company. Emissions (0.01 Mg) occur when the waste stream is transferred to drums.

Massachusetts has adopted regulations for control of VOC emissions from specific sources such as surface coating operations. Methylene chloride is not specifically excluded from these regulations. However, none of the regulations are applicable to chemical production facilities.

## 3.2 COST OF ADDITIONAL CONTROL

Cost estimates were developed for control of process, equipment leak and storage emissions at each chemical production facility where these emissions are presently not well controlled. The cost of controlling loading and handling emissions at these facilities was not calculated since these emissions were low (4.4 Mg from all 12 facilities) and control would not be cost effective. The methodology used for

BEST COPY AVAILABLE

estimating costs is presented in Appendix D. A summary of the cost effectiveness to control these emission sources in presented in Table 3-3 and discussed in the following sections.

Table 3-4 summarizes the estimated MC emission reductions as a function of cost effectiveness. The emission reductions are shown by the emission types as well as the total for the entire miscellaneous production category. A total emission reduction of 4200 Mg (40 percent) is technically feasible.

### 3.2.1 Control of Process Vent Emissions

The cost of controlling MC process vent emissions by incineration was estimated for the miscellaneous production facilities reporting process vent emissions. MC emissions can be reduced by 3780 Mg (94 percent) by incineration. The cost effectiveness of controlling MC process vent emissions ranges from a net credit of $64,800/Mg VOC at the General Electric/Mount Vernon facility to a cost of $33,000,000/Mg VOC at the General Electric/Schenectady facility where process vent emissions are only 0.012 Mg of VOC.

### 3.2.2 Control of Equipment Leaks

Emissions from equipment leaks totalled 550 Mg MC at the chemical plants using MC in production. As discussed in previous sections, several chemical plants have inspection programs for detection of equipment leaks, but do not mention or define repair programs. For this reason, it was assumed that no equipment leak controls were in place. Therefore, costs were estimated for adding controls at all miscellaneous production facilities except for Mobay/Kansas City, where emissions from equipment leaks were only 0.02 Mg MC. The control techniques costed are those required under the benzene fugitives NESHAP and are shown in Appendix C.

The estimated costs effectiveness for controlling equipment leak emissions range from $142/Mg of VOC to $4,320/Mg of VOC. Methylene chloride equipment leak emissions could be reduced by 49 percent (268 Mg/yr) if additional controls were used at all of the chemical production facilities.



BEST COPY AVAILABLE

BEST COPY AVAILABLE

## TABLE 3-3 COST OF ADDITIONAL CONTROLS AT CHEMICAL PLANTS USING MC IN PRODUCTION

| Company/Location | Emission Type | Control* | Control Efficiency (%) | MC/VOC Emission Reduction (Mg/yr) | Capital Cost ($10^3$ $) | Recovery Credit ($10^3$ $) | Net Annual Cost ($10^3$ $) | Cost Effectiveness MC ($/Mg) | Cost Effectiveness VOC ($/Mg) |
|---|---|---|---|---|---|---|---|---|---|
| General Electric Pittsfield, MA | Process | Incineration | 98 | 63.3/ 63.3 | 4,430 | 1,270 | 2,190 | 34,600 | 34,600 |
| | Equipment leaks | | 59 | 3.6/ 6.6 | 17.6 | 2.7 | 9.9 | 2,750 | 1,490 |
| | Storage | FR-PO | 94 | 0.1/ 0.1 | 11.5 | 0.0 | 3.0 | 37,100 | 37,100 |
| | Storage | COND | 85 | 0.1/ 0.1 | 222 | 0.1 | 58.2 | 573,000 | 573,000 |
| | Storage | COND | 70 | 0.1/ 0.1 | 111 | 0.1 | 29.0 | 348,000 | 348,000 |
| General Electric Mount Vernon, IN Bldg. 4 | Process | Incineration | 98 | 282/282 | 74,300 | 71,220 | -18,300 | -64,800 | - 64,800 |
| General Electric Mount Vernon, IN Bldg. 13 | Process | Incineration | 98 | 582/582 | 73,300 | 81,700 | -24,500 | -42,100 | - 42,100 |
| General Electric Mount Vernon, IN Bldg. 14/16 | Process | Incineration | 98 | 1150/1150 | 2,220 | 1170 | 40,500 | 35.2 | 35.2 |
| | Equipment leaks | | 41 | 72.3/124 | 122 | 52.1 | 17.6 | 244 | 142 |
| General Electric Mount Vernon, IN Bldg. 15/31 | Process | Incineration | 98 | 600/600 | 5,760 | 5,910 | 3,220 | 5,370 | 5,370 |
| | Equipment leaks | | 74 | 53.4/ 80.8 | 156.5 | 34.9 | 26.1 | 490 | 323 |
| | Storage | FR-SS | 97 | 2.0/ 2.0 | 16.7 | 1.6 | 2.8 | 1,360 | 1,360 |
| General Electric Schenectady, NY | Process | Incineration | 98 | 0.01/ 0.01 | 1,180 | 0.0 | 402 | 33,000,000 | 33,000,000 |
| Celanese Rock Hill, SC | Equipment leaks | | 49 | 10.8/ 17.0 | 30.1 | 7.3 | 15.4 | 1,430 | 904 |
| Borden Chemical Norristown, PA | Equipment leaks | | 59 | 1.2/ 2.0 | 12.7 | 0.9 | 8.7 | 6,960 | 4,320 |
| | Storage | FR-PO | 94 | 0.4/ 0.4 | 11.5 | 0.2 | 2.8 | 7,130 | 7,130 |
| | Storage | FR-PO | 94 | 0.2/ 0.7 | 11.5 | 0.1 | 2.9 | 13,600 | 4,100 |
| | Storage | FR-PO | 94 | 0.1/ 0.3 | 11.5 | 0.0 | 3.0 | 30,300 | 9,100 |
| | Storage | FR-PO | 94 | 0.1/ 0.2 | 11.5 | 0.0 | 3.0 | 53,300 | 16,000 |
| Borden Chemical Fremont, CA | Process | Incineration | 98 | 2.2/ 2.2 | 5,210 | 708 | 1,160 | 533,000 | 533,000 |

(Continued)

TABLE 3-3 CONTINUED. COST OF ADDITIONAL CONTROLS AT CHEMICAL PLANTS USING MC IN PRODUCTION

| Company/Location | Emission Type | Control[a] | Control Efficiency (%) | MC/VOC Emission Reduction (Mg/yr) | Capital Cost ($10^3$ $) | Recovery Credit ($10^3$ $) | Net Annual Cost ($10^3$ $) | Cost Effectiveness MC ($/Mg) | Cost Effectiveness VOC ($/Mg) |
|---|---|---|---|---|---|---|---|---|---|
| B.F. Goodrich Cleveland, OH Plant I | Equipment leaks | | 68 | 3.1/ 7.8 | 26.6 | 3.0 | 10.1 | 3,270 | 1,310 |
| | Storage | FR-PO | 94 | 0.1/ 0.1 | 11.6 | 0.1 | 3.0 | 21,100 | 21,100 |
| B.F. Goodrich Cleveland, OH Plant II | Process | Incineration | 98 | 7.3/ 7.3 | 1,210 | 0.0 | 3,420 | 56,800 | 56,800 |
| | Equipment leaks | | 68 | 6.8/ 8.0 | 18.7 | 3.7 | 10.0 | 1,470 | 1,250 |
| | Storage | COND | 85 | 0.1/ 0.1 | 111 | 0.0 | 29.1 | 542,000 | 542,000 |
| | Storage | COND | 85 | 0.1/ 0.1 | 111 | 0.1 | 29.0 | 257,000 | 257,000 |
| | Storage | COND | 85 | 0.3/ 0.3 | 111 | 0.2 | 28.9 | 95,000 | 95,000 |
| Dow Chemical(#5) Midland, MI | Process | Incineration | 98 | 1.7/ 2.1 | 1,220 | 0.0 | 412 | 244,000 | 196,000 |
| | Equipment leaks | | 58 | 4.8/ 7.1 | 16.9 | 3.1 | 8.9 | 1,860 | 1,250 |
| Dow Chemical(#6) Midland, MI | Process | Incineration | 98 | 65.3/ 65.3 | 1,210 | 0.0 | 421 | 6,430 | 6,430 |
| | Equipment leaks | | 66 | 10.9/ 18.4 | 19.6 | 7.8 | 7.2 | 660 | 393 |
| Dow Chemical(#7) Midland, MI | Process | Incineration | 98 | 53.0/ 53.2 | 1,180 | 0.0 | 402 | 7,580 | 7,550 |
| | Equipment leaks | | 75 | 4.1/ 4.7 | 19.2 | 2.2 | 7.9 | 1,910 | 1,670 |
| Dow Chemical(#8) Midland, MI | Process | Incineration | 98 | 51.5/ 53.1 | 2,480 | 1,490 | 1,700 | 33,000 | 32,100 |
| | Equipment leaks | | 37 | 22.4/ 41.6 | 67.7 | 17.2 | 19.7 | 879 | 474 |
| Dow Chemical(#9) Midland, MI | Process | Incineration | 98 | 132/132 | 1,210 | 0.0 | 412 | 3,140 | 3,140 |
| | Equipment leaks | | 56 | 7.4/ 8.9 | 16.3 | 4.1 | 8.6 | 1,160 | 965 |
| | Storage | COND | 85 | 0.4/ 0.4 | 111 | 0.4 | 28.8 | 65,000 | 65,000 |
| | Storage | COND | 85 | 0.1/ 0.1 | 111 | 0.1 | 29.0 | 289,000 | 289,000 |
| | Storage | COND | 85 | 0.9/ 1.5 | 111 | 0.9 | 28.2 | 31,600 | 19,000 |
| | Storage[a] | FR-SS | 97 | 125/125 | 39.4 | 102 | -91.7 | -733 | -733 |
| Dow Chemical(#10) Midland, MI | Process | Incineration | 98 | 0.7/ 0.7 | 1,210 | 0.0 | 415 | 623,000 | 623,000 |
| | Equipment leaks | | 56 | 15.5/ 21.3 | 41.2 | 9.4 | 19.1 | 1,240 | 899 |
| | Storage | COND | 85 | 0.8/ 0.8 | 111 | 0.7 | 28.4 | 34,300 | 34,300 |
| Dow Chemical(#11) Midland, MI | Equipment leaks | | 44 | 3.0/ 8.7 | 18.8 | 3.3 | 11.1 | 3,720 | 1,270 |
| | Storage | FR-PO | 94 | 0.8/ 1.0 | 21.2 | 0.4 | 5.2 | 6,820 | 5,120 |
| | Storage | FR-PO | 94 | 0.1/ 0.3 | 10.6 | 0.0 | 2.7 | 36,900 | 9,200 |
| | Storage | FR-PO | 94 | 0.1/ 0.3 | 11.5 | 0.0 | 3.0 | 38,000 | 9,490 |

(Continued)



BEST COPY AVAILABLE

BEST COPY AVAILABLE

## TABLE 3-3 CONCLUDED. COST OF ADDITIONAL CONTROLS AT CHEMICAL PLANTS USING MC IN PRODUCTION

| Company/Location | Emission Type | Control[a] | Control Efficiency (%) | MC/VOC Emission Reduction (Mg/yr) | Capital Cost ($10^3$ $) | Recovery Credit ($10^3$ $) | Net Annual Cost ($10^3$ $) | Cost Effectiveness MC ($/Mg) | Cost Effectiveness VOC ($/Mg) |
|---|---|---|---|---|---|---|---|---|---|
| Dow Chemical(#12) Midland, MI | Process | Incineration | 98 | 795/865 | 1,190 | 0.0 | 424.8 | 532 | 480 |
| | Equipment leaks | | 31 | 21.1/ 44.0 | 22.1 | 17.8 | 16.3 | 770 | 370 |
| | Storage | FR-SS | 97 | 11.7/ 11.7 | 27.0 | 9.5 | -2.4 | -209 | -209 |
| | Storage | FR-SS | 97 | 3.6/ 4.0 | 15.3 | 3.1 | 0.9 | 255 | 229 |
| | Storage | COND | 85 | 4.0/ 4.5 | 111 | 3.4 | 25.7 | 6,390 | 5,750 |
| | Storage | FR-SS | 97 | 1.8/ 1.8 | 15.3 | 1.4 | 2.6 | 1,460 | 1,460 |
| | Storage | FR-SS | 97 | 1.9/ 2.5 | 12.6 | 1.7 | 1.6 | 837 | 628 |
| | Storage | FR-SS | 97 | 1.0/ 2.0 | 16.1 | 1.1 | 3.1 | 3,120 | 1,560 |
| Mobay Chemicals Kansas City, MO | Storage | FR-PO | 94 | 0.4/ 0.4 | 14.4 | 0.2 | 3.6 | 9,660 | 9,660 |
| Mobay Chemicals | Process | Incineration | 98 | 0.12/ 0.12 | 1,190 | 0.0 | 403 | 3,420,000 | 3,420,000 |
| Baytown, TX | Equipment leaks | | 54 | 27.4 /74.4 | 72.3 | 36.5 | 43.0 | 1,570 | 578 |

[a] Abbreviations
FR-SS: Floating roof with primary and secondary seals.
FR-PO: Floating roof with primary seals only.
COND: Refrigerated condenser.

[a] Storage tank discussed previously under process vent emissions.

TABLE 3-4. ESTIMATED MC EMISSION REDUCTIONS FOR OTHER CHEMICAL PLANTS AS A FUNCTION OF COST EFFECTIVENESS

| Cost Effectiveness Range ($/Mg VOC) | Nationwide MC Emission Reduction (Mg/Yr) | | | |
|---|---|---|---|---|
| | Process | Equipment Leak | Storage | Total |
| Credit | 864 | - | 137 | 1000 |
| 0 - 500 | 1940 | 208 | 3.6 | 2150 |
| 501 - 1000 | --- | 33.7 | 1.9 | 35.6 |
| 1001 - 2000 | --- | 25.4 | 4.8 | 30.2 |
| 2001 - 5000 | 132 | 1.2 | 0.2 | 133.4 |
| >5000 | 845 | --- | 4.7 | 850 |
| TOTAL | 3780 | 268 | 152 | 4200 |



BEST COPY AVAILABLE

### 3.2.3 Control of Storage Emissions

Cost estimates were developed for control of storage tanks containing MC. In 1983, emissions from these storage tanks were estimated to be 31.0 Mg/yr of MC. Three control options were evaluated: contact internal roof with a primary seal (FR-PO), contact internal roof with a secondary seal (FR-SS), and a refrigerated condenser. The most cost effective option is presented in Table 3-3.

The estimated cost effectiveness of controlling storage emissions at CFC facilities ranges from a net credit of $209/Mg of VOC to $573,000/Mg of VOC. The additional storage controls costing less than $2,000/Mg of VOC would reduce MC emissions by 27.6 Mg (85 percent).

BEST COPY AVAILABLE

## 3.3 REFERENCES


1. PEI Associates, Inc. Occupational Exposure and Environmental Release Assessment of Methylene Chloride. Prepared for the U.S. Environmental Protection Agency. Washington, D.C. (Contract No. 68-02-3935). April 1985.

2. Letter and attachments from Pullen, J.C., Celanese, to Farmer, J.R., EPA/ESED. April 3, 1985. Response to MC 114 questionnaire.

3. Letter and attachments from Perkins, D.K., General Electric, to Farmer, J.R., EPA/ESED. April 4, 1985. Response to MC 114 questionnaire.

4. Letter and attachments from Granger, L.S., Mobay Chemicals, to Farmer, J.R., EPA/ESED. April 9, 1985. Response to MC 114 questionnaire.

5. Letter and attachments from Springer, C.R., Borden Chemical, to Farmer, J.R., EPA/ESED. February 15, 1985. Response to MC 114 questionnaire.

6. Letter and attachments from Holbrock, W.C., B.F. Goodrich, to Farmer, J.R., EPA/ESED. February 5, 1985. Response to MC 114 questionnaire.

7. Letter and attachments from Drake, A.L., General Electric, to Farmer, J.R., EPA/ESED. April 9, 1985. Response to MC 114 questionnaire.

8. Letter and attachments from Arnold, S.L., Dow Chemicals, to Farmer, J.R., EPA/ESED. February 22, 1985. Response to MC 114 questionnaire.

9. TRW, Inc. Vinyl Chloride - A Review of National Emission Standards. Prepared for the U.S. Environmental Protection Agency. Research Triangle Park, North Carolina. EPA-450-3-82-003. February 1982.

10. Letter and attachments from Gillespie, T.E., Shell Oil, to Farmer, J.R., EPA/ESED. January 31, 1985. Response to MC 114 questionnaire.

11. Letter and attachments from Thayer, J.H., General Electric, to Farmer, J.R., EPA/ESED. April 3, 1985. Response to MC 114 questionnaire.




BEST COPY AVAILABLE

# 4.0 SOLVENT DEGREASING OPERATIONS

About 10 percent (21,300 Mg) of the total methylene chloride (MC) produced in 1983 was consumed in degreasing operations. It is estimated that of this amount about 17,700 Mg were emitted to the atmosphere. Methylene chloride was used as a solvent for degreasing in a variety of industries, primarily within five distinct Standard Industrial Classifications (SIC). Emissions from degreasing operations were estimated in this study by obtaining the 1983 consumption of MC for each user industry and applying it to an emission factor derived for degreasing operations. The following sections present a brief discussion of the types of degreasers, emissions, emissions control, estimates of emissions from degreasing operations in 1983, and estimates of the costs associated with emissions control. Due to the large number of degreasing facilities in these industries, no attempt was made in this study to identify locations of individual degreasers.

## 4.1 INDUSTRY DESCRIPTION

Degreasing is an integral part of many industrial processes such as the manufacture of automobiles, electronics, furniture, appliances, jewelry, and plumbing fixtures. It is also used to a minor extent in the textiles, paper, plastics, and glass manufacturing industries. The degreasing process makes use of nonaqueous or aqueous solvents to clean and remove debris from a surface prior to painting, plating, assembly, repair, inspection, or other treatment. Various solvents, including petroleum distillates, chlorinated hydrocarbons, ketones, and alcohols are used either alone or in blends for degreasing purposes.[1] Five major industry groups used MC in degreasing operations. These are furniture and fixtures (SIC 25), fabricated metal products (SIC 34), electric and electronic equipment (SIC 36), transportation equipment (SIC 37), and miscellaneous manufacturing industries (SIC 39).[2]



BEST COPY AVAILABLE

## 4.2 DEGREASING EQUIPMENT

There are three basic types of degreasing equipment: cold cleaners, open top vapor degreasers, and conveyorized degreasers. Cold cleaners are usually the simplest and least expensive type of degreaser. Individual cold cleaners consist of a tank of solvent with a cover for nonuse periods. More sophisticated cold cleaners may have solvent sumps, spray nozzles, drains, and automatic controls. In the typical cold cleaning process, soiled objects are dipped into the solvent bath until the soils are dissolved from the surface. The cleaning process can be enhanced by agitating the solvent, and brushing or spraying soiled parts. Solvents are normally used at room temperature, but in some applications may be heated to a temperature below the boiling point of the solvent.[1]

Open top vapor degreasers are similar in configuration to cold cleaners but are operated in a different manner. Open top vapor degreasers are operated at an elevated temperature to boil the solvent. The vapors from the boiling solvent condense on and clean soiled objects. A typical open top vapor degreaser consists of a tank equipped with a heating and cooling system. The heating coils on the inside bottom of the tank boil the solvent, thereby generating the vapors needed for cleaning. Cooling coils located near the top and on the inside perimeter of the tank condense solvent vapors, preventing them from diffusing out of the tank. Thus, a controlled vapor zone is created within the tank. Soiled objects are lowered into the vapor zone where solvent condenses on their surfaces and dissolves the soils. When condensation ceases, the cleaned objects are withdrawn. Only halogenated solvents are used for vapor degreasing because, in addition to their excellent cleaning properties, they are nonflammable and because their heavy vapors can be easily contained within the machine.[1]

Conveyorized degreasers feature automated conveying systems for continuous cleaning of parts. Conveyorized degreasers clean either by cold cleaning or vapor degreasing, although most clean using vaporized

BEST COPY AVAILABLE

solvent. While these units tend to be the largest degreasers, they are enclosed systems and actually produce less emissions per part cleaned than other types of degreasers.[1]

## 4.3 EMISSIONS FROM DEGREASING OPERATIONS

National emission estimates for degreasing operations were calculated from 1983 MC consumption data provided by the Halogenated Solvents Industry Alliance (HSIA).[2] The consumption data were used in conjunction with emission factors generated from available literature to estimate nationwide emissions.[1] A brief description of the estimation procedure follows.

Available data indicate that 67 percent of all MC consumed in degreasing operations is used in cold cleaning while about 33 percent is used in vapor degreasing.[3] Previous EPA studies estimated that for every kg of a solvent used in cold cleaning, 0.43 kg are emitted. The corresponding emission factor for open top vapor degreasing is 0.785 kg/kg consumed and for conveyorized degreasing is 0.85 kg/kg consumed.[4] Assuming that vapor degreasing use of MC is divided equally between open top and conveyorized degreasing processes, a weighted average emission factor of 0.56 kg/kg MC consumed was calculated. It was assumed that the remaining 0.44 kg/kg MC consumed would be recycled.

Based on information from solvent recyclers,[5] it was estimated that about 75 percent of all waste solvent from degreasing (0.44 kg/kg MC consumed) is recovered and reused. Therefore, total MC consumption by a degreaser equals consumption of fresh solvent plus consumption of recycled solvent. As before, 0.56 kg/kg of the recycled solvent is emitted. Taking into account the emission of recycled solvent, it is estimated that for every kg of fresh MC used in degreasing, 0.83 kg is emitted. The remaining 0.17 kg is assumed to be either incinerated or disposed of in a landfill according to applicable regulations. Appendix C presents the details of these material balance calculations.

The total 1983 MC emissions for each of the five SICs were estimated by applying the 0.83 kg factor to the 1983 MC consumption figure. Table 4-1 shows the estimated MC emissions from degreasing operations in these industries.



BEST COPY AVAILABLE

TABLE 4-1. 1983 MC EMISSIONS FROM DEGREASING OPERATIONS, BY INDUSTRY

| Industry (SIC Code) | Emissions (Mg/yr) |
|---|---|
| Furniture and Fixtures (25) | 1,140 |
| Fabricated Products (34) | 4,130 |
| Electrical and Electronic Equipment (36) | 4,910 |
| Transportation Equipment (37) | 2,170 |
| Miscellaneous Manufacturing Industries (39) | 5,360 |
| TOTAL | 17,700 |

BEST COPY AVAILABLE



'76

Emissions were also estimated for each State in the U.S. The MC emissions were estimated by assuming that emissions are proportional to the number of employees for a given industry in each State. The total number of employees in each of the five industry groups was estimated from U.S. Department of Commerce data.[6] For example, the emissions in Illinois from the fabricated products manufacturing industry (SIC 25) were estimated as follows:

- Furniture and fixtures manufacturing consumption of MC in 1983 = 1,370 Mg.

- $1{,}370 \text{ Mg} \times 0.83 \frac{\text{Mg emitted}}{\text{Mg consumed}} = 1{,}140 \text{ Mg emitted.}$

- The number of employees within the furniture and fixtures manufacturing industry for Illinois = 18,700.

- Total number of employees within the furniture and fixtures manufacturing industry = 438,000.

- $\text{Illinois emissions} = 1{,}140 \times \frac{18{,}700}{438{,}000} = 50 \text{ Mg}$

This procedure was followed for each industry identified to use MC in degreasing operations. The totals for industry groups were then aggregated for each state. The results are presented in Table 4-2.

## 4.4 EMISSIONS CONTROL

Control methods specified in the CTG and BID for degreasing are summarized in Table 4-3.[1,7] These methods include add-on equipment as well as improved work practices.

Add-on equipment for control of degreaser emissions includes adding covers to equipment openings, increasing freeboard area, adding freeboard chillers, and providing drainage racks for parts. These



BEST COPY AVAILABLE

TABLE 4-2. 1983 METHYLENE CHLORIDE EMISSIONS FROM DEGREASING OPERATIONS, BY STATE

| State | Emissions (Mg) | State | Emissions (Mg) |
|---|---|---|---|
| Alabama | 240 | Montana | 5 |
| Alaska | 1 | Nebraska | 70 |
| Arizona | 180 | Nevada | 30 |
| Arkansas | 140 | New Hampshire | 100 |
| California | 2,320 | New Jersey | 760 |
| Colorado | 190 | New Mexico | 30 |
| Connecticut | 500 | New York | 1,470 |
| Delaware | 20 | North Carolina | 550 |
| District of Columbia | 3 | North Dakota | 10 |
| Florida | 490 | Ohio | 930 |
| Georgia | 280 | Oklahoma | 160 |
| Hawaii | 10 | Oregon | 70 |
| Idaho | 10 | Pennsylvania | 940 |
| Illinois | 1,180 | Puerto Rico | 140 |
| Indiana | 610 | Rhode Island | 400 |
| Iowa | 230 | South Carolina | 160 |
| Kansas | 130 | South Dakota | 20 |
| Kentucky | 200 | Tennessee | 410 |
| Louisiana | 140 | Texas | 880 |
| Maine | 60 | Utah | 60 |
| Maryland | 200 | Vermont | 50 |
| Massachusetts | 700 | Virginia | 260 |
| Michigan | 810 | Washington | 250 |
| Minnesota | 280 | West Virginia | 40 |
| Mississippi | 200 | Wisconsin | 440 |
| Missouri | 370 | Wyoming | 1 |
| | | TOTAL | 17,700 |

BEST COPY AVAILABLE

TABLE 4-3. EXAMPLE CONTROL TECHNIQUES FOR DEGREASERS

| Degreaser Type | Control Devices | Operating Practices |
|---|---|---|
| Cold Cleaners | Cover for tank<br>Parts drainage rack<br>Raised freeboard[a] | Keep cover closed when degreaser not in use<br>Fully drain cleaned parts |
| Vapor Degreasers | Cover for tank<br>Freeboard chiller[b]<br>Raised freeboard<br>Carbon adsorber | Keep cover closed when degreaser not in use<br>Fully drain cleaned parts<br>Move parts slowly into and out of degreaser |
| Conveyorized Degreasers | Port Covers<br>Freeboard chillers<br>Carbon adsorbers | Maintain conveyor at moderate speed<br>Keep exhaust ventilation rates moderate |

[a]Freeboard is the distance from the liquid solvent surface or top of the solvent vapor to the lip of the tank. "Raised freeboard" is a physical extension of the freeboard to reduce drafts, and thereby solvent evaporation, within the degreaser.

[b]Additional cooling coils above the primary coils to further inhibit the diffusion of solvent vapors to the atmosphere.



BEST COPY AVAILABLE

devices limit evaporation losses from solvent baths and solvent carry-out. More sophisticated control techniques include carbon adsorption to recover solvent vapors.

Work practices can be improved to limit solvent emissions from degreasing. These improvements, characterized by practices that reduce solvent exposure to the atmosphere, include: keeping degreaser covers closed, fully draining parts prior to removal from degreaser, maintaining moderate conveyor speeds, and keeping ventilation rates moderate.

## 4.5 COST OF EMISSIONS CONTROL

The costs for controlling emissions from model degreasing facilities have been estimated in previous EPA-sponsored studies.[7,8,9] The purpose of the cost evaluation effort for this document is to update the costs presented in the earlier EPA studies. Costs are presented for a representative size degreaser for each of three degreaser types: (1) cold cleaners, (2) open top vapor degreasers, and (3) conveyorized vapor degreasers. The cost estimates are for retrofitting existing degreasing facilities. Tables 4-4, 4-5, and 4-6 present the retrofit cost estimates for cold cleaners, open top vapor degreasers, and conveyorized vapor degreasers, respectively. The costs estimated in the previous EPA study are in fourth quarter 1980 dollars. These costs were updated to fourth quarter 1984 dollars using the plant cost indexes (323.6/269.7=1.2).[10,11]

Several assumptions concerning degreaser operating parameters were made in developing costs for controlling emissions from the three types of degreasers. It was necessary to assume operating parameters for typical uncontrolled and controlled degreasers so that average emission reductions for each type of degreaser could be determined.

In developing cold cleaner control costs the degreaser size was assumed to be 0.4 $m^2$ and the annual period of operation was assumed to be 500 hours (2 hrs/day, 5 days/week, 50 wks per year). The uncontrolled emissions were based on a cold cleaner with a 0.3 freeboard ratio and a manual cover. Total emissions from this uncontrolled cold



BEST COPY AVAILABLE

TABLE 4-4. RETROFIT CONTROL COSTS FOR COLD CLEANERS
(FOURTH QUARTER 1984 DOLLARS)

| Cost Component | 0.7 FBR,[a] Manual Cover and Drain |
|---|---|
| Capital Costs, ($) | |
| Freeboard (installed) | 357 |
| Drain | 25 |
| Installation Costs, $ | |
| Freeboard (in purchase cost) | |
| Drain | 13 |
| Annual Operating Costs, #/yr | |
| Capital Charges[b] | 47 |
| Administration, Insurance, and Taxes[c] | 14 |
| Added Labor[d] | 285 |
| Maintenance[e] | 11 |
| Utilities | 0 |
| Total Annualized Cash, $/Yr | |
| Emission Reduction, Mg/Yr | 0.4 |
| Recovered Solvent Credit, $/Yr[f] | 194 |
| Net Annualized Cost, $/Yr | 163 |
| Cost Effectiveness, $/Mg | 410 |

[a]Freeboard ratio.

[b]Total Installed Capital Cost annualized over 15 years at a 10 percent interest rate.

[c]Four percent of total installed capital cost.

[d]Labor due to drain time requirement, based on 20 loads per day, 15 second drain time per load.

[e]Three percent of total installed capital cost.

[f]Based on solvent price of $0.485 per kilogram.



BEST COPY AVAILABLE

BEST COPY AVAILABLE

TABLE 4-5. RETROFIT CONTROLS COSTS FOR OPEN TOP VAPOR DEGREASERS
(FOURTH QUARTER 1984 DOLLARS)

| | Cover 0.75 FBR[a] | Automatic Cover 0.75 FBR | Cover Above Freezing FBC[b,c] | Cover Below Freezing FBC[c] | Cover, Carbon Adsorber |
|---|---|---|---|---|---|
| Capital Costs, $ | | | | | |
| Cover | 1,238 | 3,832 | 1,238 | 1,238 | 1,238 |
| 0.75 Freeboard | 1,012 | 268 | 1,012 | 1,012 | 1,012 |
| Refrig. Freeboard | - | - | - | - | - |
| Carbon Adsorber | - | - | - | - | - |
| Auxiliary Equipment | 595 | 595 | 595 | 595 | 595 |
| Added Plant Space | - | - | - | - | - |
| Installation Costs, $ | | | | | |
| Cover | 136 | 203 | 136 | 136 | 136 |
| 0.75 Freeboard | 136 | 136 | 136 | 136 | 136 |
| Refrig. Freeboard | - | - | - | - | - |
| Carbon Adsorber | - | - | - | - | 5,950 |
| Auxiliary Equipment | 136 | 136 | 136 | 136 | 136 |
| Total Capital Costs, $ | 3,253 | 5,170 | 8,499 | 13,021 | 18,366 |
| Operating Costs, $/yr | | | | | |
| Capital Charges $/yr.[d] | 427 | 679 | 1,117 | 1,711 | 2,413 |
| Administration, Ins., Taxes[e] | 130 | 207 | 45 | 68 | 97 |
| Maintenance[f] | 98 | 155 | 34 | 51 | 72 |
| Added Labor | 570 | - | 570 | 570 | 570 |
| Utilities | | | | | |
| Electricity | - | - | 71 | 98 | 208 |
| Steam | - | - | - | - | 201 |
| Water | - | - | - | - | 26 |

(continued)

TABLE 4-5 CONCLUDED. RETROFIT CONTROLS COSTS FOR OPEN TOP VAPOR DEGREASERS
(FOURTH QUARTER 1984 DOLLARS)

| | Cover 0.75 FBR[a] | Automatic Cover 0.75 FBR | Cover Above Freezing FBC[b,c] | Cover Below Freezing FBC[c] | Cover, Carbon Adsorber |
|---|---|---|---|---|---|
| Total Annualized Costs, $/Yr | 1,225 | 1,041 | 1,837 | 2,498 | 3,587 |
| Emission reduction, Mg/yr | 1.84 | 2.86 | 3.19 | 3.19 | 3.89 |
| Recovered solvent credit, $/yrs | 892 | 1,387 | 1,547 | 1,547 | 1,887 |
| Net annual control cost, $/yr | 333 | -346 | 290 | 951 | 1,700 |
| Cost Effectiveness, $/Mg | 180 | 10 | 90 | 300 | 440 |

[a]Freeboard Ratio.

[b]Refrigerated freeboard chiller.

[c]Also require 0.75 freeboard ratio.

[d]Total installed capital cost annualized over 15 years at a 10 percent interest rate.

[e]Four percent of total installed capital cost.

[f]Three percent of total installed capital cost.

[g]Based on solvent price of $0.485 per kilogram.



BEST COPY AVAILABLE

TABLE 4-6. RETROFIT CONTROL COSTS FOR CONVEYORIZED DEGREASERS
(FOURTH QUARTER 1984 DOLLARS)

| | RFC[a] | Carbon Adsorber | Adsorber Drying Tunnel |
|---|---|---|---|
| Capital Costs, $ | | | |
| Refrig. Freeboard | 14,994 | 0 | 0 |
| Carbon Adsorber | 0 | 58,310 | 58,310 |
| Auxiliary | 0 | 0 | 11,900 |
| Installation Costs, $ | | | |
| Refrig. Freeboard | 407 | 0 | 0 |
| Carbon Adsorber | 0 | 11,900 | 11,900 |
| Auxiliary Equipment | 0 | 0 | 2,380 |
| Additional Plant Space | 175 | 4,998 | 5,998 |
| Total Capital Costs, $ | 15,576 | 75,208 | 90,488 |
| Operating Costs, $/Yr | | | |
| Capital Charges[b] | 2,047 | 9,882 | 11,890 |
| Adm., Ins., & Taxes[c] | 623 | 3,008 | 3,620 |
| Operating Labor | 0 | 0 | 0 |
| Maintenance[d] | 467 | 2,256 | 2,715 |
| Utilities | | | |
| Electricity | 195 | 277 | 277 |
| Steam | - | 626 | 626 |
| Cooling Water | - | 62 | 62 |
| Total Annualized Cost, $/Yr | 3,332 | 16,111 | 19,190 |
| Emission Reduction, Mg/Yr | 9.84 | 10.9 | 12.4 |
| Recovered Solvent Credit, $/Yr[e] | 4,772 | 5,287 | 6,014 |
| Net Annualized Costs, $/Yr | -1,440 | 10,824 | 13,176 |
| Cost of Control, $/Mg | -150 | 990 | 1,060 |

[a]Refrigerated freeboard chiller.

[b]Total installed capital cost annualized over 5 years at a 10 percent interest rate.

[c]Four percent of total installed capital cost.

[d]Three percent of total isntalled capital cost.

[e]Based on solvent price of $0.485 per kilogram.

BEST COPY AVAILABLE

cleaner were estimated to be 1,140 kg/yr. The controlled emissions were based on a cold cleaner with a 0.75 freeboard ratio, a manual cover and a drainage rack. Total emissions from this cold cleaner were estimated to be 740 kg/yr. It is estimated that a 35 percent emissions reduction can be achieved with a raised freeboard, a manual cover, and a drainage rack.[9,12,13]

For open top vapor degreaser (OTVD) control cost development degreaser size was assumed to be 1.5 $m^2$ and an operating schedule of 1,500 hours (6 hrs/day, 5 days/wk, 50 wks/yr) was used. The uncontrolled emissions were based on an OTVD with a freeboard ratio of 0.5 and were estimated to be 8,770 kg/yr. This estimate assumes an 8-hour working day during which the degreaser is uncovered for 6 of these hours; the degreaser is idle for the remaining 2 hours. Five control options for OTVDs were investigated, including covers and raised freeboards, automated covers and raised freeboards, above-freezing refrigerated chillers, below freezing refrigerated chillers, and carbon adsorption systems. The control costs are presented in Table 4-5, and are based on the following: (1) utilization of a cover with a control efficiency of 90 percent during idle time; (2) reduction of 15 percent in vaporization losses by increasing the freeboard ratio from 0.5 to 0.75; (3) reduction of 40 percent in vaporization losses by use of either above- or below-freezing chillers; (4) reduction of 40 percent in vaporization losses due to the use of an automated cover; (5) reduction of 65 percent in vaporization losses due to the use of a carbon adsorber; and (6) a 10 percent reduction in carry out losses due to use of a refrigerated freeboard device. Overall achievable emission reductions with these techniques were estimated to range from 21 percent to 44 percent.[9,12,13]

Conveyorized degreaser control cost estimates were based on a degreaser 3.0 $m^2$ in size with an operating schedule of 2,000 hours. (8 hrs/day, 5 days/wk, 50 wks/yr) Uncontrolled emissions for a typical conveyorized degreaser were estimated to be about 21,800 kg/yr. Three control options were examined for costing purposes, including refrigerated freeboard chillers, carbon adsorbers, and carbon adsorbers along with a drying tunnel. Control costs are presented in



BEST COPY AVAILABLE

Table 4-6 and are based on the following: (1) a 45 percent reduction in solvent loss due to the use of refrigerated freeboard chillers; (2) a 50 percent reduction in solvent loss due to the use of a carbon adsorber; and (3) a 15 percent reduction in carry-out emissions only, due to the use of a drying tunnel. Achievable emission reductions using these techniques are estimated to range from 45 percent to 57 percent.[9,12,13]

Estimates of the national emission reduction associated with controlling MC emissions from degreasers were made using: (1) emission factors developed for uncontrolled cold cleaners, open top vapor degreasers, and conveyorized vapor degreasers; and (2) the estimated total number of uncontrolled degreasers in MC service in 1983. It is estimated that about 6,590 Mg/yr MC emissions can be reduced by the application of control techniques on uncontrolled cold cleaners, open top vapor degreasers, and conveyorized vapor degreasers. This represents a 37 percent reduction in MC emissions from degreasers. Potential MC emission reductions for each type of degreaser are 2,360 Mg/yr (cold cleaners), 1,770 Mg/yr (open top vapor degreasers), and 2,460 Mg/yr (conveyorized vapor degreasers). The details of the calculations for estimating national emission reduction are presented in Appendix D.

## 4.6 REGULATORY REQUIREMENTS

EPA has approved RACT guidelines for solvent degreasing operations that have been adopted by 32 States and the District of Columbia. The 10 States that have the highest estimated emissions of MC from solvent degreasing, California, Ohio, New York, Michigan, Illinois, Pennsylvania, Indiana, Texas, Massachusetts, and New Jersey, have all adopted EPA-approved RACT. These 10 States account for about 59 percent of total degreasing emissions of MC. In addition, EPA has proposed (but not promulgated) an NSPS that would control emissions from new solvent degreasers.

BEST COPY AVAILABLE

## 4.7 REFERENCES


1. Bollinger, J.C., and J.L. Shumaker. Control of Volatile Organic Emissions from Solvent Metal Cleaning. U.S. Environmental Protection Agency. Research Triangle Park, N.C. Publication No. EPA-450/2-77-022. November 1977. 203 p.

2. Letter from Morgan, D.L., Cleary, Gottlieb, Steen, and Hamilton, to Rosensteel, R.E., EPA. February 22, 1985. HSIA data on methylene chloride production and consumption.

3. Tang, J.L. Industrial Survey of Halogenated Solvent Producers and Degreaser Manufacturers. GCA/Technology Division, Chapel Hill, North Carolina. July 1981.

4. Hoogheem, T.J., D.A. Horn, T.W. Hughes, and P.J. Marn (Monsanto Research Corporation). Source Assessment: Solvent Evaporation - Degreasing Operations. Prepared for U.S. Environmental Protection Agency. Cincinnati, OH. Publication No. EPA-600/2-79-019f. August 1979. 133 p.

5. Telecon. Pandullo, R.F., Radian Corporation, with Pokorny, J., Baron-Blakeslee, Inc. March 19, 1985. General information on solvent recycling.

6. Bureau of the Census. County Business Patterns 1982. U.S. Department of Commerce. Washington, D.C. Publication No. CBP-82. October 1984.

7. GCA Corporation. Organic Solvent Cleaners - Background Information for Proposed Standards. Prepared for U.S. Environmental Protection Agency. Research Triangle Park, N.C. Publication No. EPA-450/2-78-045a. October 1979. 282 pp.

8. Memo from O'Brian, T., GCA, to D.A. Beck, EPA/CPB. March 2, 1982. Estimation of Solvent-Specific Control Costs.

9. Memo from Smith, M., GCA, to D.A. Beck, EPA/CPB. August 20, 1981. Background Information on Cost Analysis for Emission Guideline Document for Organic Solvent Cleaners.

10. Chemical Engineering plant cost index. Chemical Engineering, Volume 88, Number 8.

11. Chemical Engineering plant cost index. Chemical Engineering, Volume 92, Number 6.

12. Westlin, P.R., and J.W. Brown, Test Report-Solvent Drainage and Evaporation from Cold Cleaner Usage. U. S. Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, North Carolina, January 1978.




BEST COPY AVAILABLE

13. Suprenant, K.S. and D.W. Richards. Study to Support New Source Performance Standards for Solvent Metal Cleaning Operations. Prepared by the Dow Chemical Company for the U. S. Environmental Protection Agency, Contract No. 68-02-1329. April 1976.

BEST COPY AVAILABLE

# 5.0 PHOTORESIST STRIPPING OPERATIONS

About five percent of the methylene chloride (MC) produced in 1983 was used as a photoresist stripping solvent in the electronics industry during the production of printed circuit boards. It was not within the scope of this study to make direct contact with all manufacturers of printed circuit boards or to verify the exact number of facilities presently in operation. Emissions from photoresist stripping operations in printed circuit board manufacturing were estimated in this study by obtaining the 1983 MC consumption for printed circuit board manufacturing and applying an emission factor derived for photoresist stripping operations. It is estimated that in 1983, about 11,900 Mg of MC were consumed in photoresist stripping operations and about 6,800 Mg were emitted to the atmosphere.

## 5.1 INDUSTRY DESCRIPTION

Photoresist stripping is an operation used in the electronics industry during the production of printed circuit boards. The processing of copper-clad laminated circuit boards into printed circuit boards occurs in several basic steps. First, a polymer-based photoresist chemical is applied to the entire circuit board surface and is masked with the appropriate design. Next, the photoresist is exposed to light. Further, the photoresist is developed using a solvent to remove unwanted resist. Finally, the exposed copper is etched with acid and the remaining resist is stripped away with methylene chloride.[1]

Three types of systems are employed in the production of printed circuit boards. These are (a) solvent systems, which use methylene chloride as the stripper solvent and 1,1,1-trichloroethane as the developer solvent; (b) semi-aqueous systems; and (c) aqueous systems. The semi-aqueous system and aqueous systems do not use methylene chloride as a stripper solvent. Solvent systems may use pure methylene chloride or a blend of methylene chloride, with an alcohol (usually methanol) as the stripper solvent.



BEST COPY AVAILABLE

Overall, there is a trend away from solvent stripping systems toward semi-aqueous or aqueous systems. This has been due primarily to the growing concern for minimizing exposure to halogenated hydrocarbon solvents. Further, solvent systems have higher operating costs because of high solvent costs, solvent recovery equipment costs, and waste disposal expenses.[1] However, despite the fact that there is a trend away from solvent systems, there is indication that for printed circuit boards requiring high resolution, solvent systems will continue to be used.[2]

## 5.2 EMISSIONS AND CONTROL TECHNIQUES

National emission estimates for photoresist stripping operations were calculated from 1983 MC consumption data provided by the Halogenated Solvents Industry Alliance (HSIA).[3] The consumption data were used in conjunction with an emission factor generated from industry contacts.

Based on information from an industry representative, it was estimated that for every kg of methylene chloride consumed in photoresist stripping 0.25 kg is emitted directly to the atmosphere.[4] It was assumed that the remaining 0.75 kg/kg of methylene chloride goes to recycling. Further, information from solvent recyclers indicates that about 75 percent of all recycled solvent from photoresist stripping is recovered and reused. Therefore, total MC consumption in photoresist stripping equals consumption of fresh solvent plus consumption of recycled solvent. As before 0.25 kg/kg of the recycled solvent is emitted. Taking into account the emission of recycled solvent, it is estimated that for every kg of fresh solvent used in photoresist stripping, 0.57 kg is emitted. Appendix C presents the details of these material balance calculations. The remaining 0.43 kg is assumed to be either incinerated or disposed of in a landfill according to applicable regulations.

The total 1983 MC emissions for photoresist stripping were estimated for each State in the U.S. The MC emissions were estimated by assuming that emissions are proportional to the number of employees for

BEST COPY AVAILABLE

the printed circuit board manufacturing industry in each State. The total number of employees in printed circuit board manufacturing was estimated from U.S. Department of Commerce data.[5] For example the emissions in Illinois were estimated as follows:

- Printed circuit board manufacturing nationwide consumption of MC in 1983 = 11,900 Mg
- 11,900 Mg x 0.57 $\frac{\text{Mg emitted}}{\text{Mg consumed}}$ = 6,800 Mg nationwide emissions
- The number of employees within printed circuit board manufacturing in Illinois = 11,600
- Total number of employees within printed circuit board manufacturing industry = 215,000
- Illinois emissions = 6,800 Mg x $\frac{11,600}{215,000}$ = 370 Mg

This procedure was followed for each State and the results are presented in Table 5-1.

A broad survey of individual facilities using MC was not conducted regarding controls commonly applied within the industry. Consequently, the current status of control technology could not be ascertained. However, one printed circuit board manufacturer indicated that carbon adsorption was being used to control MC emissions from photoresist stripping operations.[6]

## 5.3 REGULATORY REQUIREMENTS

Currently only California has regulations affecting photoresist stripping operations in printed circuit board manufacturing. However, MC is exempt from these regulations because it is not considered to be an ozone precursor.



BEST COPY AVAILABLE

TABLE 5-1. 1983 METHYLENE CHLORIDE EMISSIONS FROM PHOTORESIST STRIPPING OPERATIONS, BY STATE

| State | Emissions (Mg) | State | Emissions (Mg) |
|---|---|---|---|
| Alabama | 130 | Montana | 0 |
| Alaska | 1 | Nebraska | 5 |
| Arizona | 70 | Nevada | 5 |
| Arkansas | 5 | New Hampshire | 130 |
| California | 1,910 | New Jersey | 340 |
| Colorado | 70 | New Mexico | 10 |
| Connecticut | 250 | New York | 1,020 |
| Delaware | 20 | North Carolina | 30 |
| District of Columbia | 5 | North Dakota | 5 |
| Florida | 260 | Ohio | 140 |
| Georgia | 20 | Oklahoma | 60 |
| Hawaii | 20 | Oregon | 50 |
| Idaho | 5 | Pennsylvania | 290 |
| Illinois | 370 | Puerto Rico | 120 |
| Indiana | 40 | Rhode Island | 40 |
| Iowa | 30 | South Carolina | 15 |
| Kansas | 20 | South Dakota | 5 |
| Kentucky | 10 | Tennessee | 30 |
| Louisiana | 0 | Texas | 160 |
| Maine | 30 | Utah | 0 |
| Maryland | 50 | Vermont | 5 |
| Massachusetts | 570 | Virginia | 50 |
| Michigan | 50 | Washington | 0 |
| Minnesota | 200 | West Virginia | 0 |
| Mississippi | 5 | Wisconsin | 40 |
| Missouri | 60 | Wyoming | 0 |
| | | TOTAL | 6,800 |

BEST COPY AVAILABLE

## 5.4 REFERENCES


1. PEI Associates, Inc., 1985. Occupational Exposure and Environmental Release Assessment of Methylene Chloride. Prepared for Office of Pesticides and Toxic Substances. U.S. Environmental Protection Agency. Washington, D.C. April 12, 1985.

2. Telecon. R. H. Howle, Radian with D. Berdman, Institute for Interconnecting and Packaging Electronic Circuits. April 23, 1985. Emissions of methylene chloride from photoresist stripping.

3. Letter from Morgan, D.L. of Cleary, Gottlieb, Steen and Hamilton to R.E. Rosensteel, EPA/ESED, March 8, 1985. Halogenated Solvents Industry Alliance (HSIA) information on consumption of methylene chloride.

4. Telecon. Pandullo, R.F., Radian Corporation with J. Pokorny, Baron-Blakeslee, Inc. March 19, 1985. General information on solvent recycling.

5. Bureau of the Census. County Business Patterns. 1982. U.S. Department of Commerce. Washington, D.C. Publication No. CBP-82. October 1984.

6. Telecon. R.H. Howle, Radian with R. Jensen, AT&T. April 23, 1985. Emissions of methylene chloride from photoresist stripping.




BEST COPY AVAILABLE

# 6.0 FOAM MANUFACTURING

The foam manufacturing industry consumed about 7 percent (14,200 Mg) of the methylene chloride (MC) produced in 1983. It is estimated that 100 percent of the MC consumed in foam manufacturing was emitted to the atmosphere.

There have been 85 foam manufacturing plants in the United States identified by this study. The States having the most manufacturers are California (12 plants), Texas (10 plants), North Carolina (7 plants), Indiana (6 plants), and Mississippi (6 plants).[1] It is unlikely that all of these foam plants consume, and thus, emit MC. However, it was not within the scope of this study to identify the locations of all foam manufacturing plants using MC.

## 6.1 INDUSTRY DESCRIPTION

Methylene chloride is used as an auxiliary blowing agent in the production of flexible urethane foam slabstock. The primary blowing agent is carbon dioxide which forms from the reaction of two basic formulation ingredients of the foam. Auxiliary blowing agents are used when softer foams are required. The cushioning nature of the foam is due to minute foam cells that are formed by the gaseous blowing agents. It has been reported that most foam manufacturing facilities have traditionally used CFC-11 as the auxiliary blowing agent.[2] MC is also used often because it is a relatively inexpensive agent compared to CFC-11. However, its higher boiling point requires more heat to initiate reaction than do chlorofluorocarbons and thus the reaction is more difficult to control.[1]

Methylene chloride and other ingredients are pumped to a mixing head and discharge nozzle positioned at the opening of a foam tunnel. The material is then expelled onto a conveyor belt within the foam tunnel. The exothermic reaction of materials in the tunnel vaporizes the blowing agent, forming cells in the foam. This curing process continues as the material passes through the tunnel, exiting as formed slabstock ready to be sawed into slabs and later packaged for shipment.[1]



BEST COPY AVAILABLE

## 6.2 CURRENT EMISSIONS AND CONTROLS

Methylene Chloride emissions result from vaporization in the foam tunnel primarily, but also may result from storage tanks, equipment leaks and vaporization of residual MC in the foam curing area. Based on information from an industry representative it is estimated that well over 50 percent of MC emissions from foam manufacturing processes are from the foam tunnel itself, with the remainder emitted during storage, transfer, or use.[3] Industry contacts have indicated the foam plants are typically uncontrolled.[3,4]

The Halogenated Solvents Industry Alliance reported that the foam blowing industry consumed approximately 14,200 Mg of MC in 1983.[5] It was assumed for the purposes of this study that all MC consumed is eventually emitted to the atmosphere. Emissions from foam manufacturing are presented by State in Table 6-1. These emission estimates are estimated by State according to the consumption distribution provided by HSIA.

BEST COPY AVAILABLE

Table 6-1. 1983 MC EMISSIONS FROM FOAM MANUFACTURING, BY STATE

| STATES | ANNUAL EMISSIONS (Mg) |
|---|---|
| Arkansas | 340 |
| California | 3,060 |
| Colorodo | 120 |
| Florida | 350 |
| Georgia | 670 |
| Hawaii | 120 |
| Illinois | 370 |
| Indiana | 690 |
| Kentucky | 120 |
| Maryland | 230 |
| Massachusetts | 230 |
| Michigan | 540 |
| Minnesota | 120 |
| Mississippi | 960 |
| Ohio | 230 |
| Oregon | 300 |
| Pennsylvania | 580 |
| New Jersey | 230 |
| New York | 120 |
| North Carolina | 1,970 |
| Rhode Island | 780 |
| South Carolina | 120 |
| Tennessee | 610 |
| Texas | 1,130 |
| Virginia | 110 |
| Washington | 100 |
| TOTAL | 14,200 |



BEST COPY AVAILABLE

## 6.3 REFERENCES


1. Thomas Register of American Manufacturers and Thomas Register Catalogue File. 69th Edition. Thomas Register Publishing Company, New York, New York, 1979 and 1985.

2. Mooz, W.E., S.H. Dole, D.L. Jaquette, W.H. Krase, P.F. Morrison, S.L. Salem, R.G. Salter, and K.A. Wolf, Rand Corporation, 1982. Technical Options for Reducing Chlorofluorocarbon Emissions. Prepared for U.S. Environmental Protection Agency. R-2879-EPA.

3. Telecon. Pandullo, R.F., Radian with H. Stone, General Foam. April 22, 1985. Information on operating parameters for foam manufacturing.

4. Telecon. Pandullo, R.F., Radian with A. Pereira, Foamex Products. April 22, 1985. Information on use of methylene chloride on foam manufacturing.

5. Letter from Morgan, D.L. of Cleary, Gottlieb, Steen and Hamilton to R.E. Resensteel, EPA:ESED. March 8, 1985. Halogenated Solvents Industry Alliance information on consumption of methylene chloride.


BEST COPY AVAILABLE

# 7.0 PHARMACEUTICAL MANUFACTURING

The pharmaceutical industry used approximately 6 percent (13,200 Mg) of total methylene chloride (MC) production in 1983. Methylene chloride is used in pharmaceutical manufacturing as a general solvent, as an extraction solvent, and in tablet coatings. Previous EPA studies indicate that there are over 800 pharmaceutical plants in the United States and its territories[1], although only a fraction of these plants likely use MC. Prior EPA reports indicate that in addition to its use in tablet coatings, MC is used in the manufacture of antibiotics, steroids, and vitamins, and specifically in the production of reserpine, cephalothin, cephaliride, cepharin, tolbutamide, and estrone.[2,3] The exact locations of all pharmaceutical plants using MC have not been identified in this study.

## 7.1 INDUSTRY DESCRIPTION

Pharmaceuticals typically are manufactured in a series of batch operations. The following description represents a likely sequence of operations. The solvent is received and stored in tanks ranging from 20,000 to 110,000 liters (5,280 to 29,100 gallons) capacity. From storage the solvent is piped directly to a glass - or stainless steel-lined reactor. A typical batch reactor has a capacity of 2,000 to 11,000 liters (500-3000 gallons). To begin a production cycle, the reactor is washed and dried with the solvent. After washing occurs, air or nitrogen is commonly used to purge the reactor. Solid reactants and solvent are then charged to the reactor which is equipped with a condenser. After the reaction cycle is finished, the unreacted volatile compounds and remaining solvent are cleared from the reactor through distillation and condensation. The crude product is then transferred to a holding tank where it is washed with water or solvent to remove any remaining reactants or by-products. Next, the crude product undergoes one of several separation processes.



BEST COPY AVAILABLE

Typical separation processes include distillation, extraction, and filtering. The crude product may then be dissolved in another solvent and transferred to a crystallizer for purification. After crystallization, the solid material may be separated from the remaining solvent by centrifugation. While in the centrifuge, the product may be washed again with water or solvent. Tray, rotary, or fluid-bed dryers are then used for final product finishing.[1]

## 7.2 CURRENT EMISSIONS AND CONTROLS

At pharmaceutical plants where MC is used as a solvent, each operation within the manufacturing process, as well as the storage and handling steps, may be sources of MC emissions. The level of emissions varies significantly among different operations and depends on the quantity of solvent used, the type of equipment performing the operation, and the frequency of performing the operation. Dryers are potentially large emission sources. Emission rates from dryers vary depending on the size of the unit, the number and duration of drying cycles per year, and the amount of MC evaporated during a given drying cycle. Emissions from reactors result from the displacement of MC-laden air during reactor charging, as well as from solvent evaporation during the reaction cycle, the venting of uncondensed MC from overhead condensers during refluxing, from the purging of vaporized MC following solvent wash, and from the opening of reactors during the cycle for sampling. Distillation columns emit MC as uncondensed solvent. Storage and handling emissions result from displacement of vapors during storage tank filling and from displacement of vapors within the storage tank when temperature or atmospheric pressure changes occur.[1]

A survey of 17 ethical drug manufacturers in 1982 indicated a total annual MC purchase of about 11,400 Mg by these manufacturers. The responding firms were estimated to represent approximately one-half of the production of ethical domestic pharmaceuticals in 1982. The estimated final disposition of the above total MC usage was the following: 4,900 Mg air emissions (43 percent); 570 Mg sewer disposal (5 percent); 4,330 Mg incinerated (38 percent); 1,250 Mg contract hauled

BEST COPY AVAILABLE

(11 percent); and 340 Mg disposed of off-site (3 percent).[4] Assuming the same disposition for 1983 consumption provided by the Halogenated Solvents Industry Alliance, estimated air emissions are 5,700 Mg.[5]

Individual facilities using MC were not contacted regarding the control techniques commonly used within the industry. Consequently, the current status of control technology for pharmaceutical manufacturing could not be ascertained. However, the controls available to the industry include condensers, absorbers, carbon adsorbers and, in some cases, incinerators. Storage and transfer emissions can be controlled by vapor return lines, conservation vents, vent scrubbers, pressurized storage tanks, and floating roof storage tanks.[1]



BEST COPY AVAILABLE

## 7.3 REFERENCES


1. U.S. Environmental Protection Agency. Control of Volatile Organic Emissions From Manufacture of Synthesized Pharmaceutical Products. Office of Air Quality Planning and Standards. EPA-450/2-78-029. December 1978.

2. PEI Associates, Inc., 1985. Occupational Exposure and Environmental Release Assessment of Methylene Chloride. Prepared for Office of Pesticides and Toxic Substances. U.S. Environmental Protection Agency. Washington, D.C. April 12, 1985.

3. Memorandum and attachments from M.A. Callahan, TSPC Solvents Work Group #2 to M.C. Bracken, Toxic Substances Priorities Committee. February 1, 1982. Summary of data collection and analysis efforts of the TSPC Sources and Exposure Work Group.

4. Letter and attachment from T.X. White, Pharmaceutical Manufacturers Association (PMA) to D.A. Beck, EPA:ESED. June 1984. Emissions of selected organic compounds in the pharmaceutical industry.

5. Letter from Morgan, D.L. of Cleary, Gottlieb, Steen and Hamilton to R.E. Rosensteel, EPA:ESED. April 11, 1985. Halogenated Solvents Industry Alliance information on consumption of methylene chloride.

6. Letter from Morgan, D.L. of Cleary, Gottlieb, Steen and Hamilton to R.E. Rosensteel, EPA:ESED. June 28, 1985. Clarification of Halogenated Solvents Industry Alliance information on consumption of methylene chloride.


BEST COPY AVAILABLE

# 8.0 PESTICIDE MANUFACTURING

Pesticide manufacturing accounted for about one percent (2,700 Mg) of total methylene chloride (MC) consumption in 1983.[1] Methylene chloride has several applications in the pesticide industry. It is used for extraction, phase separations, purifications, crystallization, and as a general transport solvent.[2,3,4] Previous studies indicate that there are about 140 individual pesticide facilities in the United States manufacturing one or more pesticides.[5] Of these, a fraction are users of MC.

According to information provided by the Halogenated Solvents Industry Alliance (HSIA), pesticide facilities in three cities accounted for about 77 percent of total 1983 use of MC in pesticide production.[1] The facilities in these cities were identified from a list of pesticide manufacturers in the available literature.[6] No attempt was made in this study to verify the amount of MC used by these facilities.

Three additional pesticide facilities accounting for about 2 percent of total MC production in 1983 were identified directly through a telephone survey.[2,3] The identified pesticide facilities and associated 1983 methylene chloride consumption volumes are presented in Table 8-1.

## 8.1 INDUSTRY DESCRIPTION

The methods and exact technology for manufacturing pesticides varies considerably depending on the type of pesticide. The pesticide industry employs the same unit processes and operations used in the chemical processing industry. These include chemical reactions, filtering, separation operations, condensation, and drying. Production processes are usually carried out at ambient or slightly above ambient temperatures. Elemental chlorine is the raw material common to most pesticide production and is also frequently used to prepare other raw material used for pesticide production. The raw materials, intermediates, by-products, and products may be highly toxic to certain plants and animals, including man.[5]



BEST COPY AVAILABLE

TABLE 8-1. 1983 CONSUMPTION OF METHYLENE CHLORIDE IN PESTICIDE MANUFACTURING

| Company/Location | Consumption/Emissions (Mg/yr) |
|---|---|
| Chevron Chemical Company<br>Richmond, CA | 740 |
| Union Carbide<br>Woodbine, GA | 1060 |
| Great Lakes Chemical Company<br>El Dorado, AR | 265 |
| Buckman Laboratories<br>Memphis, TN | 26 |
| Buckman Laboratories<br>Cadet, MO | 7 |
| Rhone-Poulenc Chemical Company<br>Mt. Pleasant, TN | 12 |
| Unidentified | 590 |
| TOTAL | 2,700 |

BEST COPY AVAILABLE

## 8.2 EMISSIONS AND CONTROLS

Air emissions from pesticide facilities include particulates, gases, and vapors which may emanate from process equipment at each step of the manufacturing process. There is indication that evaporation of wastewater from holding ponds may be a significant source, although few quantitative data are available.[5] The limited data gathered in this source assessment study indicate that primary MC emission sources are equipment leaks, and waste treatment facilities as well as emissions from control devices such as condensers and scrubbers.[2,3,4] It is likely that most of the MC consumption in pesticide manufacturing is emitted to the atmoshpere. In this study it was assumed that all the MC consumed in pesticide manufacturing during 1983 was emitted.

It was not within the scope of this study to undertake a comprehensive survey of the control techniques commonly used within the industry. Consequently, typical control levels for pesticide manufacturing could not be ascertained. However, the control techniques employed by two pesticide facilities using MC that were contacted include condensers, recycling systems, refrigerated condensers, and incinerators.[2,4]



BEST COPY AVAILABLE

## 8.3 REFERENCES


1. Letter from Morgan, D.L., Cleary, Gottlieb, Steen and Hamilton. March 8, 1985. HSIA information on methylene chloride consumption.

2. Letter from Hentschel, M.K., Buckman Laboratories, to J.A. Kowalski, Radian. March 22, 1985. Information on methylene chloride use.

3. Letter from Embry, W.A., Rhone-Poulenc, to J.A. Kowalski, Radian. March 14, 1985. Information on methylene chloride use.

4. Letter from Nevin, J.B., Chevron, to J.A. Kowalski, Radian. May 1, 1985. Information on methylene chloride use.

5. Archer, S.R., W.R. McCurley, and G.S. Rawlings. 1978 Source Assessment: Pesticide Manufacturing Air Emissions - Overview and Prioritization. EPA-600/2-78-004d Prepared for U.S. Environmental Protection Agency. Office of Research and Development. Washington, D.C.

6. SRI Directory of Chemical Producers-1983. SRI International. Menlo Park, California.


BEST COPY AVAILABLE

# 9.0 DISTRIBUTION FACILITIES

Virtually all methylene chloride (MC) produced is sold through chemical distributors. There are an estimated 300 chemical distributors handling chlorinated solvents. Table 9-1 presents the five largest MC distributors. These distributors handle about 40 percent of the total MC sold through distributors. In general, distributors maintain as few as three to as many as 65 regional distribution facilities spread out across the nation. One chemical distributor estimated the number of regional distribution facilities at 500 nationwide.[2] Each district distributor receives chemicals directly from the producer by tank truck or railcar. Transportation is provided by the distributor. The received chemicals are stored by district distributors in 8,000 to 20,000 gallon fixed-roof storage tanks. The storage tanks used by district distributors include vertical, horizontal, and underground tanks. Turnover times for storage tanks typically range from 2 weeks to a little over a month. Although the exact number of distributors and distribution facilities that handle MC is not known, it is estimated that there are 109 MC storage tanks owned by distributors, the majority of which are fixed roof tanks. The procedure used to estimate the number of tanks is given in Appendix E.

## 9.1 EMISSIONS FROM DISTRIBUTION FACILITIES

Emissions from distribution facilities can be categorized as two types, storage and handling. Storage emissions include breathing and working losses from tanks. Handling emissions result from vapor displacement when drums and tank trucks are filled.

Storage and handling emissions of MC from distribution facilities were estimated using AP-42 emission factors[4] and data supplied by the major distributors. The details of those calculations are presented in Appendix E. It is estimated that approximately 490 Mg of MC were emitted in 1983 from distribution facilities. Storage emissions accounted for 280 Mg, while handling emissions were about 210 Mg.



BEST COPY AVAILABLE

## 9.2 REGULATORY REQUIREMENTS

There are State and Federal regulations that may affect methylene chloride distribution facilities. Most States have regulations for storage and handling of volatile organic liquids (VOL). However, many of these States exclude MC from their VOL regulations due to its low photochemical reactivity. Also, a Federal regulation for volatile organic liquid storage has been proposed. However, these regulations generally apply to storage tanks with a volume of 25,000 gallons or greater. According to the major distributors of MC, the size of MC storage tanks is typically 15,000 gallons or less.[5]

BEST COPY AVAILABLE

TABLE 9-1. SUMMARY OF MAJOR METHYLENE CHLORIDE DISTRIBUTORS

| Company | Number Of Distribution Facilities | Number Of MC Storage Tanks | Typical Size. (Gal) | Typical Size Turnover |
|---|---|---|---|---|
| Ashland[1] | 61 | 46 | 8,000 | 3 wks - 1 mo |
| McKesson[2] | 63 | 32 | 10,000 | N/A |
| Chem-Central[3] | 31 | 25 | 10,000 | 1 mo |
| Detrex[6] | 25 | Drum Directly | 15,000 | |
| Thompson-Hayward | 26 | 6 | 10,000 | 2 - 3 months |



BEST COPY AVAILABLE

## 9.3 REFERENCES


1. Telecon. Sterett, R., Ashland Chemical Company, with Howle, R. H., Radian Corporation. February 7, 1985. Conversation on storage of chlorinated solvents.

2. Telecon. Eisner, D., McKesson Chemical Company, with Howle, R. H., Radian Corporation. February 7, 1985. Conversation on storage of chlorinated solvents.

3. Telecon. Trice, L., Chem-Central, with Howle, R. H., Radian Corporation. February 8, 1985. Conversation on storage of chlorinated solvents.

4. U.S. Environmental Protection Agency. Compilation of Air Pollutant Emission Factors. Supplement 7. Research Triangle Park, North Carolina. Publication No. AP-42. August 1977.

5. Memorandum from Howle, R. to D. A. Beck, EPA. February 19, 1985. Distribution of Methylene Chloride, Trichloroethylene, and Perchloroethylene.

6. Telecon. Roberts, M., Detrex Chemical Industries, Inc. with Howle, R. H., Radian Corporation. February 12, 1985. Conversation on storage of halogenated solvents.

7. Telecon. Hart, W., Thompson-Hayward, with Howle, R. H., Radian Corporation. February 18, 1985. Conversation on storage of halogenated solvents.


BEST COPY AVAILABLE

# 10.0 ADDITIONAL EMISSION SOURCES OF MC

About 138,000 Mg of methylene chloride (MC) were consumed in 1983 in various uses including aerosol products, paint removers, photographic film processing, the food processing industry, and general miscellaneous applications. No attempt was made in this study to identify individual emission points for each use. However, several of these uses of MC result in emissions from the industrial point sources as well as from end use by the consumer. In general, the entire amount of MC used in these applications is emitted to the atmosphere. Table 10-1 identifies the amount of MC consumed and emitted in these additional source categories.

## 10.1 AEROSOLS

Methylene chloride is used as a solvent in aerosol products including finishes and coatings, hair sprays, cleaners, room deodorants, and various household and personal products. Approximately 52,900 Mg of MC were consumed in aerosol products in 1983.[1]

Aerosols are largely consumer products, although they are also used in industrial applications. Methylene chloride emissions from consumption of aerosol products result from the volatilization of suspended droplets or by evaporation from sprayed surfaces. Due to the nature of the use of aerosol products all MC in aerosol products (52,900 Mg in 1983) is emitted.

Emissions also occur at aerosol packaging plants due to spills and from evaporation during mixing and aerosol can charging.[2] It was outside of the scope of this study to investigate the amount of MC emitted at aerosol packaging facilities. However, those emissions are believed to be small relative to the total amount emitted nationwide from aerosol consumption.[2]





BEST COPY AVAILABLE

TABLE 10-1. ADDITIONAL USES OF METHYLENE CHLORIDE IN 1983

| Source | Consumption/ Emissions (Mg/Yr) |
|---|---|
| Aerosols | 52,900 |
| Paint Removers | 62,000 |
| Photographic (film processing) | 8,100 |
| Food Processing | 3,300 |
| Miscellaneous | 12,100 |



BEST COPY AVAILABLE

///

## 10.2 PAINT REMOVERS

Methylene chloride is used as a solvent in paint removers. The solvent is the primary ingredient in stripping formulations and acts to penetrate, soften, or dissolve the paint, film, or coating. Approximately 62,000 Mg of MC were consumed in paint removers in 1983.[1]

Paint removers, like aerosols, are used by both industry and consumers. The stripping formulation is applied to a painted surface and allowed to penetrate or dissolve the coating. The surface is then cleaned and the paint remnants are disposed. Emissions occur during application, use, and disposal of the removed coating. Due to the nature of the use of paint removers, all MC used in paint removers is eventually emitted to the atmosphere.

Methylene chloride is also emitted at paint remover formulation facilities. Emissions result from evaporation during mixing, packaging, and storage. These emission levels are believed to be low relative to the total amount of MC emitted nationwide from use of paint removers.[2]

## 10.3 PHOTOGRAPHIC FILM PROCESSING

Methylene chloride serves as a solvent in the glue used to splice film. Since the MC evaporates soon after application, emissions are assumed to be 100 percent of consumption. Total consumption and therefore emissions, of MC from splicing glue was 8,100 Mg in 1983.[1]

## 10.4 FOOD PROCESSING INDUSTRY

Methylene chloride consumption in the food processing industry was 3,300 Mg in 1983.[1] It is used as an extraction solvent in the extraction of heat sensitive substances such as caffeine, cocoa, and edible fats.[3] Specific emission sources were not identified in this study. However, major emission sources would most likely be in the extraction process and storage and handling facilities. In this study it was assumed that the entire 3,300 Mg consumed in the food processing industry in 1983 was emitted.



BEST COPY AVAILABLE

## 10.5 GENERAL MISCELLANEOUS

Approximately 12,100 Mg/yr of MC are consumed through miscellaneous end uses.[1] Examples of miscellaneous methylene chloride uses include use in the printing industry as a solvent for cleaning ink from printing equipment and as a thinning agent in some ink formations. It is also used to bond pieces of plastic together by dissolving the plastic at the interface of two pieces. After MC evaporation the pieces are "welded" together. Other uses for methylene chloride include use as a thinning agent for adhesives, and as a cleaner or in cleaning solutions. Emissions from these general miscellaneous categories are from evaporation during use. Additionally, MC may be used as a solvent or reactant in the chemical processing industry by companies not discussed in the chapter discussing chemical plants using MC in production (Chapter 3). The magnitude of MC use in these individual miscellaneous applications is not known at present. In addition, other small unknown uses of MC may also exist.

BEST COPY AVAILABLE

## 10.6 REFERENCES


1. Letter from D. L. Morgan, Cleary, Gottlieb, Steen, and Hamilton, to R. E. Rosensteel, EPA:ESED. March 8, 1985. Response for Halogenated Solvents Industry Alliance (HSIA).

2. PEI Associates, Inc. Occupational Exposure and Environmental Release Assessment of Methylene chloride. Prepared for the U. S. Environmental Protection Agency. Washington, D. C. (Contract No. 68-02-3935). April 1985.

3. Mannsville Chemical Products. Chemical Products Synopsis - Methylene chloride. Cortland, New York. 1984.




BEST COPY AVAILABLE

APPENDIX A

METHODS USED FOR ESTIMATING STORAGE TANKS AND EQUIPMENT LEAK EMISSIONS

## A.1 EMISSION FACTORS FOR FIXED-ROOF STORAGE TANKS

### A.1.1 Emission Equations

The major types of emissions from fixed-roof storage tanks are breathing and working losses. Emission equations for breathing and working losses from storage tanks were developed in EPA Publication No. AP-42. The equations used in estimating emissions rates for fixed-roof tanks storing VOL are:

- $L_T = L_B + L_W$
- $L_B = 1.02 \times 10^{-5} M_v \left(\frac{P}{14.7-P}\right) 0.68\ D^{1.73} H^{0.51} T^{0.5} F_p C K_c$
- $L_W = 1.09 \times 10^{-8} M_v P V N K_n K_c$

where, $L_T$ = total loss (Mg/yr)

$L_B$ = breathing loss (Mg/yr)

$L_W$ = working loss (Mg/yr)

### A.1.2 Parameter Values and Assumptions

The following MC physical property values, plant-specific information, and engineering assumptions were used to estimate the emission losses:

$M_v$ = molecular weight of product vapor (lb/lb mole);
for MC, $M_v = 84.93$

P = true vapor pressure of product, function of temperature.

D = tank diameter (ft); dependent upon plant-specific information.

C = tank diameter factor (dimensionless):
for diameter $\geq$ 30 feet, C = 1
for diameter < 30 feet, $C = 0.0771\ D - 0.0013(D)^2 - 0.1334$

V = tank capacity (gal); dependent upon plant-specific information

N = number of turnovers per year (dimensionless); dependent upon plant-specific information



BEST COPY AVAILABLE

$T$ = average diurnal temperature change in °F; diurnal temperature change assumptions were plant specific according to location

$F_p$ = paint factor (dimensionless); the storage tanks were assumed to be in good condition and painted white; therefore, $F_p = 1$ (see Table A-1)

$H$ = average vapor space height (ft): used tank-specific values or an assumed value of one-half the tank height (H/2)

$K_c$ = product factor (dimensionless) = 1.0 for VOL

$K_n$ = turnover factor (dimensionless); dependent upon plant-specific information

for turnovers > 36, $K_n = \frac{180 + N}{6N}$

for turnovers $\leq$ 36, $K_n = 1$

A.1.3 Sample Calculation

The following sample calculation is provided to demonstrate the evaluation of emissions from a typical fixed-roof storage tank containing MC. For the general equations,

$$L_T = L_W + L_B$$

$$L_B = 1.02 \times 10^{-5} M_v \left(\frac{P}{14.7-P}\right)^{0.68} D^{1.73} H^{0.51} T^{0.5} F_p C K_C$$

$$L_W = 1.09 \times 10^{-8} M_v PVNK_nK_C$$

where, $M_v = 84.93$

$P = 6.75$ psia (68°F)

$D = 37$ ft

$C = 1$

$V = 233{,}000$ gallons

$N = 10$

$T = 20$°F

$F_p = 1.0$

$H = 14$ ft

$K_C = 1.0$

$K_n = 1$

BEST COPY AVAILABLE

TABLE A-1. PAINT FACTORS FOR FIXED-ROOF TANKS[1]

| Tank Color | | Paint factors ($F_p$) | |
|---|---|---|---|
| | | Paint condition | |
| Roof | Shell | Good | Poor |
| White | White | 1.00 | 1.15 |
| Aluminum (specular) | White | 1.04 | 1.18 |
| White | Aluminum (specular) | 1.16 | 1.24 |
| Aluminum (specular) | Aluminum (specular) | 1.20 | 1.29 |
| White | Aluminum (diffuse) | 1.30 | 1.38 |
| Aluminum (diffuse) | Aluminum (diffuse) | 1.39 | 1.46 |
| White | Gray | 1.30 | 1.38 |
| Light gray | Light gray | 1.33 | 1.44 |
| Medium gray | Medium gray | 1.40 | 1.58 |



BEST COPY AVAILABLE

the emissions from this storage tank are:

$$L_B = 1.02 \times 10^{-5} (84.93)\left(\frac{6.75}{14.7-6.75}\right)^{0.68} (37)^{1.73}(14)^{0.51}(20)^{0.5}(1)(1)(1)$$

$$= 6.877 \text{ Mg/yr}$$

$$L_W = 1.09 \times 10^{-8} (84.93)(6.75)(233{,}000)(10)(1)(1)$$

$$= 14.560 \text{ Mg/yr}$$

$$L_T = 6.877 \text{ Mg/yr} + 14.560 \text{ Mg/yr} = 21.44 \text{ Mg/yr}$$

## A.2 EMISSION FACTORS FOR INTERNAL FLOATING ROOF STORAGE TANKS

### A.2.1 Emission Equations

Emissions from internal floating roof tanks can be estimated from the following equations:[1] (Note that these equations apply only to freely vented internal floating roof tanks.)

$$L_T = L_W + L_r + L_f + L_d$$

where, $L_T$ = the total loss (Mg/yr)

$L_W$ = the working loss (Mg/yr) = $\dfrac{(0.943)\ Q\ C\ W_L}{D}\left[1 + \left(\dfrac{N_C F_C}{D}\right)\right]/2205$

where, $D$ = tank diameter (ft)

$N_C$ = number of columns (dimensionless); (see Table A-2)

$F_C$ = effective column diameter (ft); 1.0 assumed

$L_r$ = the rim seal loss (Mg/yr) = $(K_r D)\ P^*\ M_v\ K_C/2205$

$L_f$ = the fitting loss (Mg/yr) = $(F_f)\ P^*\ M_v\ K_C/2205$

$L_d$ = the deck seam loss (Mg/yr) = $(F_d\ K_d\ D^2)\ P^*\ M_v\ K_C/2205$

### A.2.2 Parameter Values and Assumptions

The assumptions and values used to calculate emissions from internal floating roof tanks are:

Q = product average throughput (bbl/yr); tank capacity (bbl/turnover) x turnovers/yr; dependent upon plant-specific information

BEST COPY AVAILABLE

TABLE A-2. TYPICAL NUMBER OF COLUMNS AS A FUNCTION OF TANK DIAMETERS

| Tank Diameter Range D (Ft) | | | |
|---|---|---|---|
| Greater Than | And | Less Than Or Equal To | Typical Number Columns, $N_c$ |
| 0 | | 85 | 1 |
| 85 | | 100 | 6 |
| 100 | | 120 | 7 |
| 120 | | 135 | 8 |
| 135 | | 150 | 9 |
| 150 | | 170 | 16 |
| 170 | | 190 | 19 |
| 190 | | 220 | 22 |
| 220 | | 235 | 31 |
| 235 | | 270 | 37 |
| 270 | | 275 | 43 |
| 275 | | 290 | 49 |
| 290 | | 330 | 61 |
| 330 | | 360 | 71 |
| 360 | | 400 | 81 |



BEST COPY AVAILABLE

$C$ = product withdrawal shell clingage factor (bbl/$10^3$ $ft^2$); use 0.0015 bbl/$10^3$ $ft^2$ for VOL in a welded steel tank with light rust (0.0075 for dense rust)

$W_L$ = density of product (lb/gal); for MC, 11.1 lb/gal

$D$ = tank diameter (ft)

$N_C$ = number of columns (dimensionless); (see Table A-2)

$F_C$ = effective column diameter (ft); 1.0 assumed

$D$ = the tank diameter (ft); dependent upon plant-specific information

$M_V$ = the average molecular weight of the product vapor (lb/lb mole). For MC, $M_V$ = 84.93

$K_C$ = the product factor (dimensionless) = 1.0 for VOL

2205 = constant (lb/Mg)

$P^*$ = the vapor pressure function (dimensionless)

$P^* = 0.068\ P/((1 + (1 - 0.068\ P)^{0.5})^2)$

$P$ = the true vapor pressure of the material stored (6.75 psia for MC)

$K_r$ = the rim seal loss factor (lb mole/ft yr) that for an average fitting seal is as follows:

| Seal system description | $K_r$ (lb mole/ft yr) |
|---|---|
| Vapor-mounted primary seal only | 6.7 |
| Liquid-mounted primary seal only | 3.0 |
| Vapor-mounted primary seal plus secondary seal | 2.5 |
| Liquid-mounted primary seal plus secondary seal | 1.6 |

$F_f$ = the total deck fitting loss factor (lb mole/yr)

$$= \sum_{i=1}^{n} (N_{f_i} K_{f_i}) = [(N_{f_1} K_{f_1}) + (N_{f_2} K_{f_2}) + \ldots + (N_{f_n} K_{f_n})]$$

BEST COPY AVAILABLE

where, $N_{f_i}$ = number of fittings of a particular type (dimensionless). $N_{f_i}$ is determined for the specific tank or estimated from Tables A-2 and A-3. The values used for these emissions estimates are designated by * in Table A-3.

$K_{f_i}$ = deck fitting loss factor for a particular type fitting (lb mole/yr). $K_{f_i}$ is determined for each fitting type from Table A-3. The values used for these emissions estimates are designated by *.

$n$ = number of different types of fittings (dimensionless)

$F_d$ = the deck seam length factor (ft/ft$^2$)

= 0.15, for a deck constructed from continuous metal sheets with a 7 ft spacing between seams

= 0.33, for a deck constructed from rectangular panels 5 ft by 7.5 ft

= 0.20, an approximate value for use when no construction details are known

$K_d$ = the deck seam loss factor (lb mole/ft yr)

= 0.34 for nonwelded roofs

= 0 for welded decks

A.2.3 Sample Calculation

The following sample calculation is provided to demonstrate the evaluation of emissions from a typical storage tank with an internal floating roof containing MC. For the general equations,

$$L_T = L_W + L_r + L_f + L_d$$

$$L_W = \frac{(0.943)QCW_L}{D}\left[1 + \frac{N_C F_C}{D}\right]/2205$$

$$L_r = (K_r D)\ P^*\ M_v\ K_c/2205$$



BEST COPY AVAILABLE

TABLE A-3. SUMMARY OF DECK FITTING LOSS FACTORS ($K_f$) AND TYPICAL NUMBER OF FITTINGS ($N_f$)

| | Deck Fitting Type | Deck Fitting Loss Factor, $K_f$ (lb mole/yr) | | Typical Number Of Fittings ($N_f$) |
|---|---|---|---|---|
| 1. | Access Hatch | | | |
| | A. Bolted cover, gasketed | 1.6 | | 1 |
| | B. Unbolted cover, gasketed | 11 | * | |
| | C. Unbolted cover, ungasketed | 25 | | |
| 2. | Automatic Gauge Float Well | | | |
| | A. Bolted cover, gasketed | 5.1 | | 1 |
| | B. Unbolted cover, gasketed | 15 | * | |
| | C. Unbolted cover, ungasketed | 28 | | |
| 3. | Column Well | | | (see Table A-2) |
| | A. Built-up column-sliding cover, gasketed | 33 | | |
| | B. Built-up column-sliding cover, ungasketed | 47 | | |
| | C. Pipe column-flexible fabric sleeve seal | 10 | | |
| | D. Pipe column-sliding fabric gasketed | 19 | * | |
| | E. Pipe column-sliding cover, ungasketed | 32 | | |
| 4. | Ladder Well | | | 1 |
| | A. Sliding cover, gasketed | 56 | * | |
| | B. Sliding cover, ungasketed | 76 | | |
| 5. | Roof Leg or Hanger Well | | | |
| | A. Adjustable | 7.9 | * | $(5 + \frac{D}{10} + \frac{D^2}{600})^a$ |
| | B. Fixed | 0 | | |
| 6. | Sample Pipe or Well | | | 1 |
| | A. Slotted pipe-sliding cover, gasketed | 44 | * | |
| | B. Slotted pipe-sliding cover, ungasketed | 57 | | |
| | C. Sample well-slit fabric seal, 10% open area | 12 | | |
| 7. | Stub Drain, 1-inch diameter | 1.2 | * | $(\frac{D^2}{125})^b$ |
| 8. | Vacuum Breaker | | | 1 |
| | A. Weighted mechanical actuation, gasketed | 0.7 | * | |
| | B. Weighted mechanical actuation, ungasketed | 0.9 | | |

BEST COPY AVAILABLE

$$L_f = (F_f)\ P^*\ M_v\ K_c/2205$$

$$L_D = (F_d K_d D^2)\ P^*\ M_v\ K_c/2205$$

where, $M_v$ = 84.93 lb/lb mole

$P^*$ = 0.152

$Q$ = 500,000 bbl/yr

$C$ = 0.0015

$W_L$ = 11.1 lb/gal

$D$ = 30 ft

$N_c$ = 1

$F_c$ = 1.0

$K_r$ = 6.7 lb mole/ft yr

$K_c$ = 1.0

$F_f$ = 242 lb mole yr

$F_d$ = 0.20

$K_d$ = 0.34



BEST COPY AVAILABLE

the emissions from this storage tank are:

$$L_W = \left[\frac{(0.943)(500{,}000)(0.0015)(12.3)}{30}\left(1 + \frac{(1)(1)}{30}\right)\right]/2205$$

$$= 0.123 \text{ Mg/yr}$$

$$L_r = ((6.7)(30))(0.152)(84.93)(1.0)/2205$$

$$= 1.177 \text{ Mg/yr}$$

$$L_f^{\bullet} = (242)(0.152)(84.93)(1.0)/2205$$

$$= 1.417 \text{ Mg/yr}$$

$$L_D = ((0.20)(0.34)(30)^2)(0.152)(84.93)(1.0)/2205$$

$$= 0.358 \text{ Mg/yr}$$

$$L_T = 0.123 \text{ Mg/yr} + 1.177 \text{ Mg/yr} + 0.417 \text{ Mg/yr} + 0.358 \text{Mg/yr}$$

$$L_T = 3.08 \text{ Mg/yr}$$

## A.3 EQUIPMENT LEAK EMISSIONS - SAMPLE CALCULATIONS

Emissions were estimated from the number of equipment leak sources (provided by the plant), the percentage of MC in the stream (provided by the plant), and the emission factors for each type of equipment (from the SOCMI AID).[2] The following sample calculations illustrate the procedure.

| Emissions Source | Number | | % MC Service | | Mg/yr source Emission Factor[a] | | Total Emissions Mg/yr |
|---|---|---|---|---|---|---|---|
| Pump seals | 3 | x | 7.5 | x | 0.0494 | = | 0.011 |
| | 6 | x | 50.5 | x | 0.0494 | = | 0.150 |
| | 2 | x | 87.5 | x | 0.0494 | = | 0.086 |
| | 12 | x | 100.0 | x | 0.0494 | = | 0.593 |



BEST COPY AVAILABLE

| Emissions Source | Number | | % MC Service | | Mg/yr source Emission Factor[a] | | Total Emissions Mg/yr |
|---|---|---|---|---|---|---|---|
| Compressors | 1 | x | 87.5 | x | 0.228 | = | 0.200 |
| Flanges | 4 | x | 5.0 | x | 0.00083 | = | 0.0002 |
| | 112 | x | 7.5 | x | 0.00083 | = | 0.007 |
| | 30 | x | 18.0 | x | 0.00083 | = | 0.004 |
| | 235 | x | 50.5 | x | 0.00083 | = | 0.099 |
| | 66 | x | 87.5 | x | 0.00083 | = | 0.048 |
| | 456 | x | 100.0 | x | 0.00083 | = | 0.378 |
| Valves (gas) | 4 | x | 5.0 | x | 0.0056 | = | 0.001 |
| | 8 | x | 7.5 | x | 0.0056 | = | 0.003 |
| | 3 | x | 50.5 | x | 0.0056 | = | 0.008 |
| | 4 | x | 87.5 | x | 0.0056 | = | 0.020 |
| | 11 | x | 100.0 | x | 0.0056 | = | 0.062 |
| Valves (liquid) | 5 | x | 5.0 | x | 0.0071 | = | 0.002 |
| | 3 | x | 7.5 | x | 0.0071 | = | 0.002 |
| | 8 | x | 87.5 | x | 0.0071 | = | 0.050 |
| | 9 | x | 100.0 | x | 0.0071 | = | 0.064 |
| Pressure Relief Devices | 2 | x | 5.0 | x | 0.1042 | = | 0.01 |
| | 4 | x | 50.5 | x | 0.1042 | = | 0.21 |
| | 6 | x | 100.0 | x | 0.1042 | = | 0.63 |
| Sampling Connections | 5 | x | 5.0 | x | 0.0150 | = | 0.004 |
| | 3 | x | 50.5 | x | 0.0150 | = | 0.023 |
| | 1 | x | 87.5 | x | 0.0150 | = | 0.013 |
| | 3 | x | 100.0 | x | 0.0150 | = | 0.045 |
| Open Ended Lines | 1 | x | 100.0 | x | 0.0017 | = | 0.002 |
| | | | | | TOTAL | = | 2.7252 |

Annual Emissions = 2.72 kg/hr x 8760 hrs/year x Mg/1,000 kg

[a] U. S. Environmental Protection Agency. Fugitive Emission Sources of Organic Compounds - Additional Information on Emissions, Emission Reductions, and Costs. Research Triangle Park, NC. Publication No. EPA-450/3-82-010. April 1982.



BEST COPY AVAILABLE

## A.4 REFERENCES


1. U. S. Environmental Protection Agency. VOC Emissions from Volatile Organic Liquid Storage Tanks - Background Information for Proposed Standards. Research Triangle Park, North Carolina. Publication No. EPA-450/3-81-003a. July 1984. 252 pp.

2. U.S. Environmental Protection Agency. Fugitive Emission Sources of Organic Compounds - Additional Information on Emissions, Emission Reductions, and Costs. Research Triangle Park, N.C. Publication No. EPA-450/3-82-010. April 1982.


BEST COPY AVAILABLE

# APPENDIX B
# METHODS FOR ESTIMATING EMISSION CONTROL COSTS

## B.1 PROCESS VENT EMISSIONS CONTROL COST ESTIMATION

The cost estimates for process vent emission control are based on the use of thermal incineration. The procedure for estimating these costs uses the methods presented in the Air Oxidation Processes Control Techniques Guidelines (CTG) document.[1] A detailed discussion of the incinerator costing methods may be found in Chapter 5 of this document. It should be noted that these incinerator costing procedures are designed for vent streams having high flowrates. Since the vent streams containing MC generally have lower flowrates, the cost estimates for process vent emission control may be somewhat overstated. Further work will be performed to develop incinerator costing procedures for lower flowrate vent streams if regulatory development proceeds.

The total installed capital cost of control is determined using the following equation:

Total Installed Capital Cost ($10^3$\$) = (# of incinerators) x (escalation factor) x (C1 - (Waste Heat Boiler Correction Factor) + (C2 x (Flowrate per incinerator Design Vent Size Factor)$^{C3}$) + (pipe rack cost) + (additional ductwork cost)

where: C1, C2, and C3 are coefficients from Table B-1 that depend upon heating value and halogenation status of a given vent stream; waste heat boiler correction factor of 40 ($10^3$\$) is used for vent streams with flowrates below 700 scfm, where no heat recovery in a waste heat boiler is assumed; escalation factor of 0.90 deescalates costs to 1978 dollars;

design vent size factor of 0.95 increases vent stream flowrate for costing purposes;

pipe rack cost is calculated using the equation presented in Table B-2;

additional ductwork cost is calculated using the equation presented in Table B-3.



BEST COPY AVAILABLE

TABLE B-1. TOTAL INSTALLED CAPITAL COST AS A FUNCTION OF VENT STREAM FLOW RATE

| Category | Maximum Flowrate Per Unit ($10^3$ scm/min) | Minimum Net Heating Value (MJ/scm) | Maximum Net Heating Value (MJ/scm) | Fabricated Equipment Cost Escalation Factor | C1 | C2 | C3 |
|---|---|---|---|---|---|---|---|
| A1[a] | 0.74 | 0.0 | 3.5 | 0.90 | 803.11 | 12.83 | 0.88 |
| A2[a] | 0.74 | 3.5 | - | 0.90 | 786.61 | 12.44 | 0.88 |
| B | 1.42 | 0.0 | 0.48 | 0.90 | 259.88 | 4.91 | 0.88 |
| C | 1.42 | 0.48 | 1.9 | 0.90 | 297.99 | 2.84 | 0.88 |
| D | 1.25 | 1.9 | 3.6 | 0.90 | 236.35 | 3.23 | 0.88 |
| E[a] | 1.25 | 3.6 | - | 0.90 | 236.35 | 3.23 | 0.88 |

[a]Halogenated vent stream.

[b]Dilution flow rate is used in capital cost equation. Dilution flow rate = (design flow rate) x (original heating value) ÷ (3.65 MJ/scm).



BEST COPY AVAILABLE

TABLE B-2. ADDITIONAL DUCT COST[1,2]

Additional duct cost ($10^3$ \$) = (length) x (cost per unit length) x (installation factor) x (duct escalation factor) x (retrofit correction factor) ÷ 1000

Cost per unit length = 1.37L - 1.76

where L = duct diameter in inches

$$\text{Diameter} = \left[ \frac{\text{Flow rate (ft}^3\text{/min)}}{\text{Linear velocity (ft/min)}} \times \frac{4}{\pi} \right]^{0.5}$$

$$= \left[ \frac{\text{Flow rate (ft}^3\text{/min)}}{2000 \text{ ft/min}} \times \frac{4}{3.1412} \right]^{0.5}$$

if linear velocity is assumed to be 2000 ft/min

Additional duct length = 150 ft + (additional vents x 100 ft/vent)

Installation factor = 1.087

Escalation factor (from 1977 to 1978) = 1.088

Retrofit correction factor = 1.0



BEST COPY AVAILABLE

TABLE B-3. PIPE RACK COST[1,2]

Pipe rack cost ($10^3$ \$) = (pipe rack length) x (cost per unit length) x (installation factor) x (pipe rack escalation factor) x (retrofit correction factor) ÷ 1000

Pipe rack length = 250 ft + (# additional vents x 100 ft/vent)

Cost per unit length = \$32.045/ft

Installation factor = 1.087

Deescalation factor (1982 to 1978) = 0.746

Retrofit correction factor = 1.0



BEST COPY AVAILABLE

TABLE B-4. OPERATING FACTORS FOR EACH DESIGN CATEGORY

| Category | Minimum Net Heating Value (MJ/scm) | Maximum Net Heating Value (MJ/scm) | Ratio of Flue Gas Flow to Offgas Flow[a] | Heat Recovery Factor (MJ/scm) | Pressure Drop (Inches $H_2O$) | Natural Gas Use Coefficients G0 | G1 | G2 | G3 |
|---|---|---|---|---|---|---|---|---|---|
| A1[b] | 0 | 3.5 | 2.9 | 3.38 | 22[c] | 0 | 4.56 | -0.985 | 0 |
| A2[b] | 3.5 | - | 2.9 | 3.38 | 22[c] | 0 | 0.329 | 0 | 0 |
| B | 0. | 0.48 | 1.9 | 0 | 10[d] | 0.425 | 0.666 | -1.29 | 0.015 |
| C | 0.48 | 1.9 | 2.3 | 0 | 10[d] | 0 | 2.39 | -1.22 | 0 |
| D | 1.9 | 3.6 | 2.5 | 0 | 6[e] | 0 | 0.183 | 0 | 0 |
| E | 3.6 | - | 2.5 | 0 | 6[e] | 0 | 0.183 | 0 | 0 |

[a]Both at standard conditions.

[b]Offgas contains halogenated compounds.

[c]Includes 6 inches across the combustion chamber, 4 inches across the waste heat boiler, and 12 inches across the scrubber.

[d]Includes 6 inches across the combustion chamber and 4 inches across the recuperative heat exchanger.

[e]Across the combustion chamber.



BEST COPY AVAILABLE

BEST COPY AVAILABLE

TABLE B-5. ANNUALIZED COST FACTORS

All Factors are Based on June 1980

**Direct**

Operating Labor: $8.50/hr (Includes Overhead)
Operating Labor Factor: 2400 Man-hr/yr (Categories A1-A2)
2133 Man-hr/yr (Categories B-C)
1200 Man-hr/yr (Categories D-E)

Supervisory Labor: $8.50/hr x (0.15)

Total Labor: [($8.50/hr x 1.15) + (0.03 of Total Installed Capital)]

Overhead Labor: 0.80 of Total Labor
Electricity: $0.0279/kWh
Natural Gas: $4.16/GJ =
Heat Recovery Credit: $4.16/GJ =
Quench Water Price: $0.22/Thousand Gallons
Scrubbing Water Price: $0.22/Thousand Gallons
Caustic Price: $0.0436/lb[a]
Maintenance Labor Plus Materials Factor = 0.06 of Total Installed Capital

**Indirect ("Capital Charges")**

Interest Rate = i = 10%

Incinerator Lifetime = 10 Years = $N_N$

Capital Recovery Factor = $\frac{i\,(1+i)^N}{(1+i)^N-1}$

= 0.163 of Total Installed Capital

Taxes, Insurance and Administrative Charges Factor = 0.04 of Total Installed Capital

Overall Capital Charges Factor = 0.203 of Total Installed Capital

Overall Taxes and Maintenance Factor = 0.10 of Total Installed Capital

[a] Fifty percent liquid solution of caustic soda.

[b] Memo to Hurley, E., EEA, from Galloway, J., EEA. January 13, 1981. Average capacity utilization for the air oxidation industry.

TABLE B-6. SAMPLE CALCULATION FOR INCINERATOR COSTING

| | |
|---|---|
| 1. Capital Cost ($10^3$ $) | = (# incinerators) x (incinerator capital cost per unit) x (escalation factor)<br>= (# incinerators) x (803.11 - 40.0 + 12.83 x (flow/0.95)$^{0.88}$) x escalation factor<br>= 1 x (803.11 - 40.0 + 12.83 (14.2)$^{0.88}$) x 0.9<br>= 806.1 |
| 2. Additional Duct Cost ($10^3$ $) | = (length) x (cost per unit length) x (escalation factor) x (installation factor) = 350 ft. x ((((500 ft$^3$/min) x 4 ÷ 2000 ÷ 3.1412))$^{0.5}$ x 12 x 1.37 ÷ 1.76) x 1.088 x 1.087 ÷ 1000<br>= 3.111 |
| 3. Pipe Rack Cost ($10^3$ $) | = (length) x (cost per unit length) x (installation factor) x (pipe rack escalation factor) x (retrofit correction factor) ÷ 1000 = 250 ft. + (2 additional vents x 100 ft./vent) x $32.045/ft. x 1.087 x 0.746 x 1.0 ÷ 1000<br>= 11.693 |
| 4. Total Installed Total Capital | = Capital cost ($10^3$ $) + extra duct cost ($10^3$ $) + pipe rack cost ($10^3$ $)<br>= 806.1 + 3.111 + 11.693<br>= 820.9 |

(continued)



BEST COPY AVAILABLE

TABLE B-6. (Continued)

| | |
|---|---|
| 5. Natural Gas Use (MJ/yr) | = (minutes per year) x (supplemental gas required per minute)<br>= 0.5256 $10^6$ min/yr x $G_0$ + flow x ($G_1$ + $G_2$ x $H_T$)<br>= 0.5256 $10^6$ min/yr x (3.96) x (4.53 - 0.985 x 1.49) MJ/min)<br>= 6.37 MJ/yr |
| 6. Natural Gas Cost ($10^3$ $) | = Natural gas price ($/$10^9$ J) x natural gas use (MJ/yr)<br>= $4.16/GJ x 6.37 MJ<br>= 26.2 |
| 7. Operating Labor Cost ($10^3$ $) | = Wage ($/hr) x labor factor (hr/yr) ÷ 1000<br>= $8.50/hr x 2400 hrs<br>= 20.4 |
| 8. Supervisory Labor Cost ($10^3$ $) | = Operating labor cost ($10^3$/yr) x 0.15<br>= 20.4 ($10^3$ $/yr) x 0.15<br>= 3.06 |
| 9. Maintenance Labor Cost ($10^3$ $) | = Installed capital cost ($10^3$ $) x 0.03<br>= 820.9 ($10^3$) $ x 0.03<br>= 24.63 |
| 10. Overhead Labor Cost ($10^3$ $) | = Operating labor cost ($10^3$ $) + supervisory labor cost ($10^3$ $) + maintenance labor cost ($10^3$ $) x 0.80<br>= (20.40 + 3.06 + 24.63) x 0.80<br>= 38.47 |

(continued)

BEST COPY AVAILABLE

TABLE B-6. (Continued)

| | |
|---|---|
| 11. Total Labor Cost ($10^3$ $) | = Operating labor cost ($10^3$ $) + supervisory labor cost ($10^3$ $) + maintenance labor cost ($10^3$ $) + overhead labor cost ($10^3$ $)<br>= 20.4 + 3.06 + 24.63 + 38.47<br>= 86.56 |
| 12. Electricity Cost ($10^3$ $) | = (electricity price) x (pressure drop) x (flow rate) x (flue gas:offgas ratio) x (fan equation conversion factor) x (# of hours per year) ÷ fan efficiency ÷ 1000<br>= 0.0279 ($/KWhr) x 22 in. x 3.96 scm/min x 2.9 x 0.004136 (KW/scmin.) ÷ 0.6 ÷ 1000 ($/$10^3$ $)<br>= 0.426 |
| 13. Quench Water Cost ($10^3$ $) | = (quench water price) x (flow rate) x (flue gas:offgas ratio) x (water required per unit flow) x (minutes per year) ÷ 1000<br>= 0.22 ($ $10^3$ gal) x 3.96 (scm/min) x 2.9 x 1.68 x $10^{-5}$ ($10^3$ gal/scm) x 0.5256 ($10^6$ min/yr) ÷ 1000 ($/$10^3$ $)<br>= 0.0223 |

(continued)



BEST COPY AVAILABLE

TABLE B-6. (Continued)

| | |
|---|---|
| 14. Scrubbing Water Cost ($10^3$ $) | = (scrub water price) x (flow rate) x (flue gas:offgas ratio) x (chlorine content of flue gas) x (water required per unit chlorine) x (# of hours per year)<br>= 0.22 ($\$10^3$ gal) x 3.96 (scm/min) x 35.314 scf/scm x 2.9 x 0.0487 (lb/hr chlorine)/(scf/min flue gas) x 0.0192 ($10^3$ gal/lb chlorine) x 8760 (hr/yr) ÷ 1000<br>= 0.73 |
| 15. Neutralization Cost ($10^3$ $) | = (caustic cost) x (flow rate) x (flue gas:offgas ratio) x (chlorine content of flue gas) x (caustic requirement per unit chlorine) x (# of hours per year) ÷ 1000<br>= 0.0436 ($/lb NaOH) x 3.96 (scm/min) x 35.314 scf/scm x 2.9 x 0.0487 (lb/hr chlorine)/(scf/min flue gas) x 1.14 (lb NaOH/lb chlorine) x 8760 (hr/yr) ÷ 1000<br>= 8.6 |
| 16. Heat Recovery Credit | = 0 (for all streams <700 scfm) |

(continued)

BEST COPY AVAILABLE

TABLE B-6. (Continued)

| | |
|---|---|
| 17. Taxes, Insurance, and Maintenance Cost ($10^3$ $) | = (installed capital cost) x (taxes, insurance, and administrative charges factor + maintenance labor factor)<br>= 820.9 ($10^3$ $) x (0.04 + 0.03)<br>= 57.46 |
| 18. Annual Operating Cost ($10^3$ $) | = (TI&M cost) + (gas cost) + total labor cost) + (electricity cost) + (quench cost) + (scrubbing cost) + (scrubbing cost) + (caustic cost)<br>= 57.46 + 26.20 + 86.56 + 0.426 + 0.0223 + 0.73 + 8.6<br>= 180.90 |
| 19. Annualized Cost ($10^3$ $) | = (operating cost) + (capital recovery factor x total installed capital cost)<br>= 180.0 + (.163 x 820.9)<br>= 313.8 |
| 20. Annual Emissions (Mg/yr) | = (hourly emissions) x 365 (days/yr) x 24 (hrs/day) x (Mg/$10^3$ kg)<br>= 15.86 kg/hr x 365 (days/yr) x 24 (hrs/day) x 1 (Mg/$10^3$ kg)<br>= 138.9 |
| 21. Annual Emission Reduction (Mg/yr) | = (annual emissions) x 0.98<br>= 138.9 x 0.98 (MC) = 136.1 (MC)<br>= 349.6 (VOC) |

(continued)



BEST COPY AVAILABLE

TABLE B-6. (Continued)

| | |
|---|---|
| 22. Cost Effectiveness ($/Mg) | = (annual cost) ÷ (annual emission reduction)<br>= 313.8 ($10^3$ $) ÷ 136.1 Mg (MC<br>= 2305/Mg (MC)<br>= 313.8 ($10^3$ $) ÷ 349.6 Mg (VOC)<br>= $898/Mg |
| 23. Updated Cost-Effectiveness Values ($/Mg) | = 2305 ($/Mg) x 1.486 = $3420/Mg (MC)<br>= 898 ($/Mg) x 1.486 = $1330/Mg (VOC) |



BEST COPY AVAILABLE

TABLE B-7. COST CONVERSION FACTORS
FOR INCINERATOR COMPONENTS

| Original Cost Component | Original Conversion Year | Conversion Year | Conversion Factor |
|---|---|---|---|
| Incinerator | 1979 | 1978 | 0.900 |
| Pipe Rack | 1982 | 1978 | 0.745 |
| Duct Work | 1977 | 1978 | 1.088 |
| Annualized Costs | 1978 | 1984 | 1.486 |



BEST COPY AVAILABLE

A sample calculation for incinerator costing is shown in Table B-6. The calculation is based on representative vent stream parameters for a typical MC production facility. The cost estimate was initially calculated in 1978 dollars and then was updated to 1984 dollars using the annualized cost escalation factor shown in Table B-7.

## B.2 COST CALCULATIONS FOR INSTALLING INTERNAL FLOATING ROOFS IN FIXED ROOF TANKS

The following equations were used to calculate the capital and annualized cost for the installation of a mild steel welded contact internal floating roof to a fixed roof storge tank. This internal floating roof utilizes both primary (constructed of Teflon$^{R}$) and secondary (constructed of Viton$^{R}$) seals.

### B.2.1 Capital Cost (4th Quarter 1982 Dollars)

1. Degassing Cost[4]

Cost = $\$130.8\ V^{0.5132}$ or \$1,000, whichever is greater where V = tank volume in cubic meters.

2. Estimated Installation Cost[4]

a. Basic cost of roof and primary seal:
Cost = (1.91 + 2.54 x D) x \$1,000 + (\$204 x D)
D = tank diameter in meters

(The \$204 x D cost reflects the additional cost of using Teflon$^{R}$ coated fiberglass to protect against MC attack versus the standard polyurethane coating)[5]

b. Additional cost of adding secondary seal:[4]

Cost = \$580 x D



BEST COPY AVAILABLE

(The $580 x D cost reflects using a Viton[R] coating material for the secondary seal)

3. Door Sheet Opening Cost[6]

Cost = $1,300

Total capital cost (primary seal) = degassing cost + estimated installed cost (2a) + door sheet opening cost.

Total capital cost (primary + secondary seals) = degassing costs + estimated installed cost (2a,b) + door sheet opening cost.

B.2.2 Annual Cost (4th Quarter 1982 Dollars)

1. Taxes, insurance, and administration -- 4% of capital cost (based on 10 percent interest rate and 10 year equipment life)

2. Maintenance -- 5% of capital cost

3. Inspection -- 1% of capital cost

4. Capital recovery factor -- 16.275% of capital cost

Total annual cost = [26.275% of capital cost]

B.2.3 MC/VOC Reduction

1. Emissions calculated for fixed roof tanks using AP-42 formulas.

2. Emissions calculated for internal floating roof tanks using AP-42 formulas.
   a. Liquid mounted primary seal only
   b. Liquid primary and secondary seal



BEST COPY AVAILABLE

3. Emissions from fixed roof tank - emissions from internal floating roof tank = VOC emission reduction

MC emission reduction = VOC emission reduction x percentage of MC in stored material

B.2.4 Recovery Credits (4th Quarter 1984 Dollars)

Credits = (MC emission reduction) x (4th Quarter 1984 MC market value ($485/Mg)) + [(VOC emission reduction-MC emission reduction) x (4th Quarter 1984 VOC market value ($330/Mg))].

B.2.5 Net Annual Cost

Before annual cost can be calculated, all costing data is converted to 1984 dollars using Chemical Engineering Economic Indicators)

Cost = annual cost (4th quarter 1984 dollars) - VOC recovery credits (4th Quarter 1984 dollars)

B.2.6 Cost Effectiveness

MC cost effectiveness = net annual cost/MC emission reduction (Mg)

VOC cost effectiveness = net annual cost/VOC emission reduction (Mg)

B.3 COST CALCULATIONS FOR INSTALLATION OF REFRIGERATED CONDENSERS TO CONTROL STORAGE AND LOADING EMISSIONS

This section presents methods used to estimate costs for controlling storage and loading emission by condensation. Based on Section 114 letter responses, 85% control efficiency was assumed for storage applications and 90% control efficiency was assumed for loading applications.



BEST COPY AVAILABLE

Costs were estimated using methods in Capital and Operating Costs of Selected Air Pollution Control Systems. Based on conversation with one chloroflorocarbon producer, one carbon tetrachloride producer and Section 114 response the following assumptions were made.

| Source of Stored Material | Filling Rate (gpm) | Gas Flow Rate to condenser (scfm) |
|---|---|---|
| Production | 200 | 27 |
| Ship | 1800 | 240 |
| Barge | 800 | 110 |
| Rail Car | 200 | 27 |
| Tank Truck | 200 | 27 |

B.3.1 Capital Cost (4th Quarter 1984 Dollars)

Capital Cost (1977$) = [0.27 x Flow (scfm) + 34] x $1000^3$

Installed Cost = Capital Cost x $1.74^2$

4th Quarter 84 Installed Cost = Installed Cost x $\frac{324.4}{210.3}$

CE Index

December 77 = 210.3
November 84 = 324.4

B.3.2 Annual Cost

1. Taxes, insurance, and administration -- 4 percent of capital
2. Maintenance -- 5 percent of capital
3. Inspection -- 1 percent of capital
4. Capital Recovery Factor -- 16.275 percent of capital

Annualized capital cost = Installed capital cost x .26275

Electricity cost = [(0.35) x Flow (scfm) + 10] x kw cost

kw cost = $0.522/kw

B.3.3 MC/VOC Emission Reduction

1. Calculate fixed roof storage emission using AP-42 and storage tank data

MC emission = FR emissions x % MC in stored material
VOC emission = Total FR emissions



BEST COPY AVAILABLE

2. MC emission red = MC emissions x .85
VOC emission red = VOC emissions x .85

B.3.4 Recovery Credit

Credits = (MC emission reduction) x (4th Quarter 1984 MC market value ($485/MG)) + [(VOC emission reduction-MC emission reduction) x (4th Quarter 1984 VOC market value ($330/MG))].

B.3.5 Net Annual Cost

Net annual cost = (total annual cost) - (recovery credit)

B.3.6 Cost Effectiveness

MC C/E = Net annual cost ÷ MC emission red
VOC C/E = Net annual cost ÷ VOC emission red

B.4 SAMPLE CALCULATIONS FOR EQUIPMENT LEAK CONTROL COSTS

To calculate the cost for the implementation of technologies to control equipment leak emissions, the specific control techniques, removal efficiencies and capital/annualized costs per component are given in Table B-8. The equipment leak emission sources costed are pump seals, compressors, flanges, valves, pressure relief devices, sample connections, and open ended lines.

Capital cost per emission source: (No. of components) x (capital cost per component)

Total capital cost per plant: ÷ [capital cost per emission source] annual cost per emission source: (No. of components) x (annual cost per component)

MC emission reduction per emission source: (current MC emission) x (percent reduction)

Total MC emission reduction per plant: ÷ [MC emission reduction per emission source]

BEST COPY AVAILABLE

TABLE B-8. CONTROL TECHNIQUES AND COST FOR[a] CONTROLLING EQUIPMENT LEAK EMISSION SOURCES
(4th Quarter 1984 Dollars)

| Equipment Type (Emission Source) | Control Techniques | Percent Reduction[5] | Capital[6] Cost $/Component | Annualized[6] Cost $/Component |
|---|---|---|---|---|
| 1. Pump seals | | | | |
| - Packed | Monthly LDAR | 61 | 0 | 370 |
| - Mechanical | Monthly LDAR | 61 | 0 | 370 |
| - Double Mechanical | N/A | N/A | N/A | N/A |
| 2. Compressors | Vent to combustion device | 100 | 10,200 | 2,580 |
| 3. Flanges | None Available | N/A | N/A | N/A |
| 4. Valves | | | | |
| - Gas | Monthly LDAR | 73 | 0 | 20 |
| - Liquid | Monthly LDAR | 59 | 0 | 20 |
| 5. Pressure Relief devices | | | | |
| - Gas | O-Ring | 100 | 310 | 80 |
| - Liquid | N/A | N/A | N/A | N/A |
| 6. Sample Connections | | | | |
| - Gas | Closed-purge sampling systems | 100 | 670 | 170 |
| - Liquid | Closed-purge sampling systems | 100 | 670 | 170 |
| 7. Open Ended Lines | | | | |
| - Gas | Caps on open ends | 100 | 70 | 20 |
| - Liquid | Caps on open ends | 100 | 70 | 20 |

[a]Updated to 4th quarter 1984 using CE index.





BEST COPY AVAILABLE

VOC emission reduction per emission source: (current VOC emission) x (percent reduction)

Total VOC emission reduction per plant: $\Sigma$ [VOC emission reduction per emission source i]

Recovery credit per emission source: (MC emission reduction per source i) x (4th Quarter 1984 MC market value ($485/Mg)) + [(VOC emission reduction per source i - MC emission reduction per source i) x (4th Quarter 1984 VOC market value ($330/Mg))].

Recovery credit per plant: The summation of recovery credits per emission source.

Net annual cost (MC) per emission source: (annual cost per emission source) minus (recovery credits per emission source).

Net annual cost (MC) per plant: (total annual cost per plant) minus (total recovery credits per plant).

Net annual cost (VOC) per emission source: (annual cost per emission source) minus (recovery credits per emission source).

Net annual cost (VOC) per plant: (total annual cost per plant) minus (total recovery credits per plant).

Cost effectiveness for controlling MC emissions per emission source: (net annual cost (MC) per emission source) $\div$ (MC emission reduction per emission source).

Cost effectiveness for controlling MC emissions per plant: (net annual cost (MC) per plant) $\div$ (MC emission reduction per plant).



BEST COPY AVAILABLE

Cost effectiveness for controlling VOC emissions per emission source: (net annual cost (VOC) per emission source) ÷ (emission reduction per emission source).

Cost effectiveness for controlling VOC emissions per plant: (net annual cost (VOC) per plant) ÷ (emission reduction per plant).



BEST COPY AVAILABLE

## B-5 REFERENCES


1. U.S. Environmental Protection Agency. Control of Volatile Organic Compound Emissions from Air Oxidation Processes in Synthetic Organic Chemical Manufacturing Industry. Research Triangle Park, N.C. Publication No. EPA-450/3-84-015. December 1984. p. 510.

2. Memo from Pandullo, R. F. and I. A. McKenzie, Radian Corporation, to Air Oxidation Processes and Distillation Operations Project Filtes. May 3, 1985. 20p. Revision to the Incinerator Costing Procedures Used for the Proposed Air Oxidation and Distillation NSPS.

3. Neveril, R. B. (GARD, Inc.). Capital and Operating Costs of Selected Air Pollution Control Systems. (Prepared for the U.S. Environmental Protection Agency.) Research Triangle Park, N.C. Publication No. EPA-450/5-80-002. December 1978. pp. 5-39 through 5-49 and 5-65 through 5-71.

4. Atkinson, R. D. (MRI) et al. Source Assessment of Ethylene Dichloride Emissions. (Prepared for the U.S. Environmental Protection Agency.) Research Triangle Park, N.C. EPA Contract No. 68-02-3817. September 1984.

5. U.S. Environmental Protection Agency. Fugitive Emission Sources of Organic Compounds - Additional Information Document. Research Triangle Park, N.C. Publication No. EPA-450/3-82-010. April 1982. p. 1-4.

6. U.S. Environmental Protection Agency. Benzene Fugitive Emissions - Background Information for Promulgated Standards. Research Triangle Park, N.C. Publication No. EPA-450/3-80-032b. June 1982. Appendix A.


BEST COPY AVAILABLE

APPENDIX C

# SUMMARY OF EXISTING STATE AND FEDERAL REGULATIONS AFFECTING METHYLENE CHLORIDE EMISSION SOURCES

## C.1 EXISTING STATE REGULATIONS

### C.1.1 Introduction

Methylene chloride (MC) emissions originate from several industrial sources. These sources include producers of MC, sources that use MC as a chemical intermediate, and sources that store MC. These emissions can be characterized as either process, equipment leak, product storage tank, or loading and handling emissions.

There are a number of different regulations at the State level that limit volatile organic compound (VOC) emissions. VOC emissions in nonattainment areas (areas that have not achieved the ambient air quality standards for ozone) are normally controlled by the States' RACT program. VOC emissions in areas designated as attainment or unclassified for ozone are controlled by Prevention of Significant Deterioration (PSD) regulations. MC is excluded from many of these state regulations due to its low photochemical reactivity. However, eleven States that have regulations controlling VOC emissions do not specifically exclude MC from the applicable regulations. These States are Alabama, Kentucky, Massachusetts, Maryland, Michigan, Nevada, New Jersey, Pennsylvania, Rhode Island, Tennessee, and Wisconsin.

### C.1.2 General State VOC Regulations for Solvent Use

In addition to the RACT and PSD programs, 12 States (including the District of Columbia) have general VOC regulations that limit emissions of photochemically reactive solvents. Table C-1 presents a list of the States that have adopted a general VOC solvent usage regulation and the emission limits established by each State. These regulations affect volatile organic solvents found to be photochemically reactive and usually require 85 percent reduction in VOC emissions. Methylene chloride is excluded from regulation by all of these States with the exception of Maryland and Rhode Island.



BEST COPY AVAILABLE

TABLE C-1. GENERAL STATE VOC REGULATIONS FOR PHOTOCHEMICAL SOLVENTS[1]

| State | Emission Reduction (%) |
|---|---|
| California | 85 |
| Colorado | 85 |
| Connecticut | 85 |
| District of Columbia | 85 |
| Illinois | 85 |
| Indiana | 85 |
| Louisiana | 90 |
| Maryland | 85[2] |
| North Carolina | 85 |
| North Dakota | 85 |
| Rhode Island | 85[3] |
| Virginia | 85 |

[1]These regulations exclude MC with the exception of Maryland and Rhode Island.
[2]Applies to sources in nonattainment areas only.
[3]Applies to sources emitting less than 100 tons/year, larger sources must comply with RACT.

BEST COPY AVAILABLE

C.1.3 Prevention of Significant Deterioration Regulations

PSD regulations control VOC emissions from major sources in areas classified as attainment for ozone. Under PSD regulations, a chemical production plant must seek a PSD permit if it is: (1) a new source with emissions or potential emissions considered major (100 tons/yr); (2) a major increase in emissions or potential emissions (100 tons/yr) at an existing minor source; or (3) a significant increase in emissions or potential emissions (40 tons/yr) at an existing major source. Emission control levels for PSD are established during the State's review of the PSD permit application prepared for the emission source.

C.1.4 State Regulations Affecting Chemical Production

In addition to the general discussion of State regulations concerning MC emission sources, a more indepth review was performed for States in which MC production facilities and facilities using MC in production are located. Only two States, Michigan and Pennsylvania, had regulations controlling MC emissions from chemical production facilities. These regulations are presented in Table C-2. All applicable MC emissions must be controlled under these regulations due to the 6.75 psia vapor pressure of MC. Other VOC emissions at these facilities may also be controlled.

C.2 EXISTING FEDERAL REGULATIONS

Several VOC NSPS and a NESHAP have been developed that could affect new and some existing sources of MC emissions. A summary and the current status of each of these standards are presented in Table C-3.

BEST COPY AVAILABLE

TABLE C-2. STATE REGULATIONS AFFECTING CHEMICAL PRODUCTION FACILITIES EMITTING METHYLENE CHLORIDE

| State | Source | Regulation |
|---|---|---|
| Michigan[1] | Storage tanks >40,000 gal true vapor pressure >1.5 <11.0 (existing sources) | - Pressure tank or<br>- Floating cover with closure seal or seals<br>- Vapor recovery system capable of 90 percent recovery |
| | Storage of organic compounds having a true vapor pressure ≥11 psia in existing vessels of >40,000 gallons | - Pressure tank capable of maintaining working pressures sufficient to prevent organic vapor or gas loss to atmosphere<br>- Vapor recovery system which recovers >90% by weight of uncontrolled organic vapor<br>- All openings shall be equipped with covers, lids, or seals |
| | VOC loading facilities handling ≥5,000,000 gal/year of >1.5 psia VOC | - submerged fill pipes in ozone attainment areas |
| Pennsylvania[1] | Above ground storage tanks <40,000 gal and >2,000 gal true vapor pressure >1.5 psia | - Pressure tank or<br>- External or internal floating roof is true vapor pressure ≤11.0 psia or<br>- Vapor recovery system capable of 80 percent recovery |
| | Storage tanks ≤40,000 gal true vapor pressure >1.5 psia | - Pressure relief valves |

[1]Environment Reporter, State Air Laws. Washington, D. C. Bureau of National Affairs.

BEST COPY AVAILABLE

TABLE C-3. SUMMARY OF FEDERAL REGULATIONS AFFECTING VOLATILE ORGANIC COMPOUND EMITTING SOURCES

| Source | Proposed | Promulgated |
|---|---|---|
| SOCMI Equipment Leaks (Fugitive) NSPS | 01/05/81 | 10/18/83 |
| VOL Storage Vessels NSPS | 10/84 | |
| SOCMI Air Oxidation NSPS | 10/21/83 | |
| SOCMI Distillation Operations NSPS | 12/30/83 | |
| SOCMI Reactor Processes NSPS | draft | |



BEST COPY AVAILABLE

APPENDIX D

MATERIAL BALANCE FOR MC EMISSIONS OPERATIONS

D.1 MATERIAL BALANCE

(1) - Fraction of degreasing use of MC in cold cleaning = 0.67

Fraction of degreasing use of MC in vapor degreasing = 0.33

- Emission factors:

  - cold cleaning: 0.43 kg/kg used
  - open top degreasing: 0.78 kg/kg used
  - conveyorized degreasing: 0.85 kg/kg used

- Assuming methylene chloride usage in vapor degreasing is divided equally between open top and conveyorized vapor degreasing, a weighted average emission factor is calculated as follows:

  $(0.67)(0.43) + (0.165)(0.78) + (0.165)(0.85) = 0.56$ kg/kg used

(2) - For every kg of fresh MC used, 0.56 kg is emitted. Assume all of the remaining 0.44 kg is sent to solvent recovery.

- Estimate that 75 percent of all solvent sent to recovery is recycled.

- Calculate emissions as follows:






BEST COPY AVAILABLE

$x = 0.75\ (0.44 + 0.44x)$

$x = 0.49$ (Amount of recycled MC used per kg of fresh MC used)

$0.56x = 0.27$ (Amount of recycled MC emitted per kg of fresh MC used)

Total MC emitted per kg of fresh MC used $= 0.56 + 0.27$

$= 0.83$ kg



BEST COPY AVAILABLE

## D.2 NATIONAL EMISSION REDUCTION CALCULATIONS

National emission reduction can be calculated by estimating the amount of solvent emitted by the degreasers that are presently uncontrolled and applying a control efficiency to these emissions. The emission factors presented in Section D.1 for cold cleaners, open top vapor degreasers, and conveyorized vapor degreasers are overall emission factors representing the average emission factor from controlled and uncontrolled degreasers. An uncontrolled degreaser emission factor was developed for the three types of degreasers so that the national emissions from uncontrolled degreasers could be calculated. An uncontrolled degreaser is considered to be one that does not have the most stringent control techniques for its degreaser type. These control techniques were described in Chapter 4. For example, the most stringent control technique for an open top vapor degreaser is a carbon adsorber. Therefore, an uncontrolled open top vapor degreaser is one that does not control emissions with a carbon adsorber. In reality, degreasers have levels of controls ranging from no control techniques to the most stringent control techniques available. Therefore, defining an uncontrolled degreaser as one that does not have the most stringent control techniques for its degreaser type results in an overestimate of the achievable emission reduction.

Information on the number of uncontrolled versus controlled degreasers was obtained from industry contacts.[1,2] These are as follows:

- Ratio of uncontrolled/controlled cold cleaners = 0.65/0.35
- Ratio of uncontrolled/controlled open top vapor degreasers = 0.99/0.01
- Ratio of uncontrolled/controlled conveyorized vapor degreasers = 0.95/0.05

The uncontrolled degreaser emission factors were then calculated according to the following equation:



BEST COPY AVAILABLE

$(a)x + (b)(c)x = y$

where:

y = overall degreaser emission factor, kg/kg solvent consumed

a = fraction of uncontrolled degreasers

x = uncontrolled degreaser emission factor, kg/kg solvent consumed

b = fraction of controlled degreasers

c = 1 - achievable emission reduction

Since emission reduction is calculated only for presently uncontrolled degreasers, the total solvent consumption must be adjusted to include only the solvent used in uncontrolled degreasers. The adjusted solvent consumption levels were calculated according to the equation:

(1) $z = (s)(t)(u)$

where:

z = total solvent consumed by uncontrolled degreasers by degreaser type, Mg/yr

s = total solvent consumption by all degreasers (fresh solvent plus recycled solvent = total emissions divided by emission factor for fresh MC), Mg/yr

t = fraction of consumption by degreaser type

u = fraction of uncontrolled degreasers by degreaser type

The uncontrolled emission factors were applied to the total amount consumed by uncontrolled sources within each degreaser type to yield the national uncontrolled emissions for the degreaser type. Applying the control efficiency to the national uncontrolled emissions gives the emission reduction for the degreaser type. These calculations proceed according to the equation:

(2) $r = (z)(x)(v)$

where:

BEST COPY AVAILABLE

157

r = emission reduction for degreaser type, Mg/yr

z = total solvent consumed by uncontrolled degreasers by degreaser type, Mg/yr

x = uncontrolled degreaser emission factor (kg/kg solvent consumed)

v = achievable emission reduction

Calculations:

I. Cold Cleaners

(1) $y = (a)x + (b)(c)x$

$0.43 = (0.65)x + (0.35)(1-0.35)x$

$x = 0.49$

(2) $z = (s)(t)(u)$

$z = \frac{17,700}{0.56} (0.67)(0.65)$

$z = 13,800$ Mg/yr

(3) $r = (z)(x)(v)$

$r = 13,800\ (0.49)(0.35)$

$r = 2,360$ Mg/yr

II. Open Top Vapor Degreasers

(1) $y = (a)x + (b)(c)x$

$0.78 = (0.99)x + (0.01)(1-0.44)x$

$x = 0.78$

(2) $z = (s)(t)(u)$

$z = \frac{17,700}{0.56} (0.165)(0.99)$

$z = 5,160$ Mg/yr

(3) $r = (z)(x)(v)$

$r = (5,160)(0.78)(0.44)$

$r = 1,770$ Mg/yr



BEST COPY AVAILABLE

III. Conveyorized Vapor Degreasers

(1) $y = (a)x + (b)(c)x$

$0.85 = (0.95)x + (0.05)(1-0.57)x$

$x = 0.87$

(2) $z = (s)(t)(u)$

$z = \frac{17,700}{0.56} (0.165)(0.95)$

$z = 4,950$ Mg/yr

(3) $r = (z)(x)(v)$

$r = (4,950)(0.87)(0.57)$

$r = 2,460$ Mg/yr

D.3 PHOTORESIST STRIPPING EMISSION FACTOR

1. Emission factor = 0.25 kg/kg used

2. For every kg of fresh MC used, 0.25 is emitted. Assume remaining .75 is sent to solvent recovery.

   - Estimate that 75 percent of all solvent sent to recovery is recycled

     $x = 0.75 (0.75 + 0.75x)$

     where x = recycled solvent

     x = 1.29 (amount recycled MC used per kg of fresh MC used)

     0.25x = 0.32 (amount recycled MC emitted per kg fresh MC used)

3. Total MC emitted per kg fresh MC used

   = 0.25 + 0.32

   = 0.57



BEST COPY AVAILABLE

## D.4 REFERENCES


1. Telecon. Murphy, P.V., Radian Corporation, with Pokorng, J., Baron-Blakeslee, Inc. August 9, 1985. Information on control devices for degreasers.

2. Telecon. Murphy, P.V., Radian Corporation, with Barr, F., Graymills Corp. August 9, 1985. Information on control devices for cold cleaners.





BEST COPY AVAILABLE

APPENDIX E

EMISSIONS FROM DISTRIBUTION FACILITIES

(1) Estimate the quantity going through distribution (storage)

1983 production = 530 MM lbs

Assume 100 percent goes through distribution channels

(2) Estimate the number of storage tanks nationwide

- Assume the average tanks size is 10,000 gallons
- Assume the average turnover time is 3 weeks

$$\text{Number of tanks} = 356 \text{ MM lbs} \left(\frac{\text{gal}}{11.1 \text{ lb}}\right)\left(\frac{1 \text{ tank}}{10{,}000 \text{ gal} \times 17}\right) = 280 \text{ tanks}$$

(3) Estimate storage emissions (fixed roof tanks)

Breathing Loss

$$L_B = 1.02 \times 10^{-5} M_v \left(\frac{P}{14.7-P}\right)^{0.68} D^{1.73} H^{0.51} T^{0.5} F_p C K_x$$

$$L_B = 1.02 \times 10^{-5} (85)\left(\frac{5}{14.7-5}\right)^{0.68} (10)^{1.73} (9)^{0.51} (1.15)(0.5)(1.0)$$

$L_B = 0.23$ Mg/yr

Working Loss

$$L_W = 1.09 \times 10^{-8} M_v P V N K_n K_c$$

$$L_W = 1.09 \times 10^{-8} (85)(5)(10{,}000)(17)(1)(1)$$

$L_W = 0.79$ Mg/yr

Total Loss

$L_T = L_B + L_W = 1.0$ Mg/yr per tank

Total nationwide storage emissions = (1.0)(280) = 280 Mg/yr



BEST COPY AVAILABLE

where:

$M_v$ = molecular weight of product vapor (lb/lb mole)

P = true vapor pressure of product (psia)

D = tank diameter (ft)

H = average vapor space height (ft)

T = average diurnal temperature change (°F)

$F_p$ = paint factor (dimensionless); 1.0 for clean white paint

C = tank diameter factor (dimensionless):

for diameter $\geq$ 30 feet, C = 1

for diameter < 30 feet, $C = 0.771D - 0.013D^2 - 0.1334$

$K_c$ = product factor (dimensionless) = 1.0 for VOL

V = tank capacity (gal)

$K_n$ = turnover factor (dimensionless):

for turnovers > 36, $K_n = \frac{180 + N}{6N}$

for turnovers $\leq$ 36, $K_n = 1$

(4) Estimate container filling emissions

Loading Loss

$$L_L = 12.46 \frac{S\ T\ M}{R}$$

where: S = saturation factor (0.50 for submerged fill and 1.45 for splash fill)

T = True vapor pressure, psia

M = Molecular weight

R = Temperature, °R



BEST COPY AVAILABLE

Assume 50 percent splash filling (S = 1.0)

$S = (0.5)(0.5) + (0.5)(1.45) = 1.0$

$$L_L = 12.46\left(\frac{(1.0)(5)(85)}{530}\right) = 10.0 \text{ lb}/10^3 \text{ gal}$$

$$= 4.5 \text{ lb}/10^3 \text{ gal}$$

$$530\ 10^6 \text{ lb}\left(\frac{\text{gal}}{11.1 \text{ lb}}\right)\left(\frac{4.5 \text{ kg}}{10^3 \text{ gal}}\right) = 210 \text{ Mg/yr}$$



BEST COPY AVAILABLE

**TECHNICAL REPORT DATA**
*(Please read Instructions on the reverse before completing)*

| 1. REPORT NO. | 2. | 3. RECIPIENT'S ACCESSION NO. |
|---|---|---|
| EPA-450/3-85-015 | | |

**4. TITLE AND SUBTITLE**
Survey of Methylene Chloride Emission Sources

**5. REPORT DATE**
June 1985

**6. PERFORMING ORGANIZATION CODE**

**7. AUTHOR(S)**
R.F. Pandullo, L.E. Kincaid, P.V. Murphy, S.A. Shareef

**8. PERFORMING ORGANIZATION REPORT NO.**

Radian Corporation - Post Office Box 13000
Research Triangle Park, North Carolina 27709

**9. PERFORMING ORGANIZATION NAME AND ADDRESS**
Office of Air Quality Planning and Standards
Environmental Protection Agency
Research Triangle Park, North Carolina

**10. PROGRAM ELEMENT NO.**

**11. CONTRACT/GRANT NO.**
EPA Contract 68-02-3816

**12. SPONSORING AGENCY NAME AND ADDRESS**
DAA for Air Quality Planning and Standards
Office of Air and Radiation
U.S. Environmental Protection Agency
Research Triangle Park, North Carolina 27711

**13. TYPE OF REPORT AND PERIOD COVERED**

**14. SPONSORING AGENCY CODE**
EPA/200/04

**15. SUPPLEMENTARY NOTES**

**16. ABSTRACT**
The potential health impact of methylene chloride emissions is being investigated. This document contains information on the sources of methylene chloride emissions, current emission levels, control methods that could be used to reduce methylene chloride emissions, and cost estimates for employing controls.

**17. KEY WORDS AND DOCUMENT ANALYSIS**

| a. DESCRIPTORS | b. IDENTIFIERS/OPEN ENDED TERMS | c. COSATI Field/Group |
|---|---|---|
| Air Pollution<br>Pollution Control<br>Synthetic Organic Chemical Manufacturing Industry<br>Methylene Chloride<br>Dichloromethane | Air Pollution Control | 13B |

| 18. DISTRIBUTION STATEMENT | 19. SECURITY CLASS *(This Report)* | 21. NO. OF PAGES |
|---|---|---|
| Unlimited | Unclassified | 117 |
| | 20. SECURITY CLASS *(This page)* Unclassified | 22. PRICE |

EPA Form 2220-1 (Rev. 4-77) PREVIOUS EDITION IS OBSOLETE



BEST COPY AVAILABLE